

Hisense VRF



VRF AIR CONDITIONING SOLUTION

Qingdao Hisense HVAC Equipment Co., Ltd.
Hisense Tower, Qingdao, China

<http://www.hisensehvac.com> | hhexport@hisense.com | [Hisense HVAC](#) | [Hisense HVAC](#) | [Hisense HVAC](#)



★ Design and specifications are subject to change without notice. Pictures and diagrams are for reference only and are subject to change without notice.
All rights reserved by Qingdao Hisense HVAC Equipment Co., Ltd.

Reimagine your solution

Hisense VRF



Hisense SINCE 1969


Hisense is a well-known large-scale electronic information industrial group. With strong emphasis on technology and innovation, its efficient technological innovation system firmly grounds Hisense at the forefront of its peers. At present, Hisense brand family has expanded to include multiple famous brand Hisense, Toshiba, Gorenje and ASKO.

SINCE 1969

BUSINESS LAYOUT

Multimedia

- TV and Display Devices
- Internet TV Operation
- Mobile Communication Devices
- Optical Communication Devices
- Chip



Household Appliances

- Refrigerator
- Freezer
- Air-conditioner
- Washing Machine
- Kitchen Appliance



IT Smart Systems

- Smart City
- Smart Community
- Smart Transportation
- Smart Business
- Medical Electronic Devices
- Smart Home System and Service



Real Estate & Modern Services

- Real Estate
- High-end Plaza Chains
- Mould Design and Manufacturing
- Finance
- Trade



GLOBAL HISENSE SINCE 1969

Hisense has started a long-term sports marketing strategy to increase brand awareness worldwide. After the successful sponsorship of **UEFA EURO 2016 & 2020** and **FIFA WORLD CUP 2018 & 2022**, Hisense has made clear its focus on football. Hisense also is the official partner of **UEFA EURO 2024**.

2015: Team Supplier to Red Bull Racing

2016: Official Partner of UEFA EURO 2016

2018: Official Sponsor of 2018 FIFA World Cup

2020: Official Partner of UEFA EURO 2020

2022: Official Sponsor of 2022 FIFA World Cup

2024: Official Partner of UEFA EURO 2024



Hisense HVAC MANUFACTURING BASE

Qingdao Hisense HVAC Equipment Co. Ltd. is a leading manufacturer of heating, ventilation, air conditioning and other HVAC equipments, integrated with the product development, manufacturing, sales and after-sales service as a whole.

Hisense HVAC always regards product technology research and development as the most important value. With strong technological innovation capabilities, Hisense HVAC has participated in the formulation and revision of 112 national standards, industry standards and association standards, and boasts 2020 authorized patents in the field of CAC and heat pump products. With the great support of all shareholders and customers, Hisense HVAC is expected to become the leading brand in the industry.

Note: The above data is as of Dec. 31th, 2023.



266,000 m²
Manufacturing Area



40+
Production Line



6,000,000 units/year
Production Capacity



16,700 m²/70+
Laboratory



HISENSE HVAC PROFESSIONAL ENGINEERING TOOLS & SUPPORT



Beyond Your Expectation

Hisense HVAC is committed to providing a comprehensive suite of air conditioning solutions. Our services span every stage of the customer journey — from product development, pre-sales support, and quotation & purchase, to installation & commissioning, use & experience, and after-sales service. At Hisense HVAC, we consistently deliver enhanced support to ensure our customers receive unparalleled assistance.

Introducing our iCare vision, Hisense HVAC is taking a step further to elevate our technical support and after-sales service, reaffirming our commitment to customer satisfaction.

Informatization Unified HVAC Application Platform

Hisense has built the technical platform matrix which including the product selection software, CAD Hi-Design software, BIM, service platforms GCSS, GSD, GKP and so on.



Customer Oriented

Hisense HVAC boasts over 50 technical and service teams strategically positioned worldwide to offer prompt local support. With more than 5 regional spare parts centers and 20+ national spare parts warehouses, we ensure high-quality and swift spare part supply. Furthermore, R&D centers in Europe and America are currently under construction.



Reliable Service Anytime and Anywhere be with You

We've established a comprehensive all-media after-sales service system, ensuring reliable assistance anytime and anywhere.

Ability Focus on Full Cycle Training Support

The Hisense HVAC Academy was founded to offer a range of training courses for our staff and partners, with the goal of consistently enhancing the HVAC expertise of engineers, installers, and service agents.



5000m² training center in HQ
10+ training center globally
Skilled training team in HQ



5+ practice operation room
Real machine teaching
Live training online

Excellence Pursuit Enhancing User Experience Continuously

The technical and service team not only serves as the business's service provider but also champions excellent products. Hisense is actively promoting the application of Cloud AI and NFC in HVAC.



CONTENTS



25
COMFORT



41
OUTDOOR UNIT


Hi-FLEXi S Series Heat Recovery (High Efficiency)	-43
Hi-FLEXi S Series Heat Recovery (Standard)	-60
Hi-FLEXi S Series	-73
Hi-FLEXi S mavo+ Series	-86
Hi-Smart H5 Series	-98
Hi-Smart E+ L+ C+ Series	-109
Hi-Smart H Series	-115



03
RELIABILITY



167
CONTROL SYSTEM



187
ACCESSORIES

EFFICIENCY
17



FLEXIBILITY
33



INDOOR UNIT
129



4-Way Cassette Type / Mini 4-Way Cassette Type	-133
1-Way Cassette Type	-137
2-Way Cassette Type	-139
Console Type	-141
Ceiling Ducted Type (AC/DC Low-height)	-144
Ceiling Ducted Type(DC High Static Pressure)	-147
Ceiling Ducted Type (High/Low Static Pressure)	-149
Wall Mounted Type	-153
Ceiling & Floor Type	-155
Floor Concealed Type	-157
All Fresh Air Indoor Unit	-159
Heat Recovery Ventilator	-161
AHU Connection KIT	-165

Hi-FLEXi S Series Heat Recovery

Hi-FLEXi S Series


Hi-FLEXi S mavo+ Series



Hi-FLEXi X3 Series




Hi-FLEXi W Series



Hi-Smart H5 Series

Hi-Smart E+ L+ C+ Series

Hi-Smart H Series



Hisense VRF

RELIABILITY

Refrigerant Circuit

Enhanced Anti-corrosion Solution


System & Operation

Electrical & Electronics

Indoor Unit Reliability


AIR
CONDITIONING
SOLUTION

Refrigerant Circuit



Efficient energy usage


Wasted power is reduced by minimizing leakage and anti-overcompression while compressing refrigerant gas with asymmetric scroll and patented release valves.




Revolutionary HVAC compressor

Vapour injection technology

New generation scroll compressor is now patented with higher performance capability vapour injection technology, increasing capacity up to 25% compared to conventional scroll compressor with same amount of power consumed.



Enhanced oil level retaining capability




The new compressor has a greater improvement in reliability by enhancing the oil retaining capability with lower oil circulation ratio by 50%. The "oil cup" embedded in the compressor prevents compressor bearing failures due to lack of lubrication in the inner rotating components.



Oil separation and oil return

Oil separation



First-stage Oil Separation

First-stage oil separation is realized through efficient oil separation structure inside the high-pressure-chamber compressor. Only a small amount of oil is brought out of the compressor.



Second-stage Oil Separation


During second-stage oil separation, the small amount of oil discharged from compressor is separated by a large-capacity high-efficiency centrifugal oil separator, with efficiency over 99%.

Oil return

The accumulator adopts pore tube oil return technology with a built-in fine strainer, which not only ensures oil balance between compressors within one module, but also plays an important role in the oil balance between modules.

Besides this, the system implements oil-return function based on compressor frequency and corresponding operation time. The oil-return takes 60 seconds and can return to previous condition when it is finished.

In winter under heating mode, this operation is implemented without switching to cooling mode, which guarantees the heating performance.



Enhanced Anti-corrosion Solution

Hisense's complete corrosion-proof is a perfect solution in seaside and chemical factory applications (sulphide contamination occasion), providing ultimate comfort without sacrificing life span and reducing maintenance cost simultaneously.

The components from top to toe are treated with effect treatments, and the systems have acquired UL certification.



- 1 Front Panel** Galvanized steel treated with zirconium & 100 μm ~ 180 μm epoxy zinc rich primer + pure polyester paint coating.
- 2 Heat Exchanger** Black fin (with epoxy resin & hydrophilic film); Cooper fin.
- 3 Electrical Box** Galvanized steel treated with zirconium & 50 μm~120 μm pure polyester.
- 4 Fan Motor** Coated with 10 μm ~ 30 μm Acrylic Resin coating Thickness: 10 μm ~30 μm.
- 5 Top Grill**
- 6 Motor Bracket**
- 7 Protection Net**

Note

Please refer to the catalog of Hisense VRF Anti-corrosion Solution for detailed anti-corrosion treatment measures.


System & Operation



Self-diagnosis & self-protection measures

Self-diagnosis

Operation monitoring and maintenance are made simpler by having the AC unit tells you what and where is wrong with them. Alarm codes will be flashed out when an error or breakdown occurs. Extremely helpful for installers during test run and also end-users to understand what's going on. Besides alarm codes, operating status and parameters like history temperature, pressure, compressor frequency and etc are traceable on controllers and the outdoor unit, easing service maintenance and troubleshooting.



Self-protection


Hisense VRF can protect itself with algorithms embedded to make necessary protective decisions and measures by different sensor readings and parameters, including compressor protections, system protections, inverter protections and electric protections.



Smart rotative operation & triple backup operation

Smart rotative operation

Operation duties are smartly balanced in higher capacity module combinations to prevent occurrence of individual unit overworked and hence extending the overall operating life of the overall system.



Triple backup operation


Module backup operation

If one module in a combination system malfunctions, the other ones can still keep working to ensure an emergency operation until service and repair.



Compressor backup operation

In the single module system equipped with two compressors, if one compressor malfunctions, the other one can provide emergency operation. In the combined modules, if the compressor in one module goes wrong, the other modules can provide emergency operation. Thus a stable and continuous operation can be ensured thanks to the backup of compressors.




Fan backup operation

For the module equipped with two fans, if one fan breaks down, the other one won't be influenced, the module can still keep working.




Snow hood (optional)

The snow hood kit can effectively prevent heavy snow from accumulating on the top of the unit and covering the heat exchanger. Heavy snow accumulating will affect the heat exchange seriously, thus stable operation can be ensured thanks to the snow hood.



Wider operation range

Extended operation range creates wider application potential, in cooling mode the operation range is from -5°C DB to 52°C DB and in heating mode the operation range is from -25°C WB to 16.5°C WB , which adapts to extreme conditions.




Note

1. The dry temperature range of heating operation mode is from -25°C to 26°C .
2. When the temperature is in $48^{\circ}\text{C}\sim 52^{\circ}\text{C}$ and $-20^{\circ}\text{C}\sim -25^{\circ}\text{C}$, the module is in intermittent operation.
3. Please refer to the specification table of each series for detailed operation range.


Automatic Restart

Hisense indoor units are capable to restart automatically to the previous state whenever the power supply is shut off suddenly and restores immediately. When there is long power shortage, the default setting is to keep all the indoor units off when the power restores. Also there are two other settings for users' choice, recovering to the state before power failure or restarting all the indoor units.




* DIP setting is necessary for mode 2 and mode 3.

Electrical & Electronics



Patented 360° fitted refrigerant cooling technology

Hisense VRF uses refrigerant cooling technology to cool the electrical control box. It overcomes the poor heat dissipation and high ambient temperature issues to maintain efficient operation even at harsh environment. Compared with air-cooled technology, the temperature inside the electrical box can be reduced by up to 20%*. Moreover, the refrigerant cooling kit adds a temperature sensor, which could be more precise to control the refrigerant cooling temperature and ensure the whole reliability.




Note

1. * The data is based on the S mavo+ unit under low fan speed operation. 2. Temperature sensor is only available for S mavo+ series.

Insect protection design

Special design nettings are placed on insect easy-entry openings, effectively preventing unnecessary electrical component damages.



Voltage protector reserved (optional)

Too low or too high voltage can easily damage the electronic components. The new generation of top flow unit has reserved the space for assembling the voltage protector, which can be an effective solution to protect outdoor units from any voltage spikes. The power supply of outdoor unit will be automatically cut off when there is abnormal voltage, and will be restored when power supply returns to normal after 30s. Meanwhile, it's helpful for checking the phase sequence error or phase loss according to the indicator lights, convenient for commission and maintenance.



Can bear **15000** times actions



Can be installed in the factory or on site

Quality electrical and magnetism precaution measure

Air-conditioning unit produced by Hisense VRF requires strict electromagnetic protection and preventive quality assurance to not allow electromagnetic wave from other devices surrounding the unit to interfere the normal operation and function of our unit and vice versa onto other equipment. Another typical damage causes of electronic and electrical failure is sudden high external power source exerted into the electronic compositions like thunder strike during a storm. As to overcome such inevitable natural phenomenon to cause damage, 4000V sudden high voltage test is infused into the long list of electromagnetism quality test in our internationally qualified test lab.




Indoor Unit Reliability



Independent maintenance of indoor unit




To maintain the whole system's continuous operation even when there is a breakdown occurring within the system, Hisense VRF is capable to isolate the faulty unit from the others while conducting restoration and maintaining continuous operation of other units simultaneously. It's especially practical for retail shops or offices where multiple indoor units share the same system.



*Preliminary setting is unnecessary

Condensate water leakage protection

Indoor units have build-in water-leakage float switches. Alarming warnings will be displayed on controllers when condensate reaches a certain level. Save your ceiling and carpet from being soaked in time when drain pipe is clogged or drain pump breakdowns.



Effective drainage solution

High quality seals

Water could seep through anywhere as long as there is a void. Thus, Hisense utilizes the best quality sealing material to seal up gaps between the heat exchanger and drain pan, which effectively prevents condensate leakage.

Transparent drain pipe

To ease drainage inspection, Hisense indoor units adopt transparent drain hose connection. It enhances installation and maintenance, making sure drain hoses are connected securely and make blockage inspections much easier.

Hisense VRF

EFFICIENCY

Efficient Heat Exchanger

Intelligent Defrosting Logic

Steady Air Discharge



AIR
CONDITIONING
SOLUTION

Efficient Heat Exchanger

New advanced corrugated fin design

The heat exchanger of Hisense VRF adopts the new advanced corrugated fin design. With this new design, larger amount of fins can be allocated into the heat exchanger, increasing 20% heat exchange surface area maximally compared with the last generation fin and the heating capability increase 10% averagely.


Long-time stable heating performance




Two-stage subcooling

For the conventional VRF systems without the sub-coolers, the subcooling temperature is about 12.5°C with one-stage subcooling. However, Hisense VRF's 2-stage subcooling technology can realize the subcooling temperature up to 27°C, distinctly improving the cooling capacity by pushing refrigerant further beyond its condensing temperature.

Two-stage sub-cooling cycle diagram




Two-stage sub-cooling pressure enthalpy diagram





Optimized refrigerant circuit

As refrigerant flows in the system, energy will be lost due to friction and other factors naturally especially when refrigerant change phase, latent heat are lost when gas turns to liquid. Whereby, as more heat is dissipated out, higher the heat exchanger efficiency is. By making full use of heat dissipation, refrigerant flow layout is maneuvered into 2 to 1 refrigerant flow path extends liquid refrigerant's occupancy and eventually the efficiency too.


Conventional technology



2-to-1 refrigerant flow path





Traditional Refrigerant Circuit



Optimized Refrigerant Circuit

Increase the proportion of liquid refrigerant in the heat exchanger to improve heat transfer efficiency


Why does 2 to 1 refrigerant circuit is higher in efficiency?



2 to 1 refrigerant circuit: velocity is maintained same goes to the efficiency of refrigerant heat exchange.
 Conventional refrigerant circuit: Heat exchange slows down with decreased velocity. Efficiency is greatly reduced.

Intelligent Defrosting Logic

PTT defrosting mode



During cold freezing days where temperature is low and humid, water vapour in the air would solidifies into frost and any object under such environment would accumulate frost. As frosts pile up on the heat exchanger of an outdoor unit, it would need to be liquified and removed. An Intelligent Defrosting Logic could determine the perfect timing to defrost, saving unnecessary energy usage compare to conventional defrost measures, maximizing users' comfort indoors.

T Technology
Time defrosting
High energy wastage and causing low indoor comfort

TT Technology
Time and temperature defrosting
Energy wastage and might not defrosting at accurate time


PTT Technology
Pressure, time and temperature defrosting
High energy saving and efficient use of energy

Bottom anti-frosting structure

To ensure effective frost removal, heat exchanger circuit is extended to the bottom to make sure melted frost from the top does not solidify as it reaches to the condensate drain and hence enhances smooth discharge. In the meantime, the heat also extends frost formation periods whereby prolongs defrost interval.



Extended heat exchange coils, keeping the bottom warm

Smooth continuous condensate drainage



Continuous heating during defrost

The module combination design can achieve rotation defrosting among modules for decreasing indoor temperature fluctuation, so as to improve users' comfort.




Note
Only available for module combinations of Hi-FLEXi S Heat Recovery.

Steady Air Discharge


High efficiency aerodynamic axial fan

The propeller bearing which acts as the joint connecting the propeller and motor are specially treated with anti-rain corrosion treatment and propeller made of fiber glass composite is now better corrosion resistance. Fan blades are aerodynamically designed to reduce energy wastage in converting power consumed to unnecessary noise energy, reserving the energy to improve on flowrate performance and static pressure. Integration with brushless DC fan motor further improves the efficiency and reduces noise of the propeller structure.



Stepless-smooth fan speed control

Inverter fan motors are now commonly used, where efficiency increase by 40%. Whereas in Hisense VRF, brushless DC fan motors are used, as it could further reduce power consumption and noise production than normal inverter motors.



Efficient axial fan


Auto Refrigerant Temperature Control (ART)

Hisense VRF system featured with ART technology can meet the indoor loads more accurately at a higher efficiency. The system adjusts the evaporating temperature (Et) according to actual indoor loads automatically in a wide range. The Et is raised to minimize the difference with the condensing temperature when the air-conditioning load is low, thus further improving the energy efficiency.

Features:

1. Energy efficiency is improved without sacrificing comfort.
2. ART is particularly efficient under low-load operation.
3. The initial evaporation temperature can be adjusted between 2-11°C, which is the widest in the market.
4. Realize rapid cooling with lower evaporating temperature.
5. Avoiding cold draft with higher evaporating temperature.

$E_t = E_{to} + K$
 Et: Evaporation temperature
 Eto: The initial evaporation temperature
 ΔT: The temperature difference between air inlet and the setting temperature



Hisense VRF

COMFORT

Smart Air Supply

Lower Noise

Clean Fresh Air

Auto Refrigerant Temperature Control (ART)


VIP Mode

AIR
CONDITIONING
SOLUTION


Smart Air Supply

Precise temperature control

There are multiple temperature sensors equipped in the system, which will be very helpful to judge the indoor load more accurately. Also the 2000-step EEV is specially adopted to ensure precise refrigerant flow adjustment according to the actual load of indoor units, achieving a more comfortable indoor environment with small temperature fluctuation.




2000-step EEV



3D air-flow panel(optional)

The 3D air-flow panel with luxurious appearance is available for the low-height ceiling ducted indoor units (optional). The 3D airflow panel can offer even airflow and wide airflow coverage to keep every corners of your room cool or warm. It also has three wind setting, normal mode, 3D mode and super long distance mode, flexible for you choice.




Note

It's optional for the AC/DC low height ceiling ducted unit.

Hi-motion (optional)

Hi-Motion works as an independent human sensor and can be installed separately from indoor unit. It can detect the human activities indoors to provide comfort and energy savings.


1. Automatically stops the unit when no one is in the room in order to realize energy saving.
2. Adjusting the setting temperature and air flow according to the actual human activity.



Motion sensor (optional)

Motion Sensor, assembled in the panel of 4-Way Cassette and Mini 4-Way Cassette, can provide a more comfortable environment, and achieve efficient and energy-saving operation of the unit at the same time.


1. With the sensor, indoor unit can ON or OFF automatically when people enter or leave the room.
2. The people location can be detected by the sensor automatically, and the air flow direction can be set to blow directly or to avoid blowing at people as they like.
3. The setting temperature can be changed automatically by detecting the number of people changing.



Lower Noise

Lower noise for indoor units

Hisense VRF offers indoor units with sound pressure level as low as 19dB(A), perfectly blending into library, auditorium and hospital rooms where require sound level lower than 25dB(A).




Note

*The DC ceiling ducted type (AVD-07HJFH) can achieve the 19dB(A) under the standard test condition.

Outdoor unit noise control

Auto night quiet mode

When outdoor conditions call for special low noise requirements, like in cases where outdoor units are installed in indoor equipment rooms with poor soundproof walls or continuous night operating conditions. The night mode reduces sound pressure levels upto 30% routinely with flexible time intervals to meet different customer needs.



Note

*1 : The night mute mode can last for 8hrs, 9hrs or 10hrs according to the setting.


*2 : Take the unit AWWT-96HKFSEA of S mavo+ series as an example.

Low noise mode


Low noise mode can be set by operating the DIP in the PCB. There are multiple levels by set different frequencies of compressor and fan motor speed. What's more, the low noise mode can be achieved by external input signal. The noise can be reduced by up to 14dB(A).

90s Rapid Heating Start-up

To keep you comfortable and cozy as fast as possible, Hisense VRF starts supplying warm air so rapidly with only just 90s reaching a 100% capacity output. Besides, even in extreme weather condition like -15°C outdoor temperature, Hisense VRF performance is tested with persisting capability to supply 40°C or higher warm air within 7 minutes.



*Taking 66HP as an example



VIP Mode

Hisense VRF offers VIP mode to give priority to the specific room, keeping them comfortable and satisfied as fast as possible and 5 indoor units can be set as VIP mode at the same time. Such function is exclusively practical for hotel application, where AC unit in the presidential suite is often set to VIP mode.



Clean Fresh Air

AirPure

Hisense VRF indoor unit equipped with AirPure kit can release lots of negative ions, about 20 million pcs/cc. These negative ions are carried throughout the room with air-conditioned air flow whereby obtaining air conditioning and air purification simultaneously. With the AirPure kit, the indoor unit has got the Tick Mark certification which is an authentication for air-conditioning sterilization products.



*Take AVE-09HCFRL as the test sample.




Note

4-way Cassette, Mini 4-way Cassette, Console, Ceiling Ducted can be equipped with the AirPure kit (optional).

Self-cleaning function

Featured with self-cleaning technology, the evaporator can be self-cleaned automatically, preventing the dust and potentially harmful substances from accumulating on the surface of the heat exchanger. Thus the air blown from the air conditioner is clean and healthy.




4 processes for deep cleaning

Note

The self-cleaning function is available in the wall mounted unit and DC high ESP ceiling ducted unit(AVD-07~AVD-54).


Humidity sensor (optional)

To keep up with the indoor quality requirements, Hisense VRF offers auto dehumidification function and it can be achieved by choosing a humidity sensor, and the control range is from 35% to 90%.



Fresh air intake

New Hisense VRF indoor units are now infused with a fresh air duct opening for 10% free fresh air introductory directly from outdoor air, creating a comfortable and health environment.



FLEXIBILITY



Design Flexibility


Installation Convenience

Service & Maintenance Simplicity

Design Flexibility


Interlocking solution using dry contact

3rd party thermostats can be used to control the air conditioner in a room by using the dry contact interface. Indoor units can be interlocked with various types of input signal such as key-card, window contact signal, smoke alarm signal and so on.



Adaptive fan static pressure technology


External static pressure is essential to determine the air discharge and duct connection distance. Hisense VRF's outdoor unit external static pressure is reachable up to 110Pa compare to the conventional 80Pa. Allowing longer ducting connection for better air discharge when are installed in the equipment platform that is not easy to exhaust.



Note The initial setting is 80Pa. Can be set to 110Pa from the PCB on site.


Larger capacity, minimizing footprint area

Hisense VRF outdoor units now possess larger capacity per single module unit. Reducing the installation floor space significantly also eliminates the necessity of modules for bigger capacity. Despite the beneficial space saving properties, same goes to the unit's weight per capacity too. Hence, offering more design and installation flexibility even in limited spaces.



All in one renewable energy solution

Hisense VRF heat recovery series offers an ultimate solution to satisfy heating and cooling, domestic hot water supply, floor/wall/ceiling cooling and heating simultaneously. The heat recovery system is also compatible with any auxiliary heaters like solar, electric heater and gas boiler to supply additional energy to the system in unfavorable conditions.



Installation Convenience


Compact and light-weight

With larger capacity per unit, Hisense VRF outdoor units are more compact in size with the largest capacity of 28HP single module, leading capacity of a single module in the market. Compact yet reduced overall weight makes transportation much convenient and even fit into elevators.




One-touch test run

Test run is one of the essential part in testing and commissioning to make sure the HVAC system in a building works steadily and safely before hand over or soft opening. To make test run as simple as possible, Hisense VRF systems are capable to conduct test runs with just a button away wherever installers are, both indoors and outdoors.



AUTO Intelligent matching IDUs

Match all kinds of hisense indoor units. If each air deflector can be controlled independently, the key will light. On the contrary, the key will dim and you can not click.




One-touch refrigerant recycle

Hisense VRF has one-touch refrigerant recycle function. Just with a press of the button on the PCB, the refrigerant can be recycled directly, it is very helpful and convenient when the indoor units or the compressor are under repair.




Scan the QR code to view the detailed introduction



Mistake impossible communication connection

Communication line connections between outdoor unit to indoor units might be confusing when comes to long cables from the outdoors to the indoors and vice versa. It is often incorrectly connected and caused various errors affecting the end user's comfort levels. Despite of Hisense VRF's simple wiring connection ports, the outdoor unit itself could also check on the connections and display warnings when the connections are improper.




Indoor units from different systems are connected to the incorrect outdoor unit, alarm codes flashes out warning installers to make proper corrections.

Service & Maintenance Simplicity


Automatic address distribution

The system can automatically distribute addresses for indoor units, no need to manually set the address one by one. This feature greatly simplifies the installation and commission process.




Safe and convenient system management

The new outdoor units are equipped with a service window on top of the electrical box protection panel for easy access to parameters checking and maintenance manipulation safely without exposing to high voltage segments of the electric box. With the new service windows, press switch buttons, DIP switches and the 7 segment LED operation are made safer and more convenient to operate.




Separated mechanical & electrical compartment

The outdoor unit's mechanical and electrical segments is now designed and optimized repositioned separately for a more organized maintenance. The electrical and electronics are placed on top of the compressors and accumulator to meet the practical law of center of gravity, hence minimizing toppling accidents and unnecessary vibration produced during operation. Besides, it also maximizes the heat dissipation of electrical box to keep the electrical in a stable temperature by maximizing airflow passed by.



Accurate intelligent system diagnosis

Exclusive Hi-Checker is a super intelligent service tool for system diagnosis, which can provides easy access to service parameters. Detail operation status and recent error history can be checked and analyzed by using Hi-Checker.



OUTDOOR UNIT

Hi-FLEXi S Series Heat Recovery

Hi-FLEXi S Series

Hi-FLEXi S mavo+ Series

Hi-FLEXi X3 Series

Hi-FLEXi W Series

Hi-Smart H5 Series

Hi-Smart E+ L+ C+ Series


Hi-Smart H Series

Hi-FLEXi **S** Heat Recovery Series



All in One Renewable Energy Solution

With S heat recovery series, cooling and heating of air can be realised simultaneously including water. During summer, it serves cool indoor rooms and warm water supply for night showers. With the same system, floor heating and fan coil unit heating and cooling can be done during season transition periods.




200% Connection Ratio

The powerful S heat recovery series outdoor units are connectable to indoor units up to 2 times of its own capacity with ratio of 200% for a more efficient and cost saving system.




External Static Pressure

External static pressure is reachable up to 110Pa, allowing better air discharge when are installed indoors with ducting or even outdoors in poor air ventilation spaces.



Piping Length

With extra long pipe, the height difference between the indoor unit and outdoor unit is up to 90 meters*, which makes installation more flexible.




*Note: For detailed information, please contact Hisense's technical staff.


New Upgraded Switch Box

Switch box defies the complicated piping of 3pipe heat recovery systems and simplifies the system with lesser connections and piping including refrigerant and condensate piping. Now with larger capacity up to 85kW for larger systems and increased up to 16 branch ports for more indoor units connections.

Heating Domination Mode





3 Pipes Without Switch Box



Dual 20RT EEV

Compared with conventional 10RT EEV with 480 steps, dual 20RT EEV with 3000pls can better reduce pressure loss and improve performance.



Hi-FLEXi S Heat Recovery



		HP	8HP	10HP	12HP	14HP	16HP	18HP
Model	Model		AVWT-76FKFSA	AVWT-96FKFSA	AVWT-114FKFSA	AVWT-136FKFSA	AVWT-154FKFSA	AVWT-170FKFSA
Model	Modules		—	—	—	—	—	—
	Power Supply		AC 3Φ, 380-415V/50/60Hz					
Cooling	Capacity	kW	22.4	28.0	33.5	40.0	45.0	50.0
		kBtu/h	76.4	95.5	114.3	136.5	153.5	170.6
	Power Input	kW	4.87	6.75	8.09	10.26	12.16	14.04
	EER	kW/kW	4.60	4.15	4.14	3.90	3.70	3.56
Heating	Capacity(Max/Nom)	kW	25.0 / 22.4	31.5 / 28.0	37.5 / 33.5	45.0 / 40.0	50.0 / 45.0	56.0 / 50.0
		kBtu/h	85.3 / 76.4	107.5 / 95.5	128.0 / 114.3	153.5 / 136.5	170.6 / 153.5	191.1 / 170.6
	Power Input(Max/Nom)	kW	5.20 / 4.36	6.77 / 5.63	9.17 / 7.70	10.82 / 8.89	12.14 / 10.32	14.74 / 12.02
	COP(Max)	kW/kW	4.81	4.65	4.09	4.16	4.12	3.80
Ventilation	Air Flow Rate	m ³ /min	183	183	183	200	200	200
	Fan Quantity		1	1	1	2	2	2
	Static Pressure	Pa	110	110	110	110	110	110
Sound	Sound Pressure Level	dB(A)	59	60	62	62	62	62
	Type	—	Enhanced Vapor Injection Scroll Compressor					
Compressor	Compressor Quantity	pcs	1	1	1	1	1	2
	Type	—	R410A					
Refrigerant	Pre-charged Quantity	kg	5.60	5.90	6.00	8.80	8.80	9.20
	Net Weight	kg	226	227	246	289	290	349
Weight	Gross Weight	kg	246	247	266	311	312	371
	External(HxWxD)	mm	1730x950x750	1730x950x750	1730x950x750	1730x1210x750	1730x1210x750	1730x1210x750
Dimensions	Packing(HxWxD)	mm	1930x1015x790	1930x1015x790	1930x1015x790	1930x1275x790	1930x1275x790	1930x1275x790
	Cabinet Color		Ivory White	Ivory White	Ivory White	Ivory White	Ivory White	Ivory White
Heat Recovery Operation System	Low Pressure Gas Line	mm(in.)	φ19.05(3/4)	φ22.20(7/8)	φ25.40(1)	φ25.40(1)	φ28.60(1-1/8)	φ28.60(1-1/8)
	High/Low Pressure Gas Line	mm(in.)	φ15.88(5/8)	φ19.05(3/4)	φ22.2(7/8)	φ22.2(7/8)	φ22.2(7/8)	φ22.2(7/8)
	Liquid Line	mm(in.)	φ9.53(3/8)	φ9.53(3/8)	φ12.70(1/2)	φ12.70(1/2)	φ12.70(1/2)	φ15.88(5/8)
Heat Pump Operation System	Gas Line	mm(in.)	φ19.05(3/4)	φ22.20(7/8)	φ25.40(1)	φ25.40(1)	φ28.60(1-1/8)	φ28.60(1-1/8)
	Liquid Line	mm(in.)	φ9.53(3/8)	φ9.53(3/8)	φ12.70(1/2)	φ12.70(1/2)	φ12.70(1/2)	φ15.88(5/8)
Connectable Indoor Units	Quantity	pcs	13	16	19	23	26	29
	Total Capacity	—	200%*1	200%*1	200%*1	200%*1	200%*1	200%*1
Piping Design	Height Difference Between ODU and IDU	m(above)	50(90°*)	50(90°*)	50(90°*)	50(90°*)	50(90°*)	50(90°*)
		m(below)	40(90°*)	40(90°*)	40(90°*)	40(90°*)	40(90°*)	40(90°*)
	Height Difference Between IDUs	m	15(30°*)	15(30°*)	15(30°*)	15(30°*)	15(30°*)	15(30°*)
	Max. Piping Length	m	165	165	165	165	165	165
Operation Range	Cooling	DB	-10°C-52°C	-10°C-52°C	-10°C-52°C	-10°C-52°C	-10°C-52°C	-10°C-52°C
	Heating	WB	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C

Notes:

- Rated cooling capacity and rated heating capacity are tested in the following conditions:
Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
- The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
- The final appearance of outdoor units is subject to the actual products.
- *: If you have any questions, please contact with the technical engineer.
- *: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Heat Recovery



HP		20HP	22HP	24HP	26HP	28HP	
Model	Model	AVWT-190FKFSA	AVWT-212FKFSA	AVWT-232FKFSA	AVWT-250FKFSA	AVWT-272FKFSA	
Model	Modules	—	—	—	—	—	
Power Supply		AC 3 φ, 380-415V/50/60Hz					
Cooling	Capacity	kW	56.0	61.5	68.0	72.5	80.0
		kBtu/h	191.1	209.8	232.0	247.4	273.0
	Power Input	kW	15.60	18.04	20.61	21.90	24.24
	EER	kW/kW	3.59	3.41	3.30	3.31	3.30
Heating	Capacity(Max/Nom)	kW	63.0 / 56.0	69.0 / 61.5	75.0 / 68.0	80.0 / 72.5	90.0 / 80.0
		kBtu/h	215.0 / 191.1	235.4 / 209.8	255.9 / 232.0	273.0 / 247.4	307.1 / 273.0
	Power Input(Max/Nom)	kW	16.54 / 13.56	18.80 / 15.89	21.43 / 18.38	22.35 / 19.23	26.01 / 21.92
Ventilation	COP(Max)	kW/kW	3.81	3.67	3.50	3.58	3.46
	Air Flow Rate	m³/min	267	296	296	350	350
	Fan Quantity		2	2	2	2	2
Sound	Static Pressure	Pa	110	110	110	110	110
	Sound Pressure Level	dB(A)	63	64	66	67	67
Compressor	Type	Enhanced Vapor Injection Scroll Compressor					
	Compressor Quantity	pcs	2	2	2	2	2
Refrigerant	Type	R410A					
	Pre-charged Quantity	kg	9.80	10.60	10.60	11.50	11.50
Weight	Net Weight	kg	369	377	378	400	401
	Gross Weight	kg	393	401	402	426	427
Dimensions	External(HxWxD)	mm	1730x1350x750	1730x1350x750	1730x1350x750	1730x1600x750	1730x1600x750
	Packing(HxWxD)	mm	1930x1420x790	1930x1420x790	1930x1420x790	1930x1665x790	1930x1665x790
Cabinet Color		Ivory White					
Heat Recovery Operation System	Low Pressure Gas Line	mm(in.)	φ28.60(1-1/8)	φ28.60(1-1/8)	φ28.60(1-1/8)	φ31.75(1-1/4)	φ31.75(1-1/4)
	High/Low Pressure Gas Line	mm(in.)	φ22.2(7/8)	φ25.4(1)	φ25.4(1)	φ25.4(1)	φ28.6(1-1/8)
	Liquid Line	mm(in.)	φ15.88(5/8)	φ15.88(5/8)	φ15.88(5/8)	φ19.05(3/4)	φ19.05(3/4)
Heat Pump Operation System	Gas Line	mm(in.)	φ28.60(1-1/8)	φ28.60(1-1/8)	φ28.60(1-1/8)	φ31.75(1-1/4)	φ31.75(1-1/4)
	Liquid Line	mm(in.)	φ15.88(5/8)	φ15.88(5/8)	φ15.88(5/8)	φ19.05(3/4)	φ19.05(3/4)
Connectable Indoor Units	Quantity	pcs	33	36	40	43	47
	Total Capacity	—	200%*1	200%*1	200%*1	200%*1	200%*1
Piping Design	Height Difference Between ODU and IDU	m(above)	50(90*2)	50(90*2)	50(90*2)	50(90*2)	50(90*2)
		m(below)	40(90*2)	40(90*2)	40(90*2)	40(90*2)	40(90*2)
	Height Difference Between IDUs	m	15(30*2)	15(30*2)	15(30*2)	15(30*2)	15(30*2)
Operation Range	Max. Piping Length	m	165	165	165	165	165
	Cooling	DB	-10°C-52°C	-10°C-52°C	-10°C-52°C	-10°C-52°C	-10°C-52°C
	Heating	WB	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C

Notes:
 1. Rated cooling capacity and rated heating capacity are tested in the following conditions:
 Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
 Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 2. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
 3. The final appearance of outdoor units is subject to the actual products.
 *: If you have any questions, please contact with the technical engineer.
 **: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Heat Recovery



HP		30HP	32HP	34HP	36HP	38HP	
Model	Model	AVWT-290FKFSA	AVWT-308FKFSA	AVWT-324FKFSA	AVWT-344FKFSA	AVWT-360FKFSA	
Model	Modules	AVWT-136FKFSA AVWT-154FKFSA	AVWT-154FKFSA AVWT-154FKFSA	AVWT-154FKFSA AVWT-170FKFSA	AVWT-154FKFSA AVWT-190FKFSA	AVWT-170FKFSA AVWT-190FKFSA	
Power Supply		AC 3 φ, 380-415V/50/60Hz					
Cooling	Capacity	kW	85.0	90.0	95.0	101.0	106.0
		kBtu/h	290.0	307.1	324.1	344.6	361.7
	Power Input	kW	22.41	24.32	26.20	27.75	29.64
	EER	kW/kW	3.79	3.70	3.63	3.64	3.58
Heating	Capacity(Max/Nom)	kW	95.0 / 85.0	100.0 / 90.0	106.0 / 95.0	113.0 / 101.0	119.0 / 106.0
		kBtu/h	324.1 / 290.0	341.2 / 307.1	361.7 / 324.1	385.6 / 344.6	406.0 / 361.7
	Power Input(Max/Nom)	kW	22.95 / 19.21	24.27 / 20.64	26.82 / 22.33	28.62 / 23.86	31.27 / 25.58
Ventilation	COP(Max)	kW/kW	4.14	4.12	3.95	3.95	3.81
	Air Flow Rate	m³/min	400	400	400	467	467
	Fan Quantity		4	4	4	4	4
Sound	Static Pressure	Pa	110	110	110	110	110
	Sound Pressure Level	dB(A)	67	67	67	67	67
Compressor	Type	Enhanced Vapor Injection Scroll Compressor					
	Compressor Quantity	pcs	2	2	3	3	4
Refrigerant	Type	R410A					
	Pre-charged Quantity	kg	8.80+8.80	8.80+8.80	8.80+9.20	8.80+9.80	9.20+9.80
Weight	Net Weight	kg	289+290	290+290	290+349	290+369	349+369
	Gross Weight	kg	311+312	312+312	312+371	312+393	371+393
Dimensions	External(HxWxD)	mm	1730x (1210+1210) x750	1730x (1210+1210) x750	1730x (1210+1210) x750	1730x (1210+1350) x750	1730x (1210+1350) x750
	Packing(HxWxD)	mm	1930x (1275+1275) x790	1930x (1275+1275) x790	1930x (1275+1275) x790	1930x (1275+1420) x790	1930x (1275+1420) x790
Cabinet Color		Ivory White					
Heat Recovery Operation System	Low Pressure Gas Line	mm(in.)	φ31.75(1-1/4)	φ31.75(1-1/4)	φ31.75(1-1/4)	φ38.1(1-1/2)	φ38.1(1-1/2)
	High/Low Pressure Gas Line	mm(in.)	φ28.6(1-1/8)	φ28.6(1-1/8)	φ28.6(1-1/8)	φ28.6(1-1/8)	φ31.75(1-1/4)
	Liquid Line	mm(in.)	φ19.05(3/4)	φ19.05(3/4)	φ19.05(3/4)	φ19.05(3/4)	φ19.05(3/4)
Heat Pump Operation System	Gas Line	mm(in.)	φ31.75(1-1/4)	φ31.75(1-1/4)	φ31.75(1-1/4)	φ38.1(1-1/2)	φ38.1(1-1/2)
	Liquid Line	mm(in.)	φ19.05(3/4)	φ19.05(3/4)	φ19.05(3/4)	φ19.05(3/4)	φ19.05(3/4)
Connectable Indoor Units	Quantity	pcs	50	53	56	59	64
	Total Capacity	—	200%*1	200%*1	200%*1	200%*1	200%*1
Piping Design	Height Difference Between ODU and IDU	m(above)	50(90*2)	50(90*2)	50(90*2)	50(90*2)	50(90*2)
		m(below)	40(90*2)	40(90*2)	40(90*2)	40(90*2)	40(90*2)
	Height Difference Between IDUs	m	15(30*2)	15(30*2)	15(30*2)	15(30*2)	15(30*2)
Operation Range	Max. Piping Length	m	165	165	165	165	165
	Cooling	DB	-10°C-52°C	-10°C-52°C	-10°C-52°C	-10°C-52°C	-10°C-52°C
	Heating	WB	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C

Notes:
 1. Rated cooling capacity and rated heating capacity are tested in the following conditions:
 Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
 Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 2. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
 3. The final appearance of outdoor units is subject to the actual products.
 *: If you have any questions, please contact with the technical engineer.
 **: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Heat Recovery



HP		58HP	60HP	62HP	64HP	
Model	Model	AVWT-552FKFSA	AVWT-570FKFSA	AVWT-592FKFSA	AVWT-612FKFSA	
	Modules	AVWT-170FKFSA	AVWT-190FKFSA	AVWT-170FKFSA	AVWT-190FKFSA	
		AVWT-170FKFSA	AVWT-190FKFSA	AVWT-190FKFSA	AVWT-232FKFSA	
Power Supply		AC 3Φ, 380-415V/50/60Hz				
Cooling	Capacity	161.5	168.0	174.0	180.0	
	kW	551.0	573.2	593.7	614.2	
	kBtu/h	46.11	46.80	50.18	51.72	
	Power Input	3.50	3.59	3.47	3.48	
Heating	EER	181.0 / 161.5	189.0 / 168.0	194.0 / 174.0	201.0 / 180.0	
	Capacity(Max/Nom)	617.6 / 551.0	644.9 / 573.2	661.9 / 593.7	685.8 / 614.2	
	kW	48.27 / 39.89	49.61 / 40.68	52.64 / 43.83	54.43 / 45.37	
	Power Input(Max/Nom)	3.75	3.81	3.69	3.69	
Ventilation	COP(Max)	696	801	763	830	
	Air Flow Rate	6	6	6	6	
	Fan Quantity	110	110	110	110	
Sound	Static Pressure	70	70	70	70	
	Sound Pressure Level	Enhanced Vapor Injection Scroll Compressor				
Compressor	Type	6	6	6	6	
	Compressor Quantity	R410A				
Refrigerant	Type	R410A				
	Pre-charged Quantity	9.20+9.20+10.60	9.80+9.80+9.80	9.20+9.80+10.60	9.80+9.80+10.60	
Weight	Net Weight	349+349+377	369+369+369	349+369+378	369+378+378	
	Gross Weight	371+371+401	393+393+393	371+393+402	393+393+402	
Dimensions	External(HxWxD)	mm	1730x	1730x	1730x	
		(1210+1210+1350)	(1350+1350+1350)	(1210+1350+1350)	(1350+1350+1350)	
	Packing(HxWxD)	mm	1930x	1930x	1930x	1930x
		(1275+1275+1420)	(1420+1420+1420)	(1275+1420+1420)	(1420+1420+1420)	
Cabinet Color		Ivory White	Ivory White	Ivory White	Ivory White	
Heat Recovery Operation System	Low Pressure Gas Line	mm(in.)	Φ44.5(1-3/4)	Φ44.5(1-3/4)	Φ44.5(1-3/4)	
	High/Low Pressure Gas Line	mm(in.)	Φ41.3(1-5/8)	Φ41.3(1-5/8)	Φ41.3(1-5/8)	
	Liquid Line	mm(in.)	Φ22.2(7/8)	Φ22.2(7/8)	Φ22.2(7/8)	
Heat Pump Operation System	Gas Line	mm(in.)	Φ44.5(1-3/4)	Φ44.5(1-3/4)	Φ44.5(1-3/4)	
	Liquid Line	mm(in.)	Φ22.2(7/8)	Φ22.2(7/8)	Φ22.2(7/8)	
Connectable Indoor Units	Quantity	pcs	64	64	64	
	Total Capacity	-	200%*1	200%*1	200%*1	
Piping Design	Height Difference Between ODU and IDU	m(above)	50(90*)	50(90*)	50(90*)	
		m(below)	40(90*)	40(90*)	40(90*)	
	Height Difference Between IDUs	m	15(30*)	15(30*)	15(30*)	
	Max. Piping Length	m	165	165	165	
Operation Range	Cooling	DB	-10°C-52°C	-10°C-52°C	-10°C-52°C	
	Heating	WB	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C	

Notes:

1. Rated cooling capacity and rated heating capacity are tested in the following conditions:

Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.

Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.

2. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.

3. The final appearance of outdoor units is subject to the actual products.

*: If you have any questions, please contact with the technical engineer.

?: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Heat Recovery



HP		66HP	68HP	70HP	72HP	
Model	Model	AVWT-634FKFSA	AVWT-654FKFSA	AVWT-676FKFSA	AVWT-696FKFSA	
	Modules	AVWT-190FKFSA	AVWT-190FKFSA	AVWT-212FKFSA	AVWT-232FKFSA	
		AVWT-212FKFSA	AVWT-232FKFSA	AVWT-232FKFSA	AVWT-232FKFSA	
Power Supply		AC 3Φ, 380-415V/50/60Hz				
Cooling	Capacity	185.5	192.0	197.5	204.0	
	kW	632.9	655.1	673.9	696.0	
	kBtu/h	54.18	56.73	59.23	61.82	
	Power Input	3.42	3.38	3.33	3.30	
Heating	EER	207.0 / 185.5	213.0 / 192.0	219.0 / 197.5	225.0 / 204.0	
	Capacity(Max/Nom)	706.3 / 632.9	726.8 / 655.1	747.2 / 673.9	767.7 / 696.0	
	kW	56.72 / 47.74	59.33 / 50.20	61.63 / 52.62	64.29 / 55.14	
	Power Input(Max/Nom)	3.65	3.59	3.55	3.50	
Ventilation	COP(Max)	859	859	888	888	
	Air Flow Rate	6	6	6	6	
	Fan Quantity	110	110	110	110	
Sound	Static Pressure	70	70	70	71	
	Sound Pressure Level	Enhanced Vapor Injection Scroll Compressor				
Compressor	Type	6	6	6	6	
	Compressor Quantity	R410A				
Refrigerant	Type	R410A				
	Pre-charged Quantity	9.80+10.60+10.60	9.80+10.60+10.60	10.60+10.60+10.60	10.60+10.60+10.60	
Weight	Net Weight	369+377+378	369+378+378	377+378+378	378+378+378	
	Gross Weight	393+401+402	393+402+402	401+402+402	402+402+402	
Dimensions	External(HxWxD)	mm	1730x	1730x	1730x	
		(1350+1350+1350)	(1350+1350+1350)	(1350+1350+1350)	(1350+1350+1350)	
	Packing(HxWxD)	mm	1930x	1930x	1930x	1930x
		(1420+1420+1420)	(1420+1420+1420)	(1420+1420+1420)	(1420+1420+1420)	
Cabinet Color		Ivory White	Ivory White	Ivory White	Ivory White	
Heat Recovery Operation System	Low Pressure Gas Line	mm(in.)	Φ44.5(1-3/4)	Φ50.8(2)	Φ50.8(2)	
	High/Low Pressure Gas Line	mm(in.)	Φ41.3(1-5/8)	Φ44.5(1-3/4)	Φ44.5(1-3/4)	
	Liquid Line	mm(in.)	Φ22.2(7/8)	Φ25.4(1)	Φ25.4(1)	
Heat Pump Operation System	Gas Line	mm(in.)	Φ44.5(1-3/4)	Φ50.8(2)	Φ50.8(2)	
	Liquid Line	mm(in.)	Φ22.2(7/8)	Φ25.4(1)	Φ25.4(1)	
Connectable Indoor Units	Quantity	pcs	64	64	64	
	Total Capacity	-	200%*1	200%*1	200%*1	
Piping Design	Height Difference Between ODU and IDU	m(above)	50(90*)	50(90*)	50(90*)	
		m(below)	40(90*)	40(90*)	40(90*)	
	Height Difference Between IDUs	m	15(30*)	15(30*)	15(30*)	
	Max. Piping Length	m	165	165	165	
Operation Range	Cooling	DB	-10°C-52°C	-10°C-52°C	-10°C-52°C	
	Heating	WB	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C	

Notes:

1. Rated cooling capacity and rated heating capacity are tested in the following conditions:

Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.

Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.

2. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.

3. The final appearance of outdoor units is subject to the actual products.

*: If you have any questions, please contact with the technical engineer.

?: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Heat Recovery



HP		74HP	76HP	78HP	80HP
Model	Model	AVWT-714FKFSA	AVWT-732FKFSA	AVWT-754FKFSA	AVWT-776FKFSA
	Modules	AVWT-232FKFSA	AVWT-232FKFSA	AVWT-232FKFSA	AVWT-232FKFSA
		AVWT-250FKFSA	AVWT-250FKFSA	AVWT-250FKFSA	AVWT-272FKFSA
Power Supply		AC 3Φ, 380-415V/50/60Hz			
Cooling	Capacity	kW 208.5	213.0	220.5	228.0
		kBtu/h 711.4	726.8	752.3	777.9
	Power Input	kW 63.11	64.41	66.75	69.09
	EER	kW/kW 3.30	3.31	3.30	3.30
Heating	Capacity(Max/Nom)	kW 230.0 / 208.5	235.0 / 213.0	245.0 / 220.5	255.0 / 228.0
		kBtu/h 784.8 / 711.4	801.8 / 726.8	835.9 / 752.3	870.1 / 777.9
	Power Input(Max/Nom)	kW 65.19 / 55.98	66.11 / 56.83	69.76 / 59.51	73.45 / 62.21
Ventilation	COP(Max)	kW/kW 3.53	3.55	3.51	3.47
	Air Flow Rate	m³/min 942	996	996	996
	Fan Quantity	6	6	6	6
Sound	Static Pressure	Pa 110	110	110	110
	Sound Pressure Level	dB(A) 71	71	71	71
Compressor	Type	Enhanced Vapor Injection Scroll Compressor			
	Compressor Quantity	pcs 6	6	6	6
Refrigerant	Type	R410A			
	Pre-charged Quantity	kg 10.60+10.60+11.50	10.60+11.50+11.50	10.60+11.50+11.50	10.60+11.50+11.50
Weight	Net Weight	kg 378+378+400	378+400+400	378+400+401	378+401+401
	Gross Weight	kg 402+402+426	402+426+426	402+426+427	402+427+427
Dimensions	External(HxWxD)	mm 1730x (1350+1350+1600)	1730x (1350+1600+1600)	1730x (1350+1600+1600)	1730x (1350+1600+1600)
		x750	x750	x750	x750
	Packing(HxWxD)	mm 1930x (1420+1420+1665)	1930x (1420+1665+1665)	1930x (1420+1665+1665)	1930x (1420+1665+1665)
Cabinet Color		Ivory White	Ivory White	Ivory White	Ivory White
	Low Pressure Gas Line	mm(in.) φ50.8(2)	φ50.8(2)	φ50.8(2)	φ50.8(2)
Heat Recovery Operation System	High/Low Pressure Gas Line	mm(in.) φ44.5(1-3/4)	φ44.5(1-3/4)	φ44.5(1-3/4)	φ44.5(1-3/4)
	Liquid Line	mm(in.) φ25.4(1)	φ25.4(1)	φ25.4(1)	φ25.4(1)
Heat Pump Operation System	Gas Line	mm(in.) φ50.8(2)	φ50.8(2)	φ50.8(2)	φ50.8(2)
	Liquid Line	mm(in.) φ25.4(1)	φ25.4(1)	φ25.4(1)	φ25.4(1)
Connectable Indoor Units	Quantity	pcs 64	64	64	64
	Total Capacity	- 200%*1	200%*1	200%*1	200%*1
Piping Design	Height Difference Between ODU and IDU	m(above) 50(90*)	50(90*)	50(90*)	50(90*)
		m(below) 40(90*)	40(90*)	40(90*)	40(90*)
	Height Difference Between IDUs	m 15(30*)	15(30*)	15(30*)	15(30*)
	Max. Piping Length	m 165	165	165	165
Operation Range	Cooling	DB -10°C~52°C	-10°C~52°C	-10°C~52°C	-10°C~52°C
	Heating	WB -25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C

Notes:
 1. Rated cooling capacity and rated heating capacity are tested in the following conditions:
 Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
 Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 2. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
 3. The final appearance of outdoor units is subject to the actual products.
 *: If you have any questions, please contact with the technical engineer.
 **: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Heat Recovery



HP		82HP	84HP	86HP	88HP
Model	Model	AVWT-794FKFSA	AVWT-816FKFSA	AVWT-824FKFSA	AVWT-844FKFSA
	Modules	AVWT-250FKFSA	AVWT-272FKFSA	AVWT-190FKFSA	AVWT-190FKFSA
		AVWT-272FKFSA	AVWT-272FKFSA	AVWT-212FKFSA	AVWT-232FKFSA
Power Supply		AC 3Φ, 380-415V/50/60Hz			
Cooling	Capacity	kW 232.5	240.0	241.5	248.0
		kBtu/h 793.3	818.9	824.0	846.2
	Power Input	kW 70.39	72.73	69.76	72.29
	EER	kW/kW 3.30	3.30	3.46	3.43
Heating	Capacity(Max/Nom)	kW 260.0 / 232.5	270.0 / 240.0	270.0 / 241.5	276.0 / 248.0
		kBtu/h 887.1 / 793.3	921.2 / 818.9	921.2 / 824.0	941.7 / 846.2
	Power Input(Max/Nom)	kW 74.33 / 63.05	78.03 / 65.75	73.24 / 61.26	75.83 / 63.69
Ventilation	COP(Max)	kW/kW 3.50	3.46	3.69	3.64
	Air Flow Rate	m³/min 1050	1050	1126	1126
	Fan Quantity	6	6	8	8
Sound	Static Pressure	Pa 110	110	110	110
	Sound Pressure Level	dB(A) 72	72	72	72
Compressor	Type	Enhanced Vapor Injection Scroll Compressor			
	Compressor Quantity	pcs 6	6	8	8
Refrigerant	Type	R410A			
	Pre-charged Quantity	kg 11.50+11.50+11.50	11.50+11.50+11.50	9.80+9.80+10.60+10.60	9.80+9.80+10.60+10.60
Weight	Net Weight	kg 400+401+401	401+401+401	369+369+377+378	369+369+378+378
	Gross Weight	kg 426+427+427	427+427+427	393+393+401+402	393+393+402+402
Dimensions	External(HxWxD)	mm 1730x (1600+1600+1600)	1730x (1600+1600+1600)	1730x (1350+1350+1350+1350)	1730x (1350+1350+1350+1350)
		x750	x750	x750	x750
	Packing(HxWxD)	mm 1930x (1665+1665+1665)	1930x (1665+1665+1665)	1930x (1420+1420+1420+1420)	1930x (1420+1420+1420+1420)
Cabinet Color		Ivory White	Ivory White	Ivory White	Ivory White
	Low Pressure Gas Line	mm(in.) φ50.8(2)	φ50.8(2)	φ50.8(2)	φ50.8(2)
Heat Recovery Operation System	High/Low Pressure Gas Line	mm(in.) φ44.5(1-3/4)	φ44.5(1-3/4)	φ44.5(1-3/4)	φ44.5(1-3/4)
	Liquid Line	mm(in.) φ25.4(1)	φ25.4(1)	φ25.4(1)	φ25.4(1)
Heat Pump Operation System	Gas Line	mm(in.) φ50.8(2)	φ50.8(2)	φ50.8(2)	φ50.8(2)
	Liquid Line	mm(in.) φ25.4(1)	φ25.4(1)	φ25.4(1)	φ25.4(1)
Connectable Indoor Units	Quantity	pcs 64	64	64	64
	Total Capacity	- 200%*1	200%*1	200%*1	200%*1
Piping Design	Height Difference Between ODU and IDU	m(above) 50(90*)	50(90*)	50(90*)	50(90*)
		m(below) 40(90*)	40(90*)	40(90*)	40(90*)
	Height Difference Between IDUs	m 15(30*)	15(30*)	15(30*)	15(30*)
	Max. Piping Length	m 165	165	165	165
Operation Range	Cooling	DB -10°C~52°C	-10°C~52°C	-10°C~52°C	-10°C~52°C
	Heating	WB -25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C

Notes:
 1. Rated cooling capacity and rated heating capacity are tested in the following conditions:
 Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
 Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 2. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
 3. The final appearance of outdoor units is subject to the actual products.
 *: If you have any questions, please contact with the technical engineer.
 **: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Heat Recovery



HP		90HP	92HP	94HP	96HP	
Model	Model	AVWT-866FKFSA	AVWT-886FKFSA	AVWT-908FKFSA	AVWT-928FKFSA	
	Modules	AVWT-190FKFSA	AVWT-190FKFSA	AVWT-212FKFSA	AVWT-232FKFSA	
		AVWT-212FKFSA	AVWT-232FKFSA	AVWT-232FKFSA	AVWT-232FKFSA	
		AVWT-232FKFSA	AVWT-232FKFSA	AVWT-232FKFSA	AVWT-232FKFSA	
Power Supply		AC 3φ, 380-415V/50/60Hz				
Cooling	Capacity	kW	253.5	260.0	265.5	272.0
		kBtu/h	864.9	887.1	905.9	928.1
	Power Input	kW	74.77	77.33	79.83	82.42
	EER	kW/kW	3.39	3.36	3.33	3.30
Heating	Capacity(Max/Nom)	kW	282.0 / 253.5	288.0 / 260.0	294.0 / 265.5	300.0 / 272.0
		kBtu/h	962.2 / 864.9	982.7 / 887.1	1003.1 / 905.9	1023.6 / 928.1
	Power Input(Max/Nom)	kW	78.12 / 66.09	80.75 / 68.56	83.06 / 71.00	85.71 / 73.51
	COP(Max)	kW/kW	3.61	3.57	3.54	3.50
Ventilation	Air Flow Rate	m³/min	1155	1155	1184	1184
	Fan Quantity		8	8	8	8
	Static Pressure	Pa	110	110	110	110
Sound	Sound Pressure Level	dB(A)	72	72	72	72
	Type		Enhanced Vapor Injection Scroll Compressor			
Compressor	Compressor Quantity	pcs	8	8	8	8
	Type		R410A			
Refrigerant	Pre-charged Quantity	kg	9.80+10.60+10.60+10.60	9.80+10.60+10.60+10.60	10.60+10.60+10.60+10.60	10.60+10.60+10.60+10.60
	Net Weight	kg	369+377+378+378	369+378+378+378	377+378+378+378	378+378+378+378
	Gross Weight	kg	393+401+402+402	393+402+402+402	401+402+402+402	402+402+402+402
Dimensions	External(HxWxD)	mm	1730x (1350+1350+1350+1350) x750	1730x (1350+1350+1350+1350) x750	1730x (1350+1350+1350+1350) x750	1730x (1350+1350+1350+1350) x750
		mm	1930x (1420+1420+1420+1420) x790	1930x (1420+1420+1420+1420) x790	1930x (1420+1420+1420+1420) x790	1930x (1420+1420+1420+1420) x790
	Packing(HxWxD)	mm	1730x (1350+1350+1350+1350) x750	1730x (1350+1350+1350+1350) x750	1730x (1350+1350+1350+1350) x750	1730x (1350+1350+1350+1350) x750
		mm	1930x (1420+1420+1420+1420) x790	1930x (1420+1420+1420+1420) x790	1930x (1420+1420+1420+1420) x790	1930x (1420+1420+1420+1420) x790
Cabinet Color	Low Pressure Gas Line	mm(in.)	φ50.8(2)	φ50.8(2)	φ50.8(2)	φ50.8(2)
	High/Low Pressure Gas Line	mm(in.)	φ44.5(1-3/4)	φ44.5(1-3/4)	φ44.5(1-3/4)	φ44.5(1-3/4)
	Liquid Line	mm(in.)	φ25.4(1)	φ25.4(1)	φ25.4(1)	φ25.4(1)
Heat Pump Operation System	Gas Line	mm(in.)	φ50.8(2)	φ50.8(2)	φ50.8(2)	φ50.8(2)
	Liquid Line	mm(in.)	φ25.4(1)	φ25.4(1)	φ25.4(1)	φ25.4(1)
Connectable Indoor Units	Quantity	pcs	64	64	64	64
	Total Capacity		200%*1	200%*1	200%*1	200%*1
Piping Design	Height Difference Between ODU and IDU	m(above)	50(90*)	50(90*)	50(90*)	50(90*)
		m(below)	40(90*)	40(90*)	40(90*)	40(90*)
	Height Difference Between IDUs	m	15(30*)	15(30*)	15(30*)	15(30*)
	Max. Piping Length	m	165	165	165	165
Operation Range	Cooling	DB	-10°C~52°C	-10°C~52°C	-10°C~52°C	-10°C~52°C
	Heating	WB	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C

Notes:
 1. Rated cooling capacity and rated heating capacity are tested in the following conditions:
 Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
 Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 2. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
 3. The final appearance of outdoor units is subject to the actual products.
 *: If you have any questions, please contact with the technical engineer.
 **: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Heat Recovery



HP		98HP	100HP	102HP	104HP	
Model	Model	AVWT-946FKFSA	AVWT-968FKFSA	AVWT-988FKFSA	AVWT-1008FKFSA	
	Modules	AVWT-232FKFSA	AVWT-232FKFSA	AVWT-212FKFSA	AVWT-232FKFSA	
		AVWT-232FKFSA	AVWT-232FKFSA	AVWT-232FKFSA	AVWT-232FKFSA	
		AVWT-232FKFSA	AVWT-232FKFSA	AVWT-272FKFSA	AVWT-272FKFSA	
Power Supply		AC 3φ, 380-415V/50/60Hz				
Cooling	Capacity	kW	276.5	284.0	289.5	296.0
		kBtu/h	943.4	969.0	987.8	1010.0
	Power Input	kW	83.72	86.06	87.10	89.70
	EER	kW/kW	3.30	3.30	3.32	3.30
Heating	Capacity(Max/Nom)	kW	305.0 / 276.5	315.0 / 284.0	324.0 / 289.5	330.0 / 296.0
		kBtu/h	1040.7 / 943.4	1074.8 / 969.0	1105.5 / 987.8	1126.0 / 1010.0
	Power Input(Max/Nom)	kW	86.62 / 74.36	90.29 / 77.05	92.19 / 78.05	94.87 / 80.59
	COP(Max)	kW/kW	3.52	3.49	3.51	3.48
Ventilation	Air Flow Rate	m³/min	1238	1238	1292	1292
	Fan Quantity		8	8	8	8
	Static Pressure	Pa	110	110	110	110
Sound	Sound Pressure Level	dB(A)	72	72	72	73
	Type		Enhanced Vapor Injection Scroll Compressor			
Compressor	Compressor Quantity	pcs	8	8	8	8
	Type		R410A			
Refrigerant	Pre-charged Quantity	kg	10.60+10.60+10.60+11.50	10.60+10.60+10.60+11.50	10.60+10.60+11.50+11.50	10.60+10.60+11.50+11.50
	Net Weight	kg	378+378+378+400	378+378+378+401	377+378+401+401	378+378+401+401
	Gross Weight	kg	402+402+402+426	402+402+402+427	401+402+427+427	402+402+427+427
Dimensions	External(HxWxD)	mm	1730x (1350+1350+1350+1600) x750	1730x (1350+1350+1350+1600) x750	1730x (1350+1350+1600+1600) x750	1730x (1350+1350+1600+1600) x750
		mm	1930x (1420+1420+1420+1665) x790	1930x (1420+1420+1420+1665) x790	1930x (1420+1420+1665+1665) x790	1930x (1420+1420+1665+1665) x790
	Packing(HxWxD)	mm	1730x (1350+1350+1350+1600) x750	1730x (1350+1350+1350+1600) x750	1730x (1350+1350+1600+1600) x750	1730x (1350+1350+1600+1600) x750
		mm	1930x (1420+1420+1420+1665) x790	1930x (1420+1420+1420+1665) x790	1930x (1420+1420+1665+1665) x790	1930x (1420+1420+1665+1665) x790
Cabinet Color	Low Pressure Gas Line	mm(in.)	φ50.8(2)	φ50.8(2)	φ50.8(2)	φ50.8(2)
	High/Low Pressure Gas Line	mm(in.)	φ44.5(1-3/4)	φ44.5(1-3/4)	φ44.5(1-3/4)	φ44.5(1-3/4)
	Liquid Line	mm(in.)	φ25.4(1)	φ25.4(1)	φ25.4(1)	φ25.4(1)
Heat Pump Operation System	Gas Line	mm(in.)	φ50.8(2)	φ50.8(2)	φ50.8(2)	φ50.8(2)
	Liquid Line	mm(in.)	φ25.4(1)	φ25.4(1)	φ25.4(1)	φ25.4(1)
Connectable Indoor Units	Quantity	pcs	64	64	64	64
	Total Capacity		200%*1	200%*1	200%*1	200%*1
Piping Design	Height Difference Between ODU and IDU	m(above)	50(90*)	50(90*)	50(90*)	50(90*)
		m(below)	40(90*)	40(90*)	40(90*)	40(90*)
	Height Difference Between IDUs	m	15(30*)	15(30*)	15(30*)	15(30*)
	Max. Piping Length	m	165	165	165	165
Operation Range	Cooling	DB	-10°C~52°C	-10°C~52°C	-10°C~52°C	-10°C~52°C
	Heating	WB	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C

Notes:
 1. Rated cooling capacity and rated heating capacity are tested in the following conditions:
 Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
 Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 2. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
 3. The final appearance of outdoor units is subject to the actual products.
 *: If you have any questions, please contact with the technical engineer.
 **: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Heat Recovery



HP		106HP	108HP	110HP	112HP	
Model	Model	AVWT-1026FKFSA	AVWT-1048FKFSA	AVWT-1066FKFSA	AVWT-1088FKFSA	
	Modules	AVWT-232FKFSA	AVWT-232FKFSA	AVWT-250FKFSA	AVWT-272FKFSA	
		AVWT-250FKFSA	AVWT-272FKFSA	AVWT-272FKFSA	AVWT-272FKFSA	
		AVWT-272FKFSA	AVWT-272FKFSA	AVWT-272FKFSA	AVWT-272FKFSA	
Power Supply		AC 3φ, 380-415V/50/60Hz				
Cooling	Capacity	300.5	308.0	312.5	320.0	
	Capacity	kW				
	kBtu/h	1025.3	1050.9	1066.3	1091.8	
	Power Input	kW	90.99	93.33	94.63	96.97
EER	kW/kW	3.30	3.30	3.30	3.30	
Heating	Capacity(Max/Nom)	kW	335.0 / 300.5	345.0 / 308.0	350.0 / 312.5	360.0 / 320.0
	Capacity	kBtu/h	1143.0 / 1025.3	1177.1 / 1050.9	1194.2 / 1066.3	1228.3 / 1091.8
	Power Input(Max/Nom)	kW	95.76 / 81.42	99.46 / 84.13	100.34 / 84.96	104.05 / 87.67
	COP(Max)	kW/kW	3.50	3.47	3.49	3.46
Ventilation	Air Flow Rate	m³/min	1346	1346	1400	1400
	Fan Quantity		8	8	8	8
Sound	Static Pressure	Pa	110	110	110	110
	Sound Pressure Level	dB(A)	73	73	73	73
Compressor	Type	Enhanced Vapor Injection Scroll Compressor				
	Compressor Quantity	pcs	8	8	8	8
Refrigerant	Type	R410A				
	Pre-charged Quantity	kg	10.60+11.50+11.50+11.50	10.60+11.50+11.50+11.50	11.50+11.50+11.50+11.50	11.50+11.50+11.50+11.50
Weight	Net Weight	kg	378+400+401+401	378+401+401+401	400+401+401+401	401+401+401+401
	Gross Weight	kg	402+426+427+427	402+427+427+427	426+427+427+427	427+427+427+427
Dimensions	External(HxWxD)	mm	1730x (1350+1600+1600+1600) x750	1730x (1350+1600+1600+1600) x750	1730x (1600+1600+1600+1600) x750	1730x (1600+1600+1600+1600) x750
		mm	1930x (1420+1665+1665+1665) x790	1930x (1420+1665+1665+1665) x790	1930x (1665+1665+1665+1665) x790	1930x (1665+1665+1665+1665) x790
	Packing(HxWxD)	mm	1730x (1350+1600+1600+1600) x750	1730x (1350+1600+1600+1600) x750	1730x (1600+1600+1600+1600) x750	1730x (1600+1600+1600+1600) x750
		mm	1930x (1420+1665+1665+1665) x790	1930x (1420+1665+1665+1665) x790	1930x (1665+1665+1665+1665) x790	1930x (1665+1665+1665+1665) x790
Cabinet Color	Low Pressure Gas Line	mm(in.)	φ50.8(2)	φ50.8(2)	φ50.8(2)	φ50.8(2)
	High/Low Pressure Gas Line	mm(in.)	φ44.5(1-3/4)	φ44.5(1-3/4)	φ44.5(1-3/4)	φ44.5(1-3/4)
	Liquid Line	mm(in.)	φ25.4(1)	φ25.4(1)	φ25.4(1)	φ25.4(1)
Heat Pump Operation System	Gas Line	mm(in.)	φ50.8(2)	φ50.8(2)	φ50.8(2)	φ50.8(2)
	Liquid Line	mm(in.)	φ25.4(1)	φ25.4(1)	φ25.4(1)	φ25.4(1)
Connectable Indoor Units	Quantity	pcs	64	64	64	64
	Total Capacity	-	200%*1	200%*1	200%*1	200%*1
Piping Design	Height Difference Between ODU and IDU	m(above)	50(90*)	50(90*)	50(90*)	50(90*)
	Height Difference Between IDUs	m(below)	40(90*)	40(90*)	40(90*)	40(90*)
	Max. Piping Length	m	15(30*)	15(30*)	15(30*)	15(30*)
	Max. Piping Length	m	165	165	165	165
Operation Range	Cooling	DB	-10°C~52°C	-10°C~52°C	-10°C~52°C	-10°C~52°C
	Heating	WB	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C

Notes:
 1. Rated cooling capacity and rated heating capacity are tested in the following conditions:
 Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
 Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 2. The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
 3. The final appearance of outdoor units is subject to the actual products.
 *: If you have any questions, please contact with the technical engineer.
 **: For detailed information, please contact with Hisense's technical staff.

Switch Box


Introduction

Used for heat recovery systems to achieve simultaneous cooling and heating in a system, it is very important to realize installation flexibility and reduce costs.

Advantage

- Enrich the products (1,4,8,12,16).
- Maximize capacity to 16kW or more.
- Require no drain pipes or drainage connections.
- Combine between single branch and multi-branch flexibility.
- Enable fewer connections, hooks and service parts for easy installation.

Original Products



New Switch Box



Model	Single Branch		Multi Branch						
	HCHS-N06XA	HCHS-N10XA	HCHM-N04XA	HCHM-N08XA	HCHM-N12XA	HCHM-N16XA			
Appearance									
Electrical	Power Supply	AC 1φ, 220-240V/50/60Hz							
	Power Input	W	5	5	11.2	22.4	33.6	44.8	
Maximum Total Capacity Index	kW	16	28	44.8	85	85	85		
Number of Branches	-	1	1	4	8	12	16		
Maximum Capacity Index per Branch	kW	-	-	16	16	16	16		
Maximum Connectable Indoor Units per Branch	pics	8	8	8	8	6	6		
Dimensions (H x W x D)	mm	191 x 301 x 214	191 x 301 x 214	260 x 303 x 352	260 x 543 x 352	260 x 783 x 352	260 x 1023 x 352		
Refrigerant	R410A								
Refrigerant	Outdoor Unit Side	Gas Line (High and Low Pressure Side)	mm (in.)	φ15.88(5/8)	φ15.88(5/8)	φ22.20(7/8)	φ22.20(7/8)	φ25.40(1)	φ28.58(1-1/8)
		Gas Line (Suction Gas)	mm (in.)	φ19.05(3/4)	φ19.05(3/4)	φ25.40(1)	φ28.58(1-1/8)	φ28.58(1-1/8)	φ31.75(1-1/4)
		Liquid Line	mm (in.)	Not Included	Not Included	φ12.70(1/2)	φ12.70(1/2)	φ15.88(5/8)	φ19.05(3/4)
Piping	Indoor Unit Side	Gas Line	mm (in.)	φ15.88(5/8)	φ19.05(3/4)	φ15.88(5/8)	φ15.88(5/8)	φ15.88(5/8)	φ15.88(5/8)
		Liquid Line	mm (in.)	Not Included	Not Included	φ9.52(3/8)	φ9.52(3/8)	φ9.52(3/8)	φ9.52(3/8)
Net Weight	kg	6.3	6.4	14.1	25.2	35.5	46.7		
Noise Level	Sound Pressure Level	dB (A)	33	33	31	31	34	34	
	Max Sound	dB (A)	46	46	43	46	48	49	

Hydro Box

Specification for Hydro Box

Model		AHM-080FJFAA	AHM-160FJFAA
Power Supply		AC 1 Φ, 220-240V/50Hz AC 1 Φ, 220V/60Hz	
Cooling Capacity (A 35/24°C/W 12-7°C)		7.5	12.5
Heating Capacity (A 7/6°C/W 30-35°C)		8	16
Power Input		0.08(3.08)	0.14(3.14)
Dimensions H × W × D		890 × 520 × 320	890 × 520 × 320
Packing Dimensions H × W × D		1120 × 595 × 462	1120 × 595 × 462
Weight		55	58
		72	75
Heat Exchanger		Plate Heat Exchanger	
Heat Exchanger Insulation Material		Elastomeric Foam	
Heating		20 to 55	20 to 55
DHW(with electric heater)		35 to 75	35 to 75
Cooling		5 to 20	5 to 20
Sound Pressure		33	33
Sound Power		46	46
Piping Connections		mm	mm
Gas		φ15.88	φ15.88
Liquid		φ9.53	φ9.53
Type		DC Motor	
Speed		Inverter Control	
Water Pump		m	m
Pumping Head		12.5	12.5
Pumping Head for Water Circuit		5	5
Power Input		100	160
Booster Heating		3	3
Water Filter		mm	mm
Diameter Perforations		0.85	0.85
Material		Hpb59-1	Hpb59-1
Piping Connections Diameter		G1-1/4"	G1-1/4"
Shut off Valve		Yes	Yes
Water Circuit		Yes	Yes
Drain Valve		Yes	Yes
Safety Valve		3	3
Air Purge Valve		Yes	Yes
Nominal Water		m ³ /h	m ³ /h
		1.38	2.75
Expansion Vessel		L	L
Volume		8	8
Max. Water Pressure		3	3

Operation Range

Indoor Unit Cooling

	Maximum	Minimum
Indoor	32°C DB / 23°C WB	21°C DB / 15°C WB
Outdoor	52°C DB*	-10°C DB

Indoor Unit Heating

	Maximum	Minimum
Indoor	27°C DB	15°C DB
Outdoor	16.5°C WB	-25°C WB**

Hydro Box Cooling

	Maximum	Minimum
Inlet Water	25°C	10°C
Outdoor	48°C DB	10°C DB

Hydro Box Heating (Floor Heating)

	Maximum	Minimum
Inlet Water	54°C	10°C
Outdoor	16.5°C WB	-25°C WB**

Hydro Box Heating (DHW)

	Maximum	Minimum
Inlet Water	54°C	10°C
Outdoor	43°C WB	-25°C WB**

DB: Dry Bulb
WB: Wet Bulb
(*): 48°C DB ~ 52°C DB, Operation Control Range
(**): -20°C WB ~ -25°C WB, Operation Control Range




Hi-FLEXi S Series

(Powerful Heating with EVI Compressor)



Piping Length

With extra long pipe, the height difference between the indoor unit and outdoor unit is up to 90 meters*, which makes installation more flexible.



*Note: For detailed information, please contact Hisense's technical staff.

Hi-FLEXi S Series



HP		8HP	10HP	12HP	14HP	16HP	18HP
Model		AVWT-76HKSS	AVWT-96HKSS	AVWT-114HKSS	AVWT-136HKSS	AVWT-154HKSS	AVWT-170HKSS
Model	Modules	—	—	—	—	—	—
Power Supply		AC 3Φ, 380-415V/50/60Hz					
Cooling	Capacity	kW	22.4	28.0	33.5	40.0	45.0
		kBtu/h	76.4	95.5	114.3	136.5	153.5
	Power Input	kW	5.21	7.00	8.65	10.53	12.50
	EER	kW/kW	4.30	4.00	3.87	3.80	3.60
Heating	Capacity	kW	25.0	31.5	37.5	45.0	50.0
		kBtu/h	85.3	107.5	128.0	153.5	170.6
	Power Input	kW	5.77	7.59	9.21	11.72	13.70
Ventilation	COP	kW/kW	4.33	4.15	4.07	3.84	3.30
	Air Flow Rate	m³/min	183	183	183	200	200
	Fan Quantity		1	1	1	2	2
Sound	Static Pressure	Pa	110	110	110	110	110
	Sound Pressure Level	dB(A)	59	60	62	62	62
Compressor	Type	Enhanced Vapor Injection Compressor					
	Compressor Quantity	pcs	1	1	1	1	2
Refrigerant	Type	R410A					
	Pre-charged Quantity	kg	7.4	8.6	9.5	12.0	13.2
Weight	Net Weight	kg	224	244	245	297	347
	Gross Weight	kg	243	263	265	321	371
Dimensions	External(HxWxD)	mm	1730x950x750	1730x950x750	1730x950x750	1730x1210x750	1730x1210x750
	Packing(HxWxD)	mm	1930x1015x790	1930x1015x790	1930x1015x790	1930x1275x790	1930x1275x790
Cabinet Color			Ivory White	Ivory White	Ivory White	Ivory White	Ivory White
Ref. Piping	Gas	mm	φ19.05	φ22.20	φ25.40	φ25.40	φ28.60
		inch	3/4	7/8	1	1	1-1/8
	Liquid	mm	φ9.53	φ9.53	φ12.70	φ12.70	φ15.88
		inch	3/8	3/8	1/2	1/2	5/8
Connectable Indoor Units	Quantity	pcs	13	16	19	23	29
	Total Capacity	—	50%~150%	50%~150%	50%~150%	50%~150%	50%~150%
Piping Design	Height Difference Between ODU and IDU	m(above)	50 (90**)	50 (90**)	50 (90**)	50 (90**)	50 (90**)
		m(below)	40 (90**)	40 (90**)	40 (90**)	40 (90**)	40 (90**)
	Height Difference Between IDUs	m	15 (30**)	15 (30**)	15 (30**)	15 (30**)	15 (30**)
	Max. Piping Length	m	165	165	165	165	165
Operation Range	Cooling	DB	-5°C~52°C	-5°C~52°C	-5°C~52°C	-5°C~52°C	-5°C~52°C
	Heating	WB	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C

- Notes:
- Rated cooling capacity and rated heating capacity are tested in the following conditions:
Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 - The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
 - The final appearance of outdoor units is subject to the actual products.
 - For height difference between ODU & IDU more than 50(40)m, please contact our professional engineer.
 - When the operation temperature is under 48°C ~ 52°C or -25°C ~ -20°C, please contact our professional engineer.
- ** : For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Series



HP		20HP	22HP	24HP	26HP	28HP
Model		AVWT-190HKSS	AVWT-212HKSS	AVWT-232HKSS	AVWT-250HKSS	AVWT-272HKSS
Model	Modules	—	—	—	—	—
Power Supply		AC 3Φ, 380-415V/50/60Hz				
Cooling	Capacity	kW	56.0	61.5	68.0	72.5
		kBtu/h	191.1	209.8	232.1	246.5
	Power Input	kW	17.90	20.50	22.82	24.58
	EER	kW/kW	3.13	3.00	2.98	2.95
Heating	Capacity	kW	63.0	69.0	75.0	80.0
		kBtu/h	215.0	235.4	255.0	272.0
	Power Input	kW	19.87	22.48	24.59	26.67
Ventilation	COP	kW/kW	3.17	3.07	3.05	3.00
	Air Flow Rate	m³/min	267	296	296	350
	Fan Quantity		2	2	2	2
Sound	Static Pressure	Pa	110	110	110	110
	Sound Pressure Level	dB(A)	63	64	66	67
Compressor	Type	Enhanced Vapor Injection Scroll Compressor				
	Compressor Quantity	pcs	2	2	2	2
Refrigerant	Type	R410A				
	Pre-charged Quantity	kg	14.3	15.5	15.5	17.3
Weight	Net Weight	kg	361	369	370	414
	Gross Weight	kg	395	396	397	446
Dimensions	External(HxWxD)	mm	1730x1350x750	1730x1350x750	1730x1350x750	1730x1600x750
	Packing(HxWxD)	mm	1930x1420x790	1930x1420x790	1930x1420x790	1930x1665x790
Cabinet Color			Ivory White	Ivory White	Ivory White	Ivory White
Ref. Piping	Gas	mm	φ28.60	φ28.60	φ28.60	φ31.75
		inch	1-1/8	1-1/8	1-1/8	1-1/4
	Liquid	mm	φ15.88	φ15.88	φ15.88	φ19.05
		inch	5/8	5/8	5/8	3/4
Connectable Indoor Units	Quantity	pcs	33	36	40	43
	Total Capacity	—	50%~150%	50%~150%	50%~150%	50%~150%
Piping Design	Height Difference Between ODU and IDU	m(above)	50 (90**)	50 (90**)	50 (90**)	50 (90**)
		m(below)	40 (90**)	40 (90**)	40 (90**)	40 (90**)
	Height Difference Between IDUs	m	15 (30**)	15 (30**)	15 (30**)	15 (30**)
	Max. Piping Length	m	165	165	165	165
Operation Range	Cooling	DB	-5°C~52°C	-5°C~52°C	-5°C~52°C	-5°C~52°C
	Heating	WB	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C	-25°C~16.5°C

- Notes:
- Rated cooling capacity and rated heating capacity are tested in the following conditions:
Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 - The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
 - The final appearance of outdoor units is subject to the actual products.
 - For height difference between ODU & IDU more than 50(40)m, please contact our professional engineer.
 - When the operation temperature is under 48°C ~ 52°C or -25°C ~ -20°C, please contact our professional engineer.
- ** : For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Series



HP		30HP	32HP	34HP	36HP	38HP	
Model		AVWT-290HKSS	AVWT-308HKSS	AVWT-324HKSS	AVWT-344HKSS	AVWT-360HKSS	
Model	Modules	AVWT-154HKSS AVWT-136HKSS	AVWT-154HKSS AVWT-154HKSS	AVWT-170HKSS AVWT-154HKSS	AVWT-190HKSS AVWT-154HKSS	AVWT-190HKSS AVWT-170HKSS	
	Power Supply	AC 3 ϕ , 380-415V/50/60Hz					
Cooling	Capacity	85.0	90.0	95.0	101.0	106.0	
	Capacity	290.0	307.0	324.1	344.6	361.7	
	Power Input	23.03	25.00	28.13	30.40	33.53	
	EER	3.69	3.60	3.38	3.32	3.16	
Heating	Capacity	95.0	100.0	106.0	113.0	119.0	
	Capacity	324.1	341.2	361.7	385.6	406.1	
	Power Input	25.42	27.40	30.67	33.57	36.84	
Heating	COP	3.74	3.65	3.46	3.37	3.23	
	Air Flow Rate	400	400	400	467	467	
	Fan Quantity	4	4	4	4	4	
Ventilation	Static Pressure	110	110	110	110	110	
	Sound Pressure Level	67	67	67	67	67	
Compressor	Type	Enhanced Vapor Injection Scroll Compressor					
	Compressor Quantity	2	2	3	3	4	
Refrigerant	Type	R410A					
	Pre-charged Quantity	24.0	24.0	25.20	26.30	27.5	
Weight	Net Weight	595	596	645	659	708	
	Gross Weight	643	644	693	717	766	
Dimensions	External(HxWxD)	1730x (1210+1210) x750	1730x (1210+1210) x750	1730x (1210+1210) x750	1730x (1210+1350) x750	1730x (1210+1350) x750	
	Packing(HxWxD)	1930x (1275+1275) x790	1930x (1275+1275) x790	1930x (1275+1275) x790	1930x (1275+1420) x790	1930x (1275+1420) x790	
	Cabinet Color	Ivory White					
Ref. Piping	Gas	mm	ϕ 31.75	ϕ 31.75	ϕ 38.1	ϕ 38.1	
		inch	1-1/4	1-1/4	1-1/2	1-1/2	
	Liquid	mm	ϕ 19.05	ϕ 19.05	ϕ 19.05	ϕ 19.05	ϕ 19.05
		inch	3/4	3/4	3/4	3/4	3/4
Connectable Indoor Units	Quantity	49	52	55	59	62	
	Total Capacity	50%~150%					
Piping Design	Height Difference Between ODU and IDU	m(above)	50 (90 ^{**})	50 (90 ^{**})	50 (90 ^{**})	50 (90 ^{**})	
		m(below)	40 (90 ^{**})	40 (90 ^{**})	40 (90 ^{**})	40 (90 ^{**})	
	Height Difference Between IDUs	15 (30 ^{**})	15 (30 ^{**})	15 (30 ^{**})	15 (30 ^{**})	15 (30 ^{**})	
	Max. Piping Length	165	165	165	165	165	
Operation Range	Cooling	-5 $^{\circ}$ C~52 $^{\circ}$ C					
	Heating	-25 $^{\circ}$ C~16.5 $^{\circ}$ C					

Notes:

- Rated cooling capacity and rated heating capacity are tested in the following conditions:
Cooling conditions: indoor air inlet temperature: 27 $^{\circ}$ C DB 19 $^{\circ}$ C WB, outdoor air inlet temperature: 35 $^{\circ}$ C DB, pipe length: 7.5m, pipe height difference: 0m.
Heating conditions: indoor air inlet temperature: 20 $^{\circ}$ C DB, outdoor air inlet temperature: 7 $^{\circ}$ C DB 6 $^{\circ}$ C WB, pipe length: 7.5m, pipe height difference: 0m.
- The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
- The final appearance of outdoor units is subject to the actual products.
- For height difference between ODU & IDU more than 50(40)m, please contact our professional engineer.
- When the operation temperature is under 48 $^{\circ}$ C ~ 52 $^{\circ}$ C or -25 $^{\circ}$ C ~ -20 $^{\circ}$ C, please contact our professional engineer.

**: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Series



HP		40HP	42HP	44HP	46HP	48HP
Model		AVWT-380HKSS	AVWT-402HKSS	AVWT-422HKSS	AVWT-444HKSS	AVWT-464HKSS
Model	Modules	AVWT-190HKSS AVWT-190HKSS	AVWT-232HKSS AVWT-170HKSS	AVWT-232HKSS AVWT-190HKSS	AVWT-232HKSS AVWT-212HKSS	AVWT-232HKSS AVWT-232HKSS
	Power Supply	AC 3 ϕ , 380-415V/50/60Hz				
Cooling	Capacity	112.0	118.0	124.0	129.5	136.0
	Capacity	382.1	402.7	432.2	441.9	464.2
	Power Input	35.80	38.45	40.72	43.32	45.64
	EER	3.13	3.07	3.05	2.99	2.98
Heating	Capacity	126.0	131.0	138.0	144.0	150.0
	Capacity	430.0	446.1	470.0	490.4	510.0
	Power Input	39.74	41.56	44.46	47.07	49.18
Heating	COP	3.17	3.15	3.10	3.06	3.05
	Air Flow Rate	534	496	563	592	592
	Fan Quantity	4	4	4	4	4
Ventilation	Static Pressure	110	110	110	110	110
	Sound Pressure Level	67	67	68	68	69
Compressor	Type	Enhanced Vapor Injection Scroll Compressor				
	Compressor Quantity	4	4	4	4	4
Refrigerant	Type	R410A				
	Pre-charged Quantity	28.6	28.7	29.8	31.0	31.0
Weight	Net Weight	722	717	731	739	740
	Gross Weight	790	768	792	793	794
Dimensions	External(HxWxD)	1730x (1350+1350) x750	1730x (1210+1350) x750	1730x (1350+1350) x750	1730x (1350+1350) x750	1730x (1350+1350) x750
	Packing(HxWxD)	1930x (1420+1420) x790	1930x (1275+1420) x790	1930x (1420+1420) x790	1930x (1420+1420) x790	1930x (1420+1420) x790
	Cabinet Color	Ivory White				
Ref. Piping	Gas	mm	ϕ 38.1	ϕ 38.1	ϕ 38.1	ϕ 41.3
		inch	1-1/2	1-1/2	1-1/2	1-5/8
	Liquid	mm	ϕ 19.05	ϕ 19.05	ϕ 19.05	ϕ 22.2
		inch	3/4	3/4	3/4	7/8
Connectable Indoor Units	Quantity	64	64	64	64	64
	Total Capacity	50%~150%				
Piping Design	Height Difference Between ODU and IDU	m(above)	50 (90 ^{**})	50 (90 ^{**})	50 (90 ^{**})	50 (90 ^{**})
		m(below)	40 (90 ^{**})	40 (90 ^{**})	40 (90 ^{**})	40 (90 ^{**})
	Height Difference Between IDUs	15 (30 ^{**})	15 (30 ^{**})	15 (30 ^{**})	15 (30 ^{**})	15 (30 ^{**})
	Max. Piping Length	165	165	165	165	165
Operation Range	Cooling	-5 $^{\circ}$ C~52 $^{\circ}$ C				
	Heating	-25 $^{\circ}$ C~16.5 $^{\circ}$ C				

Notes:

- Rated cooling capacity and rated heating capacity are tested in the following conditions:
Cooling conditions: indoor air inlet temperature: 27 $^{\circ}$ C DB 19 $^{\circ}$ C WB, outdoor air inlet temperature: 35 $^{\circ}$ C DB, pipe length: 7.5m, pipe height difference: 0m.
Heating conditions: indoor air inlet temperature: 20 $^{\circ}$ C DB, outdoor air inlet temperature: 7 $^{\circ}$ C DB 6 $^{\circ}$ C WB, pipe length: 7.5m, pipe height difference: 0m.
- The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
- The final appearance of outdoor units is subject to the actual products.
- For height difference between ODU & IDU more than 50(40)m, please contact our professional engineer.
- When the operation temperature is under 48 $^{\circ}$ C ~ 52 $^{\circ}$ C or -25 $^{\circ}$ C ~ -20 $^{\circ}$ C, please contact our professional engineer.

**: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Series



HP		50HP	52HP	54HP	56HP
Model		AVWT-482HKSS	AVWT-504HKSS	AVWT-522HKSS	AVWT-544HKSS
Model	Modules	AVWT-250HKSS AVWT-232HKSS	AVWT-272HKSS AVWT-232HKSS	AVWT-272HKSS AVWT-250HKSS	AVWT-272HKSS AVWT-272HKSS
	Power Supply	AC 3 ϕ , 380-415V/50/60Hz			
Cooling	Capacity	kW 478.6	148.0 504.1	152.5 518.5	160.0 544.0
	Power Input	kW 47.40	50.41	52.17	55.18
	EER	kW/kW 2.96	2.94	2.92	2.90
	Capacity	kW 155.0	165.0	170.0	180.0
Heating	Capacity	kW 527.0	561.0	578.0	612.0
	Power Input	kW 51.26	55.00	57.08	60.82
	COP	kW/kW 3.02	3.00	2.98	2.96
Ventilation	Air Flow Rate	m ³ /min 646	646	700	700
	Fan Quantity	4	4	4	4
	Static Pressure	Pa 110	110	110	110
Sound	Sound Pressure Level	dB(A) 70	70	70	70
	Type	Enhanced Vapor Injection Scroll Compressor			
Compressor	Compressor Quantity	pcs 4	4	4	4
	Type	R410A			
Refrigerant	Pre-charged Quantity	kg 32.8	32.8	34.6	34.6
	Net Weight	kg 784	785	829	830
Weight	Gross Weight	kg 843	844	893	894
	External(HxWxD)	mm 1730x (1350+1600) x750	1730x (1350+1600) x750	1730x (1600+1600) x750	1730x (1600+1600) x750
Dimensions	Packing(HxWxD)	mm 1930x (1420+1665) x790	1930x (1420+1665) x790	1930x (1665+1665) x790	1930x (1665+1665) x790
	Cabinet Color	Ivory White			
Ref. Piping	Gas	mm ϕ 41.3	ϕ 41.3	ϕ 41.3	ϕ 41.3
		inch 1-5/8	1-5/8	1-5/8	1-5/8
	Liquid	mm ϕ 22.2	ϕ 22.2	ϕ 22.2	ϕ 22.2
		inch 7/8	7/8	7/8	7/8
Connectable Indoor Units	Quantity	pcs 64	64	64	64
	Total Capacity	– 50%–150%	50%–150%	50%–150%	50%–150%
Piping Design	Height Difference Between ODU and IDU	m(above) 50 (90 ^{**})	50 (90 ^{**})	50 (90 ^{**})	50 (90 ^{**})
		m(below) 40 (90 ^{**})	40 (90 ^{**})	40 (90 ^{**})	40 (90 ^{**})
	Height Difference Between IDUs	m 15 (30 ^{**})	15 (30 ^{**})	15 (30 ^{**})	15 (30 ^{**})
	Max. Piping Length	m 165	165	165	165
Operation Range	Cooling	DB –5°C–52°C	–5°C–52°C	–5°C–52°C	–5°C–52°C
	Heating	WB –25°C–16.5°C	–25°C–16.5°C	–25°C–16.5°C	–25°C–16.5°C

Notes:

- Rated cooling capacity and rated heating capacity are tested in the following conditions:
Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
- The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
- The final appearance of outdoor units is subject to the actual products.
- For height difference between ODU & IDU more than 50(40)m, please contact our professional engineer.
- When the operation temperature is under 48°C ~ 52°C or –25°C ~ –20°C, please contact our professional engineer.

*: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi S Series



HP		58HP	60HP	62HP	64HP
Model		AVWT-552HKSS	AVWT-570HKSS	AVWT-592HKSS	AVWT-612HKSS
Model	Modules	AVWT-212HKSS AVWT-170HKSS	AVWT-190HKSS AVWT-190HKSS	AVWT-232HKSS AVWT-190HKSS	AVWT-232HKSS AVWT-190HKSS
	Power Supply	AC 3 ϕ , 380-415V/50/60Hz			
Cooling	Capacity	kW 161.5	168.0	174.0	180.0
	Power Input	kW 51.76	53.70	56.35	58.62
	EER	kW/kW 3.12	3.13	3.09	3.07
	Capacity	kW 181.0	189.0	194.0	201.0
Heating	Capacity	kW 617.6	645.0	661.1	685.0
	Power Input	kW 56.42	59.61	61.43	64.33
	COP	kW/kW 3.21	3.17	3.16	3.12
Ventilation	Air Flow Rate	m ³ /min 696	801	763	830
	Fan Quantity	6	6	6	6
	Static Pressure	Pa 110	110	110	110
Sound	Sound Pressure Level	dB(A) 70	70	70	70
	Type	Enhanced Vapor Injection Scroll Compressor			
Compressor	Compressor Quantity	pcs 6	6	6	6
	Type	R410A			
Refrigerant	Pre-charged Quantity	kg 41.9	42.9	43.0	44.1
	Net Weight	kg 1063	1083	1078	1092
Weight	Gross Weight	kg 1138	1185	1163	1187
	External(HxWxD)	mm 1730x (1210+1210+1350) x750	1730x (1350+1350+1350) x750	1730x (1210+1350+1350) x750	1730x (1350+1350+1350) x750
Dimensions	Packing(HxWxD)	mm 1930x (1275+1275+1420) x790	1930x (1420+1420+1420) x790	1930x (1275+1420+1420) x790	1930x (1420+1420+1420) x790
	Cabinet Color	Ivory White			
Ref. Piping	Gas	mm ϕ 44.5	ϕ 44.5	ϕ 44.5	ϕ 44.5
		inch 1-3/4	1-3/4	1-3/4	1-3/4
	Liquid	mm ϕ 22.2	ϕ 22.2	ϕ 22.2	ϕ 22.2
		inch 7/8	7/8	7/8	7/8
Connectable Indoor Units	Quantity	pcs 64	64	64	64
	Total Capacity	– 50%–150%	50%–150%	50%–150%	50%–150%
Piping Design	Height Difference Between ODU and IDU	m(above) 50 (90 ^{**})	50 (90 ^{**})	50 (90 ^{**})	50 (90 ^{**})
		m(below) 40 (90 ^{**})	40 (90 ^{**})	40 (90 ^{**})	40 (90 ^{**})
	Height Difference Between IDUs	m 15 (30 ^{**})	15 (30 ^{**})	15 (30 ^{**})	15 (30 ^{**})
	Max. Piping Length	m 165	165	165	165
Operation Range	Cooling	DB –5°C–52°C	–5°C–52°C	–5°C–52°C	–5°C–52°C
	Heating	WB –25°C–16.5°C	–25°C–16.5°C	–25°C–16.5°C	–25°C–16.5°C

Notes:

- Rated cooling capacity and rated heating capacity are tested in the following conditions:
Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
- The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be included at the scene.
- The final appearance of outdoor units is subject to the actual products.
- For height difference between ODU & IDU more than 50(40)m, please contact our professional engineer.
- When the operation temperature is under 48°C ~ 52°C or –25°C ~ –20°C, please contact our professional engineer.


*: For detailed information, please contact with Hisense's technical staff.

Hi-FLEXi **S** mavo+ Series

Extra Long Pipe Design



With extra long pipe, the height difference between the indoor unit and outdoor unit is up to 90 meters*, which makes installation more flexible.



Maximum height difference of indoor units: 15m(30m*)

Maximum length from the first branch pipe to the farthest indoor unit: 90m

Largest pipe length between outdoor units: 10 meters


Maximum height difference between indoor and outdoor units:
when the outdoor unit is above: 50m(90m*)
when the outdoor unit is below: 40m(90m*)

Maximum actual length of a single pipe: 165 meters
Total length of pipes: 1000 meters

*Note: For detailed information, please contact Hisense's technical staff.

High-efficiency Compressor

Hi-FLEXi S mavo+ series adopts a new generation of scroll compressor, and it has an excellent mechanism called as FCM (Frame Compliant Mechanism) which will optimally increase the performance of the whole compressor, especially for operation under low load.



Hi-FLEXi S mavo+ Series




HP		104HP	106HP	108HP	110HP	112HP	
Model	Model	AVWT-1008HKFSEA	AVWT-1026HKFSEA	AVWT-1048HKFSEA	AVWT-1066HKFSEA	AVWT-1088HKFSEA	
	Modules	AVWT-232HKFSEA	AVWT-232HKFSEA	AVWT-232HKFSEA	AVWT-250HKFSEA	AVWT-272HKFSEA	
		AVWT-232HKFSEA	AVWT-250HKFSEA	AVWT-272HKFSEA	AVWT-272HKFSEA	AVWT-272HKFSEA	
		AVWT-272HKFSEA	AVWT-272HKFSEA	AVWT-272HKFSEA	AVWT-272HKFSEA	AVWT-272HKFSEA	
Power Supply		AC 3φ, 380-415V/50/60Hz					
Cooling	Capacity	296.0	300.5	308.0	312.5	320.0	
	kW	1010.0	1025.0	1050.0	1065.0	1090.0	
	Power Input	87.96	88.91	92.17	93.12	96.39	
	EER	3.37	3.38	3.34	3.36	3.32	
Heating	Capacity	330.0	335.0	345.0	350.0	360.0	
	kW	1125.0	1145.0	1175.0	1195.0	1230.0	
	Power Input	92.57	93.83	97.42	98.68	102.27	
Ventilation	COP	3.56	3.57	3.54	3.55	3.52	
	Air Flow Rate	1292	1346	1346	1400	1400	
	Fan Quantity	8	8	8	8	8	
Sound Pressure Level	Static Pressure	110	110	110	110	110	
	Normal Mode	70	70	70	70	70	
	Night Shift Mode	55	55	55	55	55	
Compressor	Type	Scroll Compressor					
	Compressor Quantity	8	8	8	8	8	
Refrigerant	Type	R410A					
	Pre-charged Quantity	12.2+12.2+12.0+12.0	12.2+12.0+12.0+12.0	12.2+12.0+12.0+12.0	12.0+12.0+12.0+12.0	12.0+12.0+12.0+12.0	
Weight	Net Weight	365+365+392+392	365+391+392+392	365+392+392+392	391+392+392+392	392+392+392+392	
	Gross Weight	402+402+434+434	402+433+434+434	402+434+434+434	433+434+434+434	434+434+434+434	
Dimensions	External(HxWxD)	mm	1730x (1350+1350+1600+1600)	1730x (1350+1600+1600+1600)	1730x (1350+1600+1600+1600)	1730x (1600+1600+1600+1600)	1730x (1600+1600+1600+1600)
			x750	x750	x750	x750	x750
	Packing(HxWxD)	mm	1950x (1420+1420+1665+1665)	1950x (1420+1665+1665+1665)	1950x (1420+1665+1665+1665)	1950x (1665+1665+1665+1665)	1950x (1665+1665+1665+1665)
			x790	x790	x790	x790	x790
Cabinet Color		Ivory White	Ivory White	Ivory White	Ivory White	Ivory White	
Ref. Piping	Gas	mm	φ50.8	φ50.8	φ50.8	φ50.8	φ50.8
		inch	2	2	2	2	2
	Liquid	mm	φ25.4	φ25.4	φ25.4	φ25.4	φ25.4
inch		1	1	1	1	1	
Connectable Indoor Units	Quantity	64	64	64	64	64	
	Total Capacity	50%-150%	50%-150%	50%-150%	50%-150%	50%-150%	
Piping Design	Height Difference Between ODU and IDU	m(above)	50(90**)	50(90**)	50(90**)	50(90**)	
		m(below)	40(90**)	40(90**)	40(90**)	40(90**)	
	Height Difference Between IDUs	m	30	30	30	30	
Operation Range*2	Max. Piping Length	m	1000	1000	1000	1000	
	Cooling	DB	-5°C-52°C	-5°C-52°C	-5°C-52°C	-5°C-52°C	-5°C-52°C
	Heating	WB	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C	-25°C-16.5°C	

Notes:
 1. Rated capacity is tested in the following conditions:
 Pipe length: 7.5m, Pipe height difference: 0m; Cooling operation: indoor air inlet temperature 27°CDB 19°CWB, outdoor ambient temperature 35°CDB;
 Heating operation: indoor air inlet temperature 20°CDB, outdoor ambient temperature 7°CDB 6°CWB.
 2. The above noise values are measured in the anechoic chamber without reflected echo. Measurement point: 1 meter from the service cover surface and 1.5 meters from floor level.
 *: For height difference between ODU & IDU more than 50(40)m, please contact with our professional engineer.
 **: When the operation temperature is under 48°C DB ~ 52°C DB or -25°C WB ~ -20°C WB, the system may be in intermittent operation. Please contact with our professional engineer.

Hi-FLEXi X3 Series

High Performance Beyond Expectations


- 1 Wide capacity range 8~112HP
- 2 High-efficiency twin rotary compressor
- 3 Triple backup operation
- 4 Automatic refrigerant recycling



- 5 PCB refrigerant cooling technology



- 7 Automatic refrigerant charging



- 6 G-type heat exchanger with higher heat exchange efficiency

Hi-FLEXi X3 Series



HP		30HP	32HP	34HP	36HP
Model		AVWT-290HKFXE	AVWT-308HKFXE	AVWT-326HKFXE	AVWT-344HKFXE
Model	Modules	AVWT-154HKFXE AVWT-136HKFXE	AVWT-154HKFXE AVWT-154HKFXE	AVWT-190HKFXE AVWT-136HKFXE	AVWT-190HKFXE AVWT-154HKFXE
	Power Supply	AC 3Φ, 380~415V/50Hz, 380V/60Hz			
Cooling	Capacity	kW 85.0	90.0	96.0	101.0
	kBtu/h	290.0	307.0	327.6	344.6
	Power Input	kW 24.4	26.2	28.5	30.2
	EER	kW/kW 3.48	3.44	3.37	3.34
Heating	Capacity	kW 95.0	100.0	108.0	113.0
	kBtu/h	324.1	341.2	368.5	385.6
	Power Input	kW 24.2	26.0	27.8	29.6
	COP	kW/kW 3.93	3.85	3.89	3.82
Ventilation	Air Flow Rate	m ³ /min 415	420	472	477
	Fan Quantity	4	4	4	4
	Static Pressure	Pa 110	110	110	110
Sound Pressure Level	Normal Mode	dB(A) 64	64	64	64
	Night Shift Mode	dB(A) 49	49	49	49
Compressor	Type	Twin Rotary			
	Compressor Quantity	pcs 2	2	3	3
Refrigerant	Type	R410A			
	Pre-charged Quantity	kg 16.2	16.2	19.0	19.0
Weight	Net Weight	kg 517	518	590	591
	Gross Weight	kg 557	558	635	636
Dimensions	External(HxWxD)	mm 1730x (1210+1210) x750	1730x (1210+1210) x750	1730x (1210+1350) x750	1730x (1210+1350) x750
	Packing(HxWxD)	mm 1950x (1275+1275) x790	1950x (1275+1275) x790	1950x (1275+1420) x790	1950x (1275+1420) x790
Cabinet Color		Ivory White	Ivory White	Ivory White	Ivory White
Ref. Piping	Gas	mm φ31.75	φ31.75	φ38.10	φ38.10
		inch 1-1/4	1-1/4	1-1/2	1-1/2
	Liquid	mm φ19.05	φ19.05	φ19.05	φ19.05
		inch 3/4	3/4	3/4	3/4
Connectable Indoor Units	Quantity	pcs 50	53	56	59
	Total Capacity	- 50%~150%	50%~150%	50%~150%	50%~150%
Piping Design	Height Difference Between ODU and IDU	m(above) 50(90*)	50(90*)	50(90*)	50(90*)
		m(below) 40(90*)	40(90*)	40(90*)	40(90*)
	Height Difference Between IDUs	m 30	30	30	30
	Max. Piping Length	m 1000	1000	1000	1000
Operation Range*2	Cooling	DB -5°C~54°C	-5°C~54°C	-5°C~54°C	-5°C~54°C
	Heating	WB -21°C~16.5°C	-21°C~16.5°C	-21°C~16.5°C	-21°C~16.5°C

Notes:

1. Rated capacity is tested in the following conditions:

Pipe length: 7.5m, Pipe height difference: 0m; Cooling operation: indoor air inlet temperature 27°C DB 19°C WB, outdoor ambient temperature 35°C DB; Heating operation: indoor air inlet temperature 20°C DB, outdoor ambient temperature 7°C DB 6°C WB.

2. The above noise values are measured in the anechoic chamber without reflected echo. Measurement point: 1 meter from the service cover surface and 1.5 meters from floor level.

*: For height difference between ODU & IDU more than 50(40)m, please contact with our professional engineer.

?: When the operation temperature is under 48°C DB ~ 54°C DB, the system may be in intermittent operation. Please contact with our professional engineer.

Hi-FLEXi X3 Series



HP		38HP	40HP	42HP	44HP	46HP
Model		AVWT-366HKFXE	AVWT-386HKFXE	AVWT-402HKFXE	AVWT-422HKFXE	AVWT-444HKFXE
Model	Modules	AVWT-212HKFXE AVWT-154HKFXE	AVWT-232HKFXE AVWT-154HKFXE	AVWT-212HKFXE AVWT-190HKFXE	AVWT-232HKFXE AVWT-190HKFXE	AVWT-232HKFXE AVWT-212HKFXE
	Power Supply	AC 3Φ, 380~415V/50Hz, 380V/60Hz				
Cooling	Capacity	kW 106.5	113.0	117.5	124.0	129.5
	kBtu/h	363.3	385.5	401	423	442
	Power Input	kW 32.1	34.2	36.1	38.2	40.0
	EER	kW/kW 3.32	3.31	3.26	3.25	3.24
Heating	Capacity	kW 119.0	125.0	132.0	138.0	144.0
	kBtu/h	406.0	426.5	450.4	470.9	491.3
	Power Input	kW 31.2	32.8	34.8	36.4	38.1
	COP	kW/kW 3.81	3.81	3.79	3.79	3.78
Ventilation	Air Flow Rate	m ³ /min 506	506	563	563	592
	Fan Quantity	4	4	4	4	4
	Static Pressure	Pa 110	110	110	110	110
Sound Pressure Level	Normal Mode	dB(A) 65	65	65	66	66
	Night Shift Mode	dB(A) 50	50	50	51	51
Compressor	Type	Twin Rotary				
	Compressor Quantity	pcs 3	3	4	4	4
Refrigerant	Type	R410A				
	Pre-charged Quantity	kg 19.5	19.5	22.3	22.3	22.8
Weight	Net Weight	kg 607	608	680	681	697
	Gross Weight	kg 651	652	729	730	745
Dimensions	External(HxWxD)	mm 1730x (1210+1350) x750	1730x (1210+1350) x750	1730x (1350+1350) x750	1730x (1350+1350) x750	1730x (1350+1350) x750
	Packing(HxWxD)	mm 1950x (1275+1420) x790	1950x (1275+1420) x790	1950x (1420+1420) x790	1950x (1420+1420) x790	1950x (1420+1420) x790
Cabinet Color		Ivory White	Ivory White	Ivory White	Ivory White	Ivory White
Ref. Piping	Gas	mm φ38.10	φ38.10	φ38.10	φ38.10	φ41.30
		inch 1-1/2	1-1/2	1-1/2	1-1/2	1-5/8
	Liquid	mm φ19.05	φ19.05	φ19.05	φ19.05	φ22.20
		inch 3/4	3/4	3/4	3/4	7/8
Connectable Indoor Units	Quantity	pcs 64	64	64	64	64
	Total Capacity	- 50%~150%	50%~150%	50%~150%	50%~150%	50%~150%
Piping Design	Height Difference Between ODU and IDU	m(above) 50(90*)	50(90*)	50(90*)	50(90*)	50(90*)
		m(below) 40(90*)	40(90*)	40(90*)	40(90*)	40(90*)
	Height Difference Between IDUs	m 30	30	30	30	30
	Max. Piping Length	m 1000	1000	1000	1000	1000
Operation Range*2	Cooling	DB -5°C~54°C	-5°C~54°C	-5°C~54°C	-5°C~54°C	-5°C~54°C
	Heating	WB -21°C~16.5°C	-21°C~16.5°C	-21°C~16.5°C	-21°C~16.5°C	-21°C~16.5°C

Notes:

1. Rated capacity is tested in the following conditions:

Pipe length: 7.5m, Pipe height difference: 0m; Cooling operation: indoor air inlet temperature 27°C DB 19°C WB, outdoor ambient temperature 35°C DB; Heating operation: indoor air inlet temperature 20°C DB, outdoor ambient temperature 7°C DB 6°C WB.

2. The above noise values are measured in the anechoic chamber without reflected echo. Measurement point: 1 meter from the service cover surface and 1.5 meters from floor level.

*: For height difference between ODU & IDU more than 50(40)m, please contact with our professional engineer.

?: When the operation temperature is under 48°C DB ~ 54°C DB, the system may be in intermittent operation. Please contact with our professional engineer.

Hi-FLEXi X3 Series



HP		48HP	50HP	52HP	54HP	56HP
Model		AVWT-464HKFXE	AVWT-482HKFXE	AVWT-504HKFXE	AVWT-522HKFXE	AVWT-544HKFXE
Model	Modules	AVWT-232HKFXE AVWT-232HKFXE	AVWT-250HKFXE AVWT-232HKFXE	AVWT-272HKFXE AVWT-232HKFXE	AVWT-272HKFXE AVWT-250HKFXE	AVWT-272HKFXE AVWT-272HKFXE
	Power Supply	AC 3Φ, 380-415V/50Hz, 380V/60Hz				
Cooling	Capacity	kW 136.0	141.5	148.0	153.5	160.0
		kBtu/h 464	483	505	524	546
	Power Input	kW 42.1	43.8	46.1	47.8	50.1
	EER	kW/kW 3.23	3.23	3.21	3.21	3.20
Heating	Capacity	kW 150.0	157.5	162.5	170.0	175.0
		kBtu/h 511.8	537.4	554.5	580.1	597.2
	Power Input	kW 39.7	42.0	43.7	46.0	47.7
Ventilation	COP	kW/kW 3.78	3.75	3.72	3.69	3.67
	Air Flow Rate	m ³ /min 592	646	646	700	700
	Fan Quantity	4	4	4	4	4
Sound Pressure Level	Static Pressure	Pa 110	110	110	110	110
	Normal Mode	dB(A) 66	67	67	67	67
	Night Shift Mode	dB(A) 51	52	52	52	52
Compressor	Type	Twin Rotary				
	Compressor Quantity	pcs 4	4	4	4	4
Refrigerant	Type	R410A				
	Pre-charged Quantity	kg 22.8	22.8	22.8	22.8	22.8
Weight	Net Weight	kg 698	707	718	727	738
	Gross Weight	kg 746	765	766	785	786
Dimensions	External(HxWxD)	mm 1730x (1350+1350) x750	1730x (1350+1600) x750	1730x (1350+1600) x750	1730x (1600+1600) x750	1730x (1600+1600) x750
	Packing(HxWxD)	mm 1950x (1420+1420) x790	1950x (1420+1665) x790	1950x (1420+1665) x790	1950x (1665+1665) x790	1950x (1665+1665) x790
Cabinet Color		Ivory White	Ivory White	Ivory White	Ivory White	Ivory White
Ref. Piping	Gas	mm φ41.3	φ41.3	φ41.3	φ41.3	φ41.3
		inch 1-5/8	1-5/8	1-5/8	1-5/8	1-5/8
	Liquid	mm φ22.2	φ22.2	φ22.2	φ22.2	φ22.2
		inch 7/8	7/8	7/8	7/8	7/8
Connectable Indoor Units	Quantity	pcs 64	64	64	64	64
	Total Capacity	- 50%-150%	50%-150%	50%-150%	50%-150%	50%-150%
Piping Design	Height Difference Between ODU and IDU	m(above) 50(90**)	50(90**)	50(90**)	50(90**)	50(90**)
		m(below) 40(90**)	40(90**)	40(90**)	40(90**)	40(90**)
	Height Difference Between IDUs	m 30	30	30	30	30
	Max. Piping Length	m 1000	1000	1000	1000	1000
Operation Range ²²	Cooling	DB -5°C-54°C	-5°C-54°C	-5°C-54°C	-5°C-54°C	-5°C-54°C
	Heating	WB -21°C-16.5°C	-21°C-16.5°C	-21°C-16.5°C	-21°C-16.5°C	-21°C-16.5°C

Notes:
 1. Rated capacity is tested in the following conditions:
 Pipe length: 7.5m, Pipe height difference: 0m; Cooling operation: indoor air inlet temperature 27°C DB 19°C WB, outdoor ambient temperature 35°C DB; Heating operation: indoor air inlet temperature 20°C DB, outdoor ambient temperature 7°C DB 6°C WB.
 2. The above noise values are measured in the anechoic chamber without reflected echo. Measurement point: 1 meter from the service cover surface and 1.5 meters from floor level.
 **: For height difference between ODU & IDU more than 50(40)m, please contact with our professional engineer.
 **: When the operation temperature is under 48°C DB - 54°C DB, the system may be in intermittent operation. Please contact with our professional engineer.

Hi-FLEXi X3 Series



HP		58HP	60HP	62HP	64HP
Model		AVWT-556HKFXE	AVWT-576HKFXE	AVWT-598HKFXE	AVWT-618HKFXE
Model	Modules	AVWT-212HKFXE AVWT-190HKFXE AVWT-154HKFXE	AVWT-232HKFXE AVWT-190HKFXE AVWT-154HKFXE	AVWT-232HKFXE AVWT-212HKFXE AVWT-154HKFXE	AVWT-232HKFXE AVWT-232HKFXE AVWT-154HKFXE
	Power Supply	AC 3Φ, 380-415V/50Hz, 380V/60Hz			
Cooling	Capacity	kW 162.5	169.0	174.5	181.0
		kBtu/h 554.4	576.6	595.3	617.5
	Power Input	kW 49.2	51.3	53.1	55.2
	EER	kW/kW 3.30	3.30	3.29	3.28
Heating	Capacity	kW 182.0	188.0	194.0	200.0
		kBtu/h 621.0	641.5	661.9	682.4
	Power Input	kW 47.8	49.4	51.1	52.7
Ventilation	COP	kW/kW 3.81	3.81	3.80	3.80
	Air Flow Rate	m ³ /min 773	773	802	802
	Fan Quantity	6	6	6	6
Sound Pressure Level	Static Pressure	Pa 110	110	110	110
	Normal Mode	dB(A) 67	67	67	67
	Night Shift Mode	dB(A) 52	52	52	52
Compressor	Type	Twin Rotary			
	Compressor Quantity	pcs 5	5	5	5
Refrigerant	Type	R410A			
	Pre-charged Quantity	kg 30.4	30.4	30.9	30.9
Weight	Net Weight	kg 939	940	956	957
	Gross Weight	kg 1008	1009	1024	1025
Dimensions	External(HxWxD)	mm 1730x (1210+1350+1350) x750	1730x (1210+1350+1350) x750	1730x (1210+1350+1350) x750	1730x (1210+1350+1350) x750
	Packing(HxWxD)	mm 1950x (1275+1420+1420) x790	1950x (1275+1420+1420) x790	1950x (1275+1420+1420) x790	1950x (1275+1420+1420) x790
Cabinet Color		Ivory White	Ivory White	Ivory White	Ivory White
Ref. Piping	Gas	mm φ44.5	φ44.5	φ44.5	φ44.5
		inch 1-3/4	1-3/4	1-3/4	1-3/4
	Liquid	mm φ22.2	φ22.2	φ22.2	φ22.2
		inch 7/8	7/8	7/8	7/8
Connectable Indoor Units	Quantity	pcs 64	64	64	64
	Total Capacity	- 50%-150%	50%-150%	50%-150%	50%-150%
Piping Design	Height Difference Between ODU and IDU	m(above) 50(90**)	50(90**)	50(90**)	50(90**)
		m(below) 40(90**)	40(90**)	40(90**)	40(90**)
	Height Difference Between IDUs	m 30	30	30	30
	Max. Piping Length	m 1000	1000	1000	1000
Operation Range ²²	Cooling	DB -5°C-54°C	-5°C-54°C	-5°C-54°C	-5°C-54°C
	Heating	WB -21°C-16.5°C	-21°C-16.5°C	-21°C-16.5°C	-21°C-16.5°C

Notes:
 1. Rated capacity is tested in the following conditions:
 Pipe length: 7.5m, Pipe height difference: 0m; Cooling operation: indoor air inlet temperature 27°C DB 19°C WB, outdoor ambient temperature 35°C DB; Heating operation: indoor air inlet temperature 20°C DB, outdoor ambient temperature 7°C DB 6°C WB.
 2. The above noise values are measured in the anechoic chamber without reflected echo. Measurement point: 1 meter from the service cover surface and 1.5 meters from floor level.
 **: For height difference between ODU & IDU more than 50(40)m, please contact with our professional engineer.
 **: When the operation temperature is under 48°C DB - 54°C DB, the system may be in intermittent operation. Please contact with our professional engineer.

Hi-FLEXi Series



Hi-FLEXi X3 Series



HP		104HP	106HP	108HP	110HP	112HP
Model	Model	AVWT-1008HKFXE	AVWT-1026HKFXE	AVWT-1048HKFXE	AVWT-1066HKFXE	AVWT-1088HKFXE
	Modules	AVWT-272HKFXE	AVWT-272HKFXE	AVWT-272HKFXE	AVWT-272HKFXE	AVWT-272HKFXE
		AVWT-232HKFXE	AVWT-250HKFXE	AVWT-272HKFXE	AVWT-272HKFXE	AVWT-272HKFXE
		AVWT-232HKFXE	AVWT-232HKFXE	AVWT-232HKFXE	AVWT-250HKFXE	AVWT-272HKFXE
Power Supply		AC 3φ, 380-415V/50Hz, 380V/60Hz				
Cooling	Capacity	296.0	301.5	308.0	313.5	320.0
	kW	1010.0	1028.8	1051.0	1069.8	1092.0
	Power Input	92.2	93.9	96.1	97.9	100.1
	EER	3.21	3.21	3.20	3.20	3.20
Heating	Capacity	325.0	332.5	337.5	345.0	350.0
	kW	1109.0	1134.6	1151.7	1177.3	1194.4
	Power Input	87.4	89.7	91.5	93.8	95.5
	COP	3.72	3.71	3.69	3.68	3.67
Ventilation	Air Flow Rate	1292	1346	1346	1400	1400
	Fan Quantity	8	8	8	8	8
	Static Pressure	110	110	110	110	110
Sound Pressure Level	Normal Mode	70	70	70	70	70
	Night Shift Mode	55	55	55	55	55
Compressor	Type	Twin Rotary				
	Compressor Quantity	8	8	8	8	8
Refrigerant	Type	R410A				
	Pre-charged Quantity	45.6	45.6	45.6	45.6	45.6
Weight	Net Weight	1436	1445	1456	1465	1476
	Gross Weight	1532	1551	1552	1571	1572
Dimensions	External(HxWxD)	1730x (1350+1350+1600+1600) x750	1730x (1350+1600+1600+1600) x750	1730x (1350+1600+1600+1600) x750	1730x (1600+1600+1600+1600) x750	1730x (1600+1600+1600+1600) x750
	Packing(HxWxD)	1950x (1420+1420+1665+1665) x790	1950x (1420+1665+1665+1665) x790	1950x (1420+1665+1665+1665) x790	1950x (1665+1665+1665+1665) x790	1950x (1665+1665+1665+1665) x790
Cabinet Color		Ivory White				
Ref. Piping	Gas	mm	φ50.8	φ50.8	φ50.8	φ50.8
		inch	2	2	2	2
	Liquid	mm	φ25.4	φ25.4	φ25.4	φ25.4
		inch	1	1	1	1
Connectable Indoor Units	Quantity	pcs	64	64	64	64
	Total Capacity	-	50%-150%	50%-150%	50%-150%	50%-150%
Piping Design	Height Difference Between ODU and IDU	m(above)	50(90**)	50(90**)	50(90**)	50(90**)
		m(below)	40(90**)	40(90**)	40(90**)	40(90**)
	Height Difference Between IDUs	m	30	30	30	30
	Max. Piping Length	m	1000	1000	1000	1000
Operation Range ²	Cooling	DB	-5°C-54°C	-5°C-54°C	-5°C-54°C	-5°C-54°C
	Heating	WB	-21°C-16.5°C	-21°C-16.5°C	-21°C-16.5°C	-21°C-16.5°C


Notes:
 1. Rated capacity is tested in the following conditions:
 Pipe length: 7.5m, Pipe height difference: 0m; Cooling operation: indoor air inlet temperature 27°C DB 19°C WB, outdoor ambient temperature 35°C DB; Heating operation: indoor air inlet temperature 20°C DB, outdoor ambient temperature 7°C DB 6°C WB.
 2. The above noise values are measured in the anechoic chamber without reflected echo. Measurement point: 1 meter from the service cover surface and 1.5 meters from floor level.
 *: For height difference between ODU & IDU more than 50(40)m, please contact with our professional engineer.
 **: When the operation temperature is under 48°C DB ~ 54°C DB, the system may be in intermittent operation. Please contact with our professional engineer.

Available for two-pipe Systems and three-pipe Systems




2-stage Heat Recovery

1-stage Heat Recovery




2-stage Heat Recovery



Patented 360° Fitted Refrigerant Cooling Technology



Patented 360° refrigerant cooling technology can help to remove the heat from the main PCB, inverter module and electrical box efficiently, which will greatly improve the reliability of the machine, especially in the high temperature ambient.

- A tin heat conductor is adopted between the refrigerant pipe and the heat sink to increase the heat transfer efficiency.
- The heat sink, made of aluminum alloy with high thermal conductivity, and the refrigerant tube are tightly combined through tube expander to improve heat exchange efficiency.



Convenient Installation


The electrical control box window is designed for service engineers to check issues of PCB conveniently. Especially for issues with a high voltage risk of electric shock, it can help engineers to avoid some risks.



It is very convenient to install and save installation space because of the front outlet pipes.


Indoor Installation, not Affected by Weather Conditions

Indoor installation does not affect the facade of building, and avoids the poor heat dissipation problems which often encountered by many air-cooled outdoor units. Water-cooled efficiency is higher than air-cooled, making the system more energy efficient.




Continuous Heating without Defrosting Operation

Because the product is generally installed indoors, in heating mode, the cold energy is discharged to the outside through water, which avoids the defrosting problem of air-cooled products.



Piping Length

Excellent piping length allows flexible design and installation. As water pipes are not connected to indoor units, users are free from water leakage problems.




- Max. equivalent pipe length L1: 190m
- Max. pipe length from first branch to each indoor unit L2: 40m
- Max. pipe length from certain branch to the nearby indoor unit L3: 30m
- Height difference between outdoor unit and indoor unit H1: Outdoor unit is higher: 50m, Outdoor unit is lower: 40m
- Height difference between indoor units using the same SW box H3: 4m
- Height difference between SW boxes H4: 5m
- Height difference between indoor units H2: 15m

Multiple Applications

Building Water Loop System

Building water loop system is a common application. The circulating water is heated by boilers during heating mode, and is cooled by the cooling tower during cooling mode to maintain the temperature of the water cycling system.



Others Applications

Uses underground heat sources like soil, surface water, underground water, seawater, lakes, rivers and more as renewable energy for cooling and heating. Water or antifreeze solution is circulated through the closed loop HDPE (High Density Poly-Ethylene) pipes buried beneath the earth's surface.



Hi-FLEXi W Series



HP		8HP	10HP	12HP	14HP	
Model		AVWW-76FKFW	AVWW-96FKFW	AVWW-114FKFW	AVWW-136FKFW	
Modules		—	—	—	—	
Power Supply		AC 3Φ, 380-415V/50/60Hz				
Cooling	Capacity	kW	22.4	28.0	33.5	40.0
		kBtu/h	76.5	95.6	114.3	136.5
	Power Input	kW	3.85	5.04	6.32	7.84
	EER	kW/kW	5.82	5.55	5.30	5.10
Heating	Capacity	kW	25.0	31.5	37.5	45.0
		kBtu/h	85.3	107.5	128.0	153.6
	Power Input	kW	4.08	5.25	6.45	8.03
	COP	kW/kW	6.12	6.00	5.81	5.60
Sound	Sound Pressure Level	dB(A)	49/51	51/53	53/54	55/57
	Cooling/Heating					
Water-side Heat Exchanger	Water Temperature	°C	10-45	10-45	10-45	10-45
	Rated Water Flow Rate	L/min	76.7	96.0	115.0	138.3
	Water Pressure Drop	kPa	30	45	45	60
	Maximum Pressure Resistance	kgf/cm ²	20	20	20	20
Weight	Net Weight	kg	166	166	171	171
	Gross Weight	kg	170	170	175	175
Dimensions	External (H × W × D)	mm	1030 × 820 × 560	1030 × 820 × 560	1030 × 820 × 560	1030 × 820 × 560
	Packing(H × W × D)	mm	1180 × 900 × 632	1180 × 900 × 632	1180 × 900 × 632	1180 × 900 × 632
Ref. Piping	Liquid Pipe	mm	φ9.53	φ9.53	φ12.70	φ12.70
		inch	3/8	3/8	1/2	1/2
	Low Pressure Gas Pipe	mm	φ19.05	φ22.20	φ25.40	φ25.40
		inch	3/4	7/8	1	1
	High/Low Pressure Gas Pipe	mm	φ15.88	φ19.05	φ22.20	φ22.20
		inch	5/8	3/4	7/8	7/8
Water Connecting Pipes	Water Pipe		DN32	DN32	DN32	DN32
	Thread of Connector		G1-1/4B	G1-1/4B	G1-1/4B	G1-1/4B
	Drain Pipe	mm	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18
MAX. Connectable Indoor Units	Recommended		12	15	18	21
	Max.		19	24	29	34

Notes:

- Operation condition:
Cooling: indoor temperature 27°C DB /19°C WB, water inlet/outlet 30/35°C.
Heating: indoor temperature 20°C DB /15°C WB, water inlet 20°C.
- The sound pressure is based on the following conditions.
1 meter from the unit service cover surface, and 1.5 meters from floor level.
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
- When unit is operating out of the allowable water temperature range, it won't start normally and will alarm.
- For Max. pipe length more than 300m, please contact with our professional engineer.

Hi-FLEXi W Series



HP		16HP	18HP	20HP	
Model		AVWW-154FKFW	AVWW-170FKFW	AVWW-190FKFW	
Modules		—	—	—	
Power Supply		AC 3Φ, 380-415V/50/60Hz			
Cooling	Capacity	kW	45.0	50.0	56.0
		kBtu/h	153.6	170.6	191.1
	Power Input	kW	8.11	9.43	10.98
	EER	kW/kW	5.55	5.30	5.10
Heating	Capacity	kW	50.0	56.0	63.0
		kBtu/h	170.6	191.1	215.0
	Power Input	kW	8.33	9.62	10.86
	COP	kW/kW	6.00	5.82	5.80
Sound	Sound Pressure Level	dB(A)	51/52	53/53	53/55
	Cooling/Heating				
Water-side Heat Exchanger	Water Temperature	°C	10-45	10-45	10-45
	Rated Water Flow Rate	L/min	153.3	166.7	193.3
	Water Pressure Drop	kPa	40	45	60
	Maximum Pressure Resistance	kgf/cm ²	20	20	20
Weight	Net Weight	kg	245	246	246
	Gross Weight	kg	250	251	251
Dimensions	External (H × W × D)	mm	1030 × 1040 × 560	1030 × 1040 × 560	1030 × 1040 × 560
	Packing(H × W × D)	mm	1180 × 1112 × 632	1180 × 1112 × 632	1180 × 1112 × 632
Ref. Piping	Liquid Pipe	mm	φ12.70	φ15.88	φ15.88
		inch	1/2	5/8	5/8
	Low Pressure Gas Pipe	mm	φ28.60	φ28.60	φ28.60
		inch	1-1/8	1-1/8	1-1/8
	High/Low Pressure Gas Pipe	mm	φ22.20	φ22.20	φ22.20
		inch	7/8	7/8	7/8
Water Connecting Pipes	Water Pipe		DN32	DN32	DN32
	Thread of Connector		G1-1/4B	G1-1/4B	G1-1/4B
	Drain Pipe	mm	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18
MAX. Connectable Indoor Units	Recommended		23	26	29
	Max.		39	43	48

Notes:

- Operation condition:
Cooling: indoor temperature 27°C DB /19°C WB, water inlet/outlet 30/35°C.
Heating: indoor temperature 20°C DB /15°C WB, water inlet 20°C.
- The sound pressure is based on the following conditions.
1 meter from the unit service cover surface, and 1.5 meters from floor level.
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
- When unit is operating out of the allowable water temperature range, it won't start normally and will alarm.
- For Max. pipe length more than 300m, please contact with our professional engineer.

Hi-FLEXi W Series



HP		22HP	24HP	26HP	28HP	30HP	
Model		AVWW-210FKFW	AVWW-228FKFW	AVWW-250FKFW	AVWW-268FKFW	AVWW-286FKFW	
Model	Modules	AVWW-96FKFW AVWW-114FKFW	AVWW-114FKFW AVWW-114FKFW	AVWW-114FKFW AVWW-136FKFW	AVWW-114FKFW AVWW-154FKFW	AVWW-96FKFW AVWW-190FKFW	
	Power Supply	AC 3Φ, 380-415V/50/60Hz					
Cooling	Capacity	kW 61.5	67.0	73.5	78.5	84.0	
	kBtu/h	209.9	228.6	250.8	267.9	286.7	
	Power Input	kW 11.4	12.6	14.2	14.4	16.0	
	EER	kW/kW 5.41	5.30	5.19	5.44	5.24	
Heating	Capacity	kW 69.0	75.0	82.5	87.5	94.5	
	kBtu/h	235.4	255.9	281.6	298.6	322.4	
	Power Input	kW 11.7	12.9	14.5	14.8	16.1	
COP	kW/kW 5.90	5.81	5.70	5.92	5.87		
Sound	Sound Pressure Level Cooling/Heating	dB(A) 56/57	56/57	58/60	56/57	56/58	
	Water Temperature	°C 10-45	10-45	10-45	10-45	10-45	
Water-side Heat Exchanger	Rated Water Flow Rate	L/min 211.0	230.0	253.3	268.3	289.3	
	Water Pressure Drop	kPa /	/	/	/	/	
	Maximum Pressure Resistance	kgf/cm ² 20	20	20	20	20	
	Net Weight	kg 337	342	342	416	412	
Weight	Gross Weight	kg 345	350	350	425	421	
	External (H × W × D)	mm 1030 × (820+820) × 560	1030 × (820+820) × 560	1030 × (820+820) × 560	1030 × (820+1040) × 560	1030 × (820+1040) × 560	
Packing(H × W × D)		mm 1180 × (900+900) × 632	1180 × (900+900) × 632	1180 × (900+900) × 632	1180 × (900+1112) × 632	1180 × (900+1112) × 632	
Ref. Piping	Liquid Pipe	mm φ15.88	φ15.88	φ19.05	φ19.05	φ19.05	
	inch	5/8	5/8	3/4	3/4	3/4	
	Low Pressure Gas Pipe	mm	φ28.60	φ28.60	φ31.75	φ31.75	φ31.75
		inch	1-1/8	1-1/8	1-1/4	1-1/4	1-1/4
	High/Low Pressure Gas Pipe	mm	φ25.40	φ25.40	φ25.40	φ28.60	φ28.60
inch		1	1	1	1-1/8	1-1/8	
Water Connecting Pipes	Water Pipe	DN32	DN32	DN32	DN32	DN32	
	Thread of Connector	G1-1/4B	G1-1/4B	G1-1/4B	G1-1/4B	G1-1/4B	
	Drain Pipe	mm Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	
MAX. Connectable Indoor Units	Recommended	33	36	39	40	40	
	Max.	53	58	63	64	64	

Notes:

1. Operation condition:
Cooling: indoor temperature 27°C DB /19°C WB, water inlet/outlet 30/35°C.
Heating: indoor temperature 20°C DB /15°C WB, water inlet 20°C.
2. The sound pressure is based on the following conditions.
1 meter from the unit service cover surface, and 1.5 meters from floor level.
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
3. When unit is operating out of the allowable water temperature range, it won't start normally and will alarm.
4. For Max. pipe length more than 300m, please contact with our professional engineer.

Hi-FLEXi W Series



HP		32HP	34HP	36HP	38HP	40HP	
Model		AVWW-304FKFW	AVWW-326FKFW	AVWW-344FKFW	AVWW-360FKFW	AVWW-380FKFW	
Model	Modules	AVWW-114FKFW AVWW-190FKFW	AVWW-136FKFW AVWW-190FKFW	AVWW-154FKFW AVWW-190FKFW	AVWW-170FKFW AVWW-190FKFW	AVWW-190FKFW AVWW-190FKFW	
	Power Supply	AC 3Φ, 380-415V/50/60Hz					
Cooling	Capacity	kW 89.5	96.0	101.0	106.0	112.0	
	kBtu/h	305.4	327.6	344.7	361.7	382.1	
	Power Input	kW 17.3	18.8	19.1	20.4	22.0	
	EER	kW/kW 5.17	5.10	5.29	5.19	5.10	
Heating	Capacity	kW 100.5	108.0	113.0	119.0	126.0	
	kBtu/h	342.9	368.6	385.6	406.0	429.9	
	Power Input	kW 17.3	18.9	19.2	20.5	21.7	
COP	kW/kW 5.81	5.72	5.89	5.81	5.80		
Sound	Sound Pressure Level Cooling/Heating	dB(A) 56/58	58/60	56/58	56/58	56/58	
	Water Temperature	°C 10-45	10-45	10-45	10-45	10-45	
Water-side Heat Exchanger	Rated Water Flow Rate	L/min 308.3	331.7	346.7	360.0	386.7	
	Water Pressure Drop	kPa /	/	/	/	/	
	Maximum Pressure Resistance	kgf/cm ² 20	20	20	20	20	
	Net Weight	kg 417	417	491	492	492	
Weight	Gross Weight	kg 426	426	501	502	502	
	External (H × W × D)	mm 1030 × (820+1040) × 560	1030 × (820+1040) × 560	1030 × (1040+1040) × 560	1030 × (1040+1040) × 560	1030 × (1040+1040) × 560	
Packing(H × W × D)		mm 1180 × (900+1112) × 632	1180 × (900+1112) × 632	1180 × (1112+1112) × 632	1180 × (1112+1112) × 632	1180 × (1112+1112) × 632	
Ref. Piping	Liquid Pipe	mm φ19.05	φ19.05	φ19.05	φ19.05	φ19.05	
	inch	3/4	3/4	3/4	3/4	3/4	
	Low Pressure Gas Pipe	mm	φ31.75	φ31.75	φ31.75	φ38.10	φ38.10
		inch	1-1/4	1-1/4	1-1/4	1-1/2	1-1/2
	High/Low Pressure Gas Pipe	mm	φ28.60	φ28.60	φ28.60	φ31.75	φ31.75
inch		1-1/8	1-1/8	1-1/8	1-1/4	1-1/4	
Water Connecting Pipes	Water Pipe	DN32	DN32	DN32	DN32	DN32	
	Thread of Connector	G1-1/4B	G1-1/4B	G1-1/4B	G1-1/4B	G1-1/4B	
	Drain Pipe	mm Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	
MAX. Connectable Indoor Units	Recommended	40	40	40	40	40	
	Max.	64	64	64	64	64	

Notes:

1. Operation condition:
Cooling: indoor temperature 27°C DB /19°C WB, water inlet/outlet 30/35°C.
Heating: indoor temperature 20°C DB /15°C WB, water inlet 20°C.
2. The sound pressure is based on the following conditions.
1 meter from the unit service cover surface, and 1.5 meters from floor level.
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
3. When unit is operating out of the allowable water temperature range, it won't start normally and will alarm.
4. For Max. pipe length more than 300m, please contact with our professional engineer.

Hi-FLEXi W Series



HP		42HP	44HP	46HP	48HP	50HP		
Model		AVWW-400FKFW	AVWW-418FKFW	AVWW-440FKFW	AVWW-456FKFW	AVWW-476FKFW		
Model	Modules	AVWW-96FKFW	AVWW-114FKFW	AVWW-96FKFW	AVWW-96FKFW	AVWW-96FKFW		
		AVWW-114FKFW	AVWW-114FKFW	AVWW-154FKFW	AVWW-170FKFW	AVWW-190FKFW		
		AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW		
		AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW		
Power Supply		AC 3Φ, 380-415V/50/60Hz						
Cooling	Capacity	kW 117.5	123.0	129.0	134.0	140.0		
		kBtu/h 401.0	419.7	440.3	457.3	477.7		
	Power Input	kW 22.3	23.6	24.1	25.5	27.0		
	EER	kW/kW 5.26	5.21	5.35	5.27	5.19		
Heating	Capacity	kW 132.0	138.0	144.5	150.5	157.5		
		kBtu/h 450.4	470.9	493.0	513.5	537.4		
	Power Input	kW 22.6	23.8	24.4	25.7	27.0		
	COP	kW/kW 5.85	5.81	5.91	5.85	5.84		
Sound	Sound Pressure Level Cooling/Heating	dB(A) 58/60	58/60	58/60	58/60	58/60		
	Water Temperature	°C 10-45	10-45	10-45	10-45	10-45		
Water-side Heat Exchanger	Rated Water Flow Rate	L/min 404.3	423.3	442.7	456.0	482.7		
	Water Pressure Drop	kPa /	/	/	/	/		
	Maximum Pressure Resistance	kgf/cm² 20	20	20	20	20		
	Weight	Net Weight	kg 583	588	657	658	658	
	Gross Weight	kg 596	601	671	672	672		
Dimensions	External (H×W×D)	mm	1030× (820+820+1040) ×560	1030× (820+820+1040) ×560	1030× (820+1040+1040) ×560	1030× (820+1040+1040) ×560	1030× (820+1040+1040) ×560	
		Packing(H×W×D)	mm	1180× (900+900+1112) ×632	1180× (900+900+1112) ×632	1180× (900+1112+1112) ×632	1180× (900+1112+1112) ×632	1180× (900+1112+1112) ×632
	Ref. Piping	Liquid Pipe	mm inch	φ19.05 3/4	φ19.05 3/4	φ19.05 3/4	φ19.05 3/4	φ19.05 3/4
		Low Pressure Gas Pipe	mm inch	φ38.10 1-1/2	φ38.10 1-1/2	φ38.10 1-1/2	φ38.10 1-1/2	φ38.10 1-1/2
High/Low Pressure Gas Pipe			mm inch	φ31.75 1-1/4	φ31.75 1-1/4	φ31.75 1-1/4	φ31.75 1-1/4	φ31.75 1-1/4
Water Connecting Pipes		Water Pipe		DN32	DN32	DN32	DN32	DN32
	Thread of Connector		G1-1/4B	G1-1/4B	G1-1/4B	G1-1/4B	G1-1/4B	
	Drain Pipe	mm	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	
MAX. Connectable Indoor Units	Recommended		40	40	40	40	40	
	Max.		64	64	64	64	64	

Notes:

- Operation condition:
Cooling: indoor temperature 27°C DB /19°C WB, water inlet outlet 30/35°C.
Heating: indoor temperature 20°C DB /15°C WB, water inlet 20°C.
- The sound pressure is based on the following conditions.
1 meter from the unit service cover surface, and 1.5 meters from floor level.
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
- When unit is operating out of the allowable water temperature range, it won't start normally and will alarm.
- For Max. pipe length more than 300m, please contact with our professional engineer.

Hi-FLEXi W Series



HP		52HP	54HP	56HP	58HP	60HP		
Model		AVWW-494FKFW	AVWW-516FKFW	AVWW-534FKFW	AVWW-550FKFW	AVWW-570FKFW		
Model	Modules	AVWW-114FKFW	AVWW-136FKFW	AVWW-154FKFW	AVWW-170FKFW	AVWW-190FKFW		
		AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW		
		AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW		
		AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW	AVWW-190FKFW		
Power Supply		AC 3Φ, 380-415V/50/60Hz						
Cooling	Capacity	kW 145.5	152.0	157.0	162.0	168.0		
		kBtu/h 496.4	518.6	535.7	552.7	573.2		
	Power Input	kW 28.3	29.8	30.1	31.4	32.9		
	EER	kW/kW 5.14	5.10	5.22	5.16	5.10		
Heating	Capacity	kW 163.5	171.0	176.0	182.0	189.0		
		kBtu/h 557.9	583.5	600.5	621.0	644.9		
	Power Input	kW 28.2	29.8	30.1	31.3	32.6		
	COP	kW/kW 5.80	5.75	5.86	5.81	5.80		
Sound	Sound Pressure Level Cooling/Heating	dB(A) 58/60	60/62	58/60	58/60	58/60		
	Water Temperature	°C 10-45	10-45	10-45	10-45	10-45		
Water-side Heat Exchanger	Rated Water Flow Rate	L/min 501.7	525.0	540.0	553.3	580.0		
	Water Pressure Drop	kPa /	/	/	/	/		
	Maximum Pressure Resistance	kgf/cm² 20	20	20	20	20		
	Weight	Net Weight	kg 663	663	737	738	738	
	Gross Weight	kg 677	677	752	753	753		
Dimensions	External (H×W×D)	mm	1030× (820+1040+1040) ×560	1030× (820+1040+1040) ×560	1030× (1040+1040+1040) ×560	1030× (1040+1040+1040) ×560	1030× (1040+1040+1040) ×560	
		Packing(H×W×D)	mm	1180× (900+1112+1112) ×632	1180× (900+1112+1112) ×632	1180× (1112+1112+1112) ×632	1180× (1112+1112+1112) ×632	1180× (1112+1112+1112) ×632
	Ref. Piping	Liquid Pipe	mm inch	φ19.05 3/4	φ19.05 3/4	φ22.20 7/8	φ22.20 7/8	φ22.20 7/8
		Low Pressure Gas Pipe	mm inch	φ38.10 1-1/2	φ38.10 1-1/2	φ38.10 1-1/2	φ38.10 1-1/2	φ38.10 1-1/2
High/Low Pressure Gas Pipe			mm inch	φ31.75 1-1/4	φ31.75 1-1/4	φ38.10 1-1/2	φ38.10 1-1/2	φ38.10 1-1/2
Water Connecting Pipes		Water Pipe		DN32	DN32	DN32	DN32	DN32
	Thread of Connector		G1-1/4B	G1-1/4B	G1-1/4B	G1-1/4B	G1-1/4B	
	Drain Pipe	mm	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	Outer Diameter 18	
MAX. Connectable Indoor Units	Recommended		40	40	40	40	40	
	Max.		64	64	64	64	64	


Notes:

- Operation condition:
Cooling: indoor temperature 27°C DB /19°C WB, water inlet outlet 30/35°C.
Heating: indoor temperature 20°C DB /15°C WB, water inlet 20°C.
- The sound pressure is based on the following conditions.
1 meter from the unit service cover surface, and 1.5 meters from floor level.
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
- When unit is operating out of the allowable water temperature range, it won't start normally and will alarm.
- For Max. pipe length more than 300m, please contact with our professional engineer.

Hi-Smart Series


High Efficiency

The H5 unit boasts cutting-edge design, utilizing 19.56mm fins to maximize heat exchange area, and an optimized fan with increased diameter. This results in significantly enhanced energy efficiency, with a maximum SEER of 8.2 and SCOP of 5.0.



Advanced corrugated fin


SEER up to 8.2
SCOP up to 5.0



Φ544



Φ600



Eco-friendly R32 Refrigerant

R32 refrigerant contributes to meeting the F-gas regulation targets as described in EU regulation 517/2014. Hisense HVAC introduces the Lower GWP refrigerant R32 on its VRF products, which is a perfect solution for attaining the CO₂ emission targets.

Features

- Zero Ozone Depletion Potential (ODP)
- Lower Global Warming Potential (GWP)
- Less charge amount under the same capacity
- Single component refrigerant, easy to handle and recycle



We are determined to become CO₂ neutral by 2050 and create a sustainable future together with you.


Compact Body & Low Weight

The Hi-Smart H5 unit features the latest exterior design from Hisense, showcasing a sleek and stylish appearance. Its compact body allows for flexible installation in confined spaces, while also reducing costs for product transportation and installation.

The height of the outdoor unit is only 840mm, which is very convenient to be concealed on the roof, does not affect the appearance of the overall building, and will not break the harmony of the city street.



reddot winner 2022



Multiple Measures Ensuring Room Safety


Refrigerant Leak Detection

Real-time refrigerant leak detection is essential for R32 refrigerant system. If the refrigerant concentration exceeds 5000ppm, the indoor unit will stop operation, and trigger a buzzer and warning flasher. Moreover, if any third-party alarm system or ventilation system, the system can also be linkaged.


Refrigerant Recovery

In the event of a refrigerant leak, our system triggers alarms, shuts down, and initiates refrigerant recovery immediately. Moreover, once there is a sudden power outage, the shut-off box can automatically close valves to prevent leaks.

The Progress of Refrigerant Recovery




Shut-off Box



- Capacity: 10HP
- Max. 17 IUs for 1 port
- Be closed automatically when power off
- 6000pls/13.0mm valve for gas pipe and 3000pls/6.1mm valve for liquid pipe

Refrigerant Detector




- Sleek and modern exterior
- Wall mounted installation
- Infrared NDIR detection
- Powered by 12 ± 10% VDC from IU or reserved dedicated power supply port
- Alarm value 5000ppm
- Dry contact reserved
- Design life ≥ 10 years

Accessories	Shut-off Box	Refrigerant Detector
Model	HESE-2V15	HOPT-ERD01


Outdoor Unit Noise Control

Auto Night Quiet Mode

In general, people are more sensitive to noise at night. Night quiet mode can be activated when necessary, and the noise can be reduced by up to 10dB(A).



Step 1: 5dB(A) decreased; Step 2: 7dB(A) decreased;
Step 3: 10dB(A) decreased.



Low Noise Mode

Users can flexibly set the low noise mode at any time. There are three levels for choice, which can be set on the controllers or the PCB.

Wide Operation Range

Extended operation range creates wider application potential. Hisense VRF can operate in a wide ambient temperature range: from -10°C to 52°C in cooling mode, and from -25°C to 26°C in heating mode.



Hi-Smart H5 Series



	HP	4HP	5HP	6HP	
Model	AC 1φ, 220-240V/50/60Hz	AVW-41HJDH2H1	AVW-48HJDH2H1	AVW-54HJDH2H1	
	AC 3φ, 380-415V/50/60Hz	AVW-41HKDH2H1	AVW-48HKDH2H1	AVW-54HKDH2H1	
Cooling	Capacity	kW 12.1	14.0	15.5	
		kBtu/h 41.5	48.0	53.0	
	Power Input	kW 3.30	4.24	4.70	
	EER	kW/kW 3.67	3.30	3.30	
Heating	SEER	kW/kW 8.20	7.90	7.90	
	Capacity	kW 14.2	16.0	18.0	
		kBtu/h 48.0	54.5	61.5	
	Power Input	kW 3.60	4.10	4.80	
Air Flow Rate	COP	kW/kW 3.94	3.90	3.75	
	SCOP	kW/kW 5.00	4.65	4.60	
		m ³ /min 80	80	80	
Sound Pressure Level(Cooling/Heating)	dB(A)	52/52	53/53	54/54	
Refrigerant	Type	-	R32		
	Pre-charged Quantity	kg	2	2	2
Weight	Net Weight(Single-phase/Three-phase)	kg	94/95	94/95	94/95
	Gross Weight(Single-phase/Three-phase)	kg	109/110	109/110	109/110
Dimensions	Net (H × W × D)	mm	840 × 1100 × 390	840 × 1100 × 390	840 × 1100 × 390
	Packing(H × W × D)	mm	1000 × 1185 × 530	1000 × 1185 × 530	1000 × 1185 × 530
Cabinet Color		-	Grayish White		
	Gas	mm	15.88	15.88	15.88
	Liquid	inch	5/8	5/8	5/8
Ref. Piping		mm	9.53	9.53	9.53
		inch	3/8	3/8	3/8
	Quantity	pcs	10	12	13
Connectable Indoor Units	Connection Ratio	-	50% - 150%		
	Max. Piping Length	m	80	80	80
Piping Design	Height Difference Between ODU and IDU	m (OD higher)	50	50	50
		m (OD lower)	40	40	40
	Height Difference Between IDUs	m	15	15	15
Operation Range	Cooling	DB °C	-10 ~ 52		
	Heating	WB/DB °C	-25.5 ~ 15.5 / -25 ~ 26		

Note:

1. Rated cooling capacity and rated heating capacity are tested in the following conditions:

Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.

Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.

2. During cooling (48-52°C) or heating (23-26°C) operations, the unit may operate intermittently.

Hi-Smart **E+** **L+** **C+** Series

High Performance Beyond Expectations



New air flow grille

Air supply distance is increased by 24% together with the 30Pa ESP.

New refrigerant cooling design

Reduce the risk of overheating of IPM, guaranteeing the stable and safe running of the control system.

High-efficiency oil separator

Improve the capacity and ensure stable operation.

Enclosed electrical box on the top

High reliability and convenient maintenance.

High-efficiency twin rotary compressor

High efficiency, low noise and high reliability.

Heat exchanger with Hi-Black fin


High anti-corrosion capability.

Take Hi-Smart E+ Series as an example.

High-efficiency DC Inverter Compressor

A high-efficiency DC inverter dual rotary compressor is adopted. It features unique dual-pressure chamber design and symmetrical location, which can effectively reduce the vibration and noise and improve the compressor performance, especially the performance under low-frequency operation.


Moreover, the dual rotary compressor has a small lubricating oil injection volume with stable oil return, and comes with a gas-liquid separator, which makes the system more reliable.



- 1 High-efficiency motor**
Optimize the motor design to improve compressor performance.
- 2 Optimized rotor design**
Lower the center of gravity of the compressor to reduce the noise and vibration.
- 3 Flat mechanism design**
Improve the volumetric efficiency and the total performance.
- 4 Screw interactive fastening**
Improve fastening effect and reduce deformation of the core.

Patented 360° Fitted Refrigerant Cooling Technology


To maintain the lifespan of the delicate electronic components, the unit uses patented 360° fitted refrigerant cooling technology to cool the whole electronic box effectively. It can overcome poor heat dissipation and solve high ambient temperature issues inside the electronic box, maintaining an efficient and reliable operation under harsh environment.



Note: 1.Compared with air-cooled technology, the temperature in electric box can be reduced about by 10%.
2.There is no refrigerant cooling kit inside the Hi-Smart L+ series(single phase unit).

Wide Operating Range

Extended operation range creates wider application potential, in cooling mode the operation range is from -10°C^* to 48°C and in heating mode the operation range is from -20°C to 26°C , which adapts to many extreme conditions.



* In cooling mode, the operation is under interval operation when the temperature is below -5°C .

Hi-Black Fin (Standard)


All the heat exchangers adopt Hi-Black fin, which has excellent anti-corrosive performance. Hi-Black fins are coated with epoxy resin using film-forming techniques while the traditional resins are acrylic resins. The epoxy resin is 1.5 times thicker than acrylic resin, and its acid-resistant, alkali-resistant and salt-fog resistant properties is 3 times better than acrylic resin.



Note: For the anti-corrosive solution for the whole outdoor unit, please contact with our local engineers.

Bistable Four-way Valve



The bistable four-way valve is adopted in the outdoor unit, which only consumes power when reversing. During the normal operation (regardless of cooling or heating), it is no need to be energized. Compared with conventional four-way valve, it is more energy-saving. Moreover, the reliability of valve coil is greatly improved.



Further Air Discharge Distance

Optimized Air Duct System Design

An additional air duct like channel surrounding the fan is designed to further discharge the air and avoid discharge air from being absorbed again. Besides, together with the 30Pa external static pressure, air is tested to discharge up to 24% further compared with the conventional one.



Hi-Smart E+ Series



Capacity (HP)		4.0	5.0	6.0	
	Model	AVW-41HJFHH1	AVW-48HJFHH1	AVW-54HJFHH1	
	Power Supply	AC 1 φ, 220-240V/50/60Hz			
Cooling	Capacity	kW	12.1	14.0	15.5
		Btu/h	41500	48000	53000
	Power Input	kW	3.73	4.33	5.64
	EER	W/W	3.24	3.23	2.75
	SEER	—	7.72	7.66	7.17
Heating	Capacity	kW	14.0	16.0	18.0
		Btu/h	48000	54500	61500
	Power Input	kW	2.99	3.73	4.63
	COP	W/W	4.05	3.75	3.35
	SCOP	—	4.41	4.36	4.26
Ventilation	Air Flow Rate	m ³ /min	71	71	71
Sound Pressure Level	Cooling/Heating	dB(A)	53/54	54/55	54/55
Weight	Net	kg	88	89	90
	Gross	kg	103	104	105
Outer Dimensions	Height	mm	990	990	990
	Width	mm	950	950	950
	Depth	mm	320	320	320
Packing Dimensions	Height	mm	1126	1126	1126
	Width	mm	1070	1070	1070
	Depth	mm	470	470	470
Cabinet Color	—	Grayish White			
Ref. Piping	Gas	mm	φ15.88	φ15.88	φ15.88
		in.	5/8	5/8	5/8
	Liquid	mm	φ9.53	φ9.53	φ9.53
		in.	3/8	3/8	3/8
Refrigerant	Type	—	R410A		
	Before Shipment	kg	4.0	4.0	4.0
Connectable Indoor Units	Max. Qty.	pc	8	9	10
	Connection Ratio	%	50-150	50-150	50-150
Piping Design	Max. Piping Length	m	70	70	70
	Total Piping Length	m	135	135	135
	Height Difference Between ODU and IDU	m	40	40	40
		m	30	30	30
	Height Difference Between IDUs	m	15	15	15
Operation Range	Cooling	DB(°C)	(-10*) -5 ~ 48		
	Heating	DB/WB(°C)	-20/-20.5 - 26/15.5		

NOTES:

- The rated cooling and heating capacity are tested in the following conditions:
Cooling Operation Conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length : 7.5m, pipe lift: 0m
Heating Operation Conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe lift: 0m
- The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be taken into consideration at the scene. Measurement point: 1m from the service cover surface and 1.5m from floor level.
- *1 When the temperature is between -10°C and -5°C, the cooling operation is under interval operation.

Hi-Smart L+ Series



Capacity (HP)		4.0	5.0	6.0	4.0	5.0	6.0	
	Model	AVW-41HJFHH2	AVW-48HJFHH2	AVW-54HJFHH2	AVW-41HKFHH2	AVW-48HKFHH2	AVW-54HKFHH2	
	Power Supply	AC 1 φ, 220-240V/50/60Hz			AC 3 φ, 380-415V/50/60Hz			
Cooling	Capacity	kW	12.1	14.0	15.5	12.1	14.0	
		Btu/h	41500	48000	53000	41500	48000	
	Power Input	kW	2.79	3.43	4.18	2.79	3.43	
	EER	W/W	4.33	4.08	3.71	4.33	4.08	
	SEER	—	8.20	8.10	8.00	8.20	8.10	
Heating	Capacity	kW	14.0	16.0	18.0	14.0	16.0	
		Btu/h	48000	54500	61500	48000	54500	
	Power Input	kW	3.08	3.71	4.47	3.08	3.71	
	COP	W/W	4.55	4.31	4.03	4.55	4.31	
	SCOP	—	4.85	4.70	4.55	4.85	4.70	
Ventilation	Air Flow Rate	m ³ /min	90	90	100	120	120	
Sound Pressure Level	Cooling/Heating	dB(A)	52/55	52/55	53/56	52/55	52/55	
Weight	Net	kg	106	107	108	112	113	
	Gross	kg	118	119	120	123	124	
Outer Dimensions	Height	mm	1380	1380	1380	1380	1380	
	Width	mm	950	950	950	950	950	
	Depth	mm	370	370	370	370	370	
Packing Dimensions	Height	mm	1531	1531	1531	1531	1531	
	Width	mm	1070	1070	1070	1070	1070	
	Depth	mm	515	515	515	515	515	
Cabinet Color	—	Grayish White						
Ref. Piping	Gas	mm	φ15.88	φ15.88	φ15.88	φ15.88	φ15.88	
		in.	5/8	5/8	5/8	5/8	5/8	
	Liquid	mm	φ9.53	φ9.53	φ9.53	φ9.53	φ9.53	
		in.	3/8	3/8	3/8	3/8	3/8	
Refrigerant	Type	—	R410A					
	Before Shipment	kg	3.8	3.8	4.1	3.8	3.8	
Connectable Indoor Units	Max. Qty.	pc	9	11	12	9	11	
	Connection Ratio	%	50-150	50-150	50-150	50-150	50-150	
Piping Design	Max. Piping Length	m	100	100	100	100	100	
	Total Piping Length	m	150	150	150	150	150	
	Height Difference Between ODU and IDU	m	50	50	50	50	50	
		m	40	40	40	40	40	
	Height Difference Between IDUs	m	15	15	15	15	15	
Operation Range	Cooling	DB(°C)	(-10*) -5 ~ 48					
	Heating	DB/WB(°C)	-20/-20.5 - 26/15.5					

NOTES:

- The rated cooling and heating capacity are tested in the following conditions:
Cooling Operation Conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length : 7.5m, pipe lift: 0m
Heating Operation Conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe lift: 0m
- The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be taken into consideration at the scene. Measurement point: 1m from the service cover surface and 1.5m from floor level.
- *1 When the temperature is between -10°C and -5°C, the cooling operation is under interval operation.

Hi-Smart **H** Series

Hi-Smart C+ Series



Capacity (HP)		8.0	10.0	12.0	
Model		AVW-76HKFHH2	AVW-96HKFHH2	AVW-114HKFHH2	
Power Supply		AC 3Φ, 380-415V/50/60Hz			
Cooling	Capacity	kW	22.4	28.0	33.5
		Btu/h	76400	95500	114300
	Power Input	kW	6.22	8.12	13.40
	EER	W/W	3.60	3.45	2.50
	SEER	—	7.00	7.80	7.55
Heating	Capacity	kW	25.0	31.5	37.5
		Btu/h	85300	107500	128000
	Power Input	kW	5.81	7.59	10.08
	COP	W/W	4.30	4.15	3.72
	SCOP	—	4.50	4.50	4.30
Ventilation	Air Flow Rate	m ³ /min	150	163	163
Sound Pressure Level	Cooling/Heating	dB(A)	55/58	56/59	56/59
	Net	kg	145	157	158
Weight	Gross	kg	161	174	175
	Height	mm	1650	1650	1650
	Width	mm	1100	1100	1100
Outer Dimensions	Depth	mm	390	390	390
	Height	mm	1806	1806	1806
	Width	mm	1185	1185	1185
Packing Dimensions	Depth	mm	530	530	530
	Cabinet Color	—	Grayish White		
Ref. Piping	Gas	mm	φ22.2	φ25.4	φ25.4
		in.	7/8	1/1	1/1
	Liquid	mm	φ12.7	φ12.7	φ12.7
		in.	1/2	1/2	1/2
Refrigerant	Type	—	R410A		
	Before Shipment	kg	5.5	6.5	6.5
Connectable Indoor Units	Max. Qty.	pc	15	18	19
	Connection Ratio	%	50-150	50-150	50-150
Piping Design	Max. Piping Length	m	150	150	150
	Total Piping Length	m	300	300	300
	Height Difference Between ODU and IDU	m	50	50	50
		m	40	40	40
	Height Difference Between IDUs	m	15	15	15
Operation Range	Cooling	DB(°C)	(-10*) -5 ~ 48		
	Heating	DB/WB(°C)	-20/-20.5 ~ 26/15.5		

NOTES:

- The rated cooling and heating capacity are tested in the following conditions:
Cooling Operation Conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length : 7.5m, pipe lift: 0m
Heating Operation Conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe lift: 0m
- The above noise values are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be taken into consideration at the scene. Measurement point: 1m from the service cover surface and 1.5m from floor level.
- *1 When the temperature is between -10°C and -5°C, the cooling operation is under interval operation.

Compact Size and Light Weight



Mini VRF H series outdoor units are compact in size for more convenient and flexible space design and installation hides in corners of balconies and yards or even on rooftops when necessary. With smaller and slimmer body frame meaning a lot of unnecessary weights are taken off which makes installation or positioning simpler.

Aviation Level Design of Grilling


Hisense H series creates a high-quality quiet environment. The design of the grilling follows the design concept of the aircraft engine design, which conforms to the aerodynamics principle. The noise has been greatly reduced. The grilling also increases safety as being a preventative for child figure being injured by the fan blade.



New Designed Air Channel

An additional air duct like channel surrounding the fan is designed to further discharge the air and avoid discharge air from being absorbed again. Air is tested to discharge up to 24% further compared with the conventional one. Besides, 30Pa external static pressure is available for units capacity ranged from 8HP to 12HP.

24%
Further Air Discharge



1.5-2m/s 2-2.5m/s 2.5-3m/s

Flexible Piping Connection



Installation restrictions on site does not stop Hisense mini VRF there with flexible piping directions which includes front, bottom, right, rear connections.



New Refrigerant Pipe Connection with Flare-nut Branch Pipe


Hisense VRF has newly developed the Flare-nut Branch Pipes, breaking through the common way of connecting refrigerant copper pipes by replacing welding processes with simple and safe flare nuts connections.

- Convenient and simple installation
- Saving installation time and cost
- Enhanced safety with no fire-involving process
- Preventing leakages due to poor welding
- No hot work permit application is required



Excellent Piping Length

Increased piping length allows for flexible design and installation. Hisense inverter technology and two-level cooling technology allows longer piping length and outstanding height differences. The air-conditioning system can be implemented more flexibly.



Power supply	AC 1 φ, 220-240V/50/60Hz			AC 1 φ, 220-240V/50/60Hz	AC 3 φ, 380-415V/50/60Hz	AC 3 φ, 380-415V/50/60Hz
	3HP	4HP	5HP	4/5/6HP	8HP	10/12HP
HP	3HP	4HP	5HP	4/5/6HP	8HP	10/12HP
Picture						
Max. total piping length L1	30	40	60	120	150	250
Max. piping length L2	25	25	50	75	100	100
Max. length between the first branch pipe and the farthest indoor unit L3	10	15	20	30	30	40
Height difference between ODU and IDU	Outdoor unit is higher H1	20	20	20	30	50
	Outdoor unit is lower H2	20	20	20	30	40
Height difference between IDUs H3	3.5	3.5	3.5	10	15	15

Hi-Smart H Series



HP		3HP	4HP	5HP
Model		AVW-28HJFH	AVW-34HJFH	AVW-43HJFH
Power Supply		AC 1 φ, 220V-240V/50/60Hz		
Cooling	Capacity	8.0	10.0	12.5
	kBtu/h	27.3	34.1	42.7
	Power Input	1.93	2.43	2.98
Heating	EER	4.15	4.27	4.19
	Capacity	9.5	11.2	14.0
	kBtu/h	32.4	38.2	47.8
Heating	Power Input	2.37	3.01	4.15
	COP	4.01	3.72	3.37
Ventilation	Air Flow Rate	46.5	69.0	78.0
Sound	Sound Pressure Level (Cooling/Heating)	50/52	53/55	54/57
Compressor	Type	Twin Rotary		
Refrigerant	Type	R410A	R410A	R410A
	Pre-charged Quantity	2.5	2.8	2.8
Weight	Net Weight	65	73	78
	Gross Weight	72	81	86
Dimensions	External(HxWxD)	800x950x370	800x950x370	800x950x370
	Packing(HxWxD)	951x1070x515	951x1070x515	951x1070x515
Cabinet Color		Ivory White	Ivory White	Ivory White
Ref. Piping	Gas	φ15.88	φ15.88	φ15.88
		inch	5/8	5/8
	Liquid	φ9.53	φ9.53	φ9.53
Connectable Indoor Units		inch	3/8	3/8
	Quantity	pcs	5	6
Piping Design	Total Capacity	-	50%-125%	50%-125%
	Height Difference Between ODU and IDU	m	20	20
	Height Difference Between IDUs	m	20	20
	Max. Piping Length	m	3.5	3.5
Operation Range	Cooling	DB	-5°C~46°C	-5°C~46°C
	Heating	WB	-15°C~15.5°C	-15°C~15.5°C

Notes:
 1. Rated cooling capacity and rated heating capacity are tested in the following conditions:
 Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
 Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 2. The sound pressure level is based on following conditions:
 1.5m beneath the unit.
 The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

Hi-Smart H Series



HP			4HP	5HP	6HP
Model			AVW-38HJFH	AVW-48HJFH	AVW-54HJFH
Power Supply			AC 1Φ, 220V-240V/50/60Hz		
Cooling	Capacity	kW	11.2	14.0	15.5
		kBtu/h	38.2	47.8	52.9
	Power Input	kW	2.60	3.46	4.21
	EER	kW/kW	4.31	4.05	3.68
Heating	Capacity	kW	12.5	16.0	18.0
		kBtu/h	42.7	54.6	61.4
	Power Input	kW	2.78	3.71	4.47
	COP	kW/kW	4.50	4.31	4.03
Ventilation	Air Flow Rate	m³/min	90.0	90.0	100.0
Sound	Sound Pressure Level (Cooling/Heating)	dB(A)	50/52	52/54	53/55
Compressor	Type	-	Twin Rotary		
Refrigerant	Type	-	R410A	R410A	R410A
	Pre-charged Quantity	kg	3.8	3.8	4.1
Weight	Net Weight	kg	93	95	97
	Gross Weight	kg	111	111	111
Dimensions	External(HxWxD)	mm	1380x950x370	1380x950x370	1380x950x370
	Packing(HxWxD)	mm	1531x1070x515	1531x1070x515	1531x1070x515
Cabinet Color			Ivory White	Ivory White	Ivory White
Ref. Piping	Gas	mm	φ15.88	φ15.88	φ15.88
		inch	5/8	5/8	5/8
	Liquid	mm	φ9.53	φ9.53	φ9.53
		inch	3/8	3/8	3/8
Connectable Indoor Units	Quantity	pcs	9	11	11
	Total Capacity	-	50%-150%	50%-150%	50%-150%
Piping Design	Height Difference Between ODU and IDU	m	30	30	30
		m	30	30	30
	Height Difference Between IDUs	m	10	10	10
	Max. Piping Length	m	75	75	75
Operation Range	Cooling	DB	-5°C~46°C	-5°C~46°C	-5°C~46°C
	Heating	WB	-20°C~15.5°C	-20°C~15.5°C	-20°C~15.5°C

Notes:
 1. Rated cooling capacity and rated heating capacity are tested in the following conditions:
 Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
 Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 2. The sound pressure level is based on following conditions:
 1.5m beneath the unit.
 The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

Hi-Smart H Series



HP			8HP	10HP	12HP
Model			AVW-76HKFH1	AVW-96HKFH1	AVW-114HKFH1
Power Supply			AC 3Φ, 380V-415V/50/60Hz		
Cooling	Capacity	kW	22.4	28.0	33.5
		kBtu/h	76.5	95.6	114.3
	Power Input	kW	6.37	7.75	10.30
	SEER	kW/kW	6.62	6.85	6.29
	EER	kW/kW	3.52	3.61	3.25
Heating	Capacity	kW	25.0	31.5	37.5
		kBtu/h	85.3	107.5	128
	Power Input	kW	5.84	7.00	10.00
	SCOP	kW/kW	4.10	4.21	3.98
	COP	kW/kW	4.28	4.50	3.75
Ventilation	Air Flow Rate	m³/min	127.0	150.0	163.0
Sound	Sound Pressure Level (Cooling/Heating)	dB(A)	57/58	58/59	59/60
Compressor	Type	-	Twin Rotary		
Refrigerant	Type	-	R410A	R410A	R410A
	Pre-charged Quantity	kg	5.63	5.50	6.50
Weight	Net Weight	kg	124	145	158
	Gross Weight	kg	139	161	175
Dimensions	External (HxWxD)	mm	1380x950x370	1650x1100x390	1650x1100x390
	Packing(HxWxD)	mm	1531x1070x515	1806x1185x530	1806x1185x530
Cabinet Color			Ivory White	Ivory White	Ivory White
Ref. Piping	Gas	mm	φ19.05	φ22.2	φ25.4
		inch	3/4	7/8	1
	Liquid	mm	φ9.53	φ12.7	φ12.7
		inch	3/8	1/2	1/2
Connectable Indoor Units	Quantity	pcs	15	17	19
	Total Capacity	-	50%-150%	50%-150%	50%-150%
Piping Design	Height Difference Between ODU and IDU	m	50	50	50
		m	40	40	40
	Height Difference Between IDUs	m	15	15	15
	Max. Piping Length	m	100	100	100
Operation Range	Cooling	DB	-5°C~50°C	-5°C~50°C	-5°C~50°C
	Heating	WB	-20°C~15.5°C	-20°C~15.5°C	-20°C~15.5°C

Notes:
 1. Rated cooling capacity and rated heating capacity are tested in the following conditions:
 Cooling conditions: indoor air inlet temperature: 27°C DB 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
 Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB 6°C WB, pipe length: 7.5m, pipe height difference: 0m.
 2. The sound pressure level is based on following conditions:
 1.5m beneath the unit.
 The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

INDOOR UNIT

4-Way Cassette Type / Mini 4-Way Cassette Type

1-Way Cassette Type

2-Way Cassette Type

Console Type

Ceiling Ducted Type (AC/DC Low-height)

Ceiling Ducted Type(DC High Static Pressure)

Ceiling Ducted Type (High/Low Static Pressure)

Wall Mounted Type

Ceiling & Floor Type

Floor Concealed Type

All Fresh Air Indoor Unit

Heat Recovery Ventilator

AHU Connection KIT

AIR
CONDITIONING
SOLUTION

Indoor Unit Line-up

HP		0.6	0.8	1.0	1.3	1.5	1.6	1.8	1.9	2.0	2.3	2.5	3.0	3.3	4.0	5.0	6.0	8.0	10.0	
kBtu/h		5	7	9	12	14	15	17	18	19	22	24	27	30	38	48	54	76	96	
R32 R410A	New 4-Way Cassette Type*				•	•		•			•	•	•	•	•	•	•	•	•	
R32 R410A	New Mini 4-Way Cassette Type*		•	•	•	•		•	•		•									
	1-Way Cassette Type			•	•	•	•			•		•								
	2-Way Cassette Type			•	•	•	•			•		•	•	•	•	•	•	•	•	
	Console Type		•	•	•	•		•	•											
	Ceiling Ducted Type (AC Low-height)		•	•	•	•		•	•		•	•	•							
R32 R410A	New Ceiling Ducted Type* (DC Low-height)		•	•	•	•		•			•	•								
	Ceiling Ducted Type (DC High Static Pressure)			•	•	•		•			•	•		•	•	•	•	•	•	•
	Ceiling Ducted Type (High Static Pressure)			•	•	•		•			•	•	•	•	•	•	•	•	•	•
	Ceiling Ducted Type (Low Static Pressure)			•	•	•		•			•	•	•	•	•	•	•	•	•	•
R32 R410A	New Wall Mounted Type*		•	•	•	•		•				•	•							
	Ceiling & Floor Type								•	•		•	•	•	•	•	•	•	•	•
	Floor Concealed Type			•		•			•			•								

Note: 1. For more details, check each unit's respective pages. 2. * Be compatible with both R32 and R410a.

Indoor Unit Feature Overview

Type	Accessories									
	Drain Pump (built-in)	Drain Pump (external)	3D Airflow Panel	Filter	Humidity Sensor	AirPure Kit	Motion Sensor	Hi-Motion	Outlet Air Temp Sensor	Float Switch
4-Way Cassette Type	●	×	×	●	○	○	○	○	●	●
Mini 4-Way Cassette Type	●	×	×	●	○	○	○	○	×	●
1-Way Cassette Type	●	×	×	●	×	×	×	○	●	●
2-Way Cassette Type	●	×	×	●	×	×	×	○	●	●
Console Type	×	○	×	●	○	○	×	○	×	×
Ceiling Ducted Type (AC Low-height)	●	×	○	●	○	○	×	○	×	●
Ceiling Ducted Type (DC Low-height)	●	×	×	●	○	○	×	○	×	●
Ceiling Ducted Type (DC High Static Pressure) AVD-07-AVD-54	○	○	×	●	○	○	×	○	●	●
Ceiling Ducted Type (DC High Static Pressure) AVD-76 & AVD-96	○	○	×	○	○	○	×	○	●	●
Ceiling Ducted Type (High Static Pressure) AVD-07-AVD-54	○	○	×	●	○	○	×	○	×	●
Ceiling Ducted Type (High Static Pressure) AVD-76 & AVD-96	×	○	×	○	×	×	×	○	●	●
Ceiling Ducted Type (Low Static Pressure) AVD-07-AVD-54	○	○	×	●	○	○	×	○	×	●
Ceiling Ducted Type (Low Static Pressure) AVD-76 & AVD-96	×	○	×	○	×	×	×	○	●	●
Wall Mounted Type	×	○	×	●	○	×	×	○	●	×
Ceiling & Floor Type	×	○	×	●	×	×	×	○	●	×
Floor Concealed Type	×	○	×	×	×	×	×	○	●	×

Type	Features											
	Dry Contact Input	Windows Linkage	Dry Contact Output	Fresh Air Intake	Sleep	Quiet	ECO	Individual Louver Control	Breeze Mode	Self Cleaning	Auto Fan Speed	
4-Way Cassette Type	●	×	●	●	●	●	●	●	●	×	×	
Mini 4-Way Cassette Type	●	×	●	●	●	●	●	●	●	×	×	
1-Way Cassette Type	●	×	●	●	●	●	●	×	×	×	●	
2-Way Cassette Type	●	×	●	●	●	×	×	●	×	×	●	
Console Type	●	×	●	●	●	●	●	×	×	×	×	
Ceiling Ducted Type (AC Low-height)	●	●	●	●	●	●	●	×	×	×	×	
Ceiling Ducted Type (DC Low-height)	●	●	●	●	●	●	●	×	×	×	×	
Ceiling Ducted Type (DC High Static Pressure) AVD-07-AVD-54	●	●	●	●	●	●	●	×	×	●	●	
Ceiling Ducted Type (DC High Static Pressure) AVD-76 & AVD-96	●	●	●	×	●	●	●	×	×	×	●	
Ceiling Ducted Type (High Static Pressure) AVD-07-AVD-54	●	●	●	●	×	×	●	×	×	×	×	
Ceiling Ducted Type (High Static Pressure) AVD-76 & AVD-96	●	×	●	×	●	×	●	×	×	×	×	
Ceiling Ducted Type (Low Static Pressure) AVD-07-AVD-54	●	●	●	●	×	×	●	×	×	×	×	
Ceiling Ducted Type (Low Static Pressure) AVD-76 & AVD-96	●	×	●	×	●	×	●	×	×	×	×	
Wall Mounted Type	●	●	●	×	●	●	●	×	×	●	●	
Ceiling & Floor Type	●	×	●	×	×	×	×	×	×	×	×	
Floor Concealed Type	●	×	●	×	●	●	●	×	×	×	●	

Remarks: Standard: ● Optional: ○ Incompatible: ×


Remarks: Standard: ● Optional: ○ Incompatible: ×

RELIABILITY
EFFICIENCY
COMFORT
FLEXIBILITY
OUTDOOR UNIT
INDOOR UNIT
CONTROL SYSTEM
ACCESSORY


4-Way Cassette Type Mini 4-Way Cassette Type

Compact and Classy Design

The 4-way cassette is as slim as 238mm, and the mini 4-way cassettes are only 215mm, making them suitable for narrow ceiling spaces. And the newly designed panel seamlessly integrates with indoor aesthetics.




4-way Cassette Type



Mini 4-way Cassette Type


Higher Installation

Air from the cassette can flow down from ceiling heights as high as 4.2m. And it's suitable for working with motion sensors.




Breeze Mode

Under the new designed breeze mode, the cold air is blown out from the microholes in the panel, and the unit is working in a mute mode, which can avoid blowing air directly on people and achieve more even and comfortable airflow.




Individual Louvers Control

4-way cassettes louvers are now capable of individual control to freely choose how you want your AC unit supplies air according to different needs, applications and installation layout. Each louvers have 7 angle settings and maximum angle reach at 64°.




Healthy Air

The cassette unit is featured with self-cleaning. By simply pressing a button on the controller, the unit can be refreshed, saving any labor costs. Moreover, it can achieve high temperature sterilization at 56°C, ensuring clean and healthy airflow.



Motion Sensor

The sensor senses the presence of people to automatically turn the cassette unit on or off and whether to direct airflow towards or avoiding humans depend settings set on the controller. During crowded times, the setting temperature is automatically lowered down and vice versa.



R32 | R410A

4-Way Cassette Type




Model	AVBC-09 HJDBA	AVBC-12 HJDBA	AVBC-15 HJDBA	AVBC-19 HJDBA	AVBC-22 HJDBA	AVBC-24 HJDBA	AVBC-27 HJDBA	AVBC-30 HJDBA	AVBC-38 HJDBA	AVBC-48 HJDBA	AVBC-54 HJDBA			
Power supply	AC 1 ϕ, 220V~240V/50Hz/60Hz													
Capacity	Cooling	kW	2.8	3.6	4.5	5.6	6.3	7.1	8.0	9.0	11.2	14.0	16.0	
		Btu/h	9,600	12,300	15,300	19,100	21,500	24,200	27,300	30,700	38,200	47,800	54,600	
Capacity	Heating	kW	3.2	4.0	5.0	6.3	7.1	8.0	9.0	10.0	12.5	16.0	18.0	
		Btu/h	10,900	13,700	17,100	21,500	24,200	27,300	30,700	34,100	42,700	54,600	61,400	
Power Input	Cooling	W	20	30	40	50	50	60	70	70	80	130	130	
		W	20	30	40	50	50	60	70	70	80	130	130	
Sound Pressure	Cooling	dB(A)	30/28/28/27/26/26	32/29/29/28/27/26	33/31/29/29/27/26	34/31/30/28/28/26	36/33/32/31/29/28	36/33/32/33/31/30	37/36/35/33/31/30	37/36/35/36/34/33	42/40/38/38/36/34	46/44/40/40/38/36	46/44/41/40/38/36	
		dB(A)	30/28/28/27/26/26	32/29/29/28/27/26	33/31/29/29/27/26	34/31/30/28/28/26	36/33/32/31/29/28	36/33/32/33/31/30	37/36/35/33/31/30	37/36/35/36/34/33	42/40/38/38/36/34	46/44/40/40/38/36	46/44/41/40/38/36	
Air Flow Rate	Cooling	m ³ /min	15.0/12.8/12.0/10.8/10.0/8.8	17.0/14.0/12.8/11.8/10.8/9.1	19.0/15.0/13.9/12.6/11.4/10.5	19.0/15.0/13.9/12.6/11.8/10.5	26.0/20.0/18.3/17.0/15.1/13.0	27.0/21.1/19.1/18.0/16.1/14.7	25.0/22.3/19.6/17.9/16.9/15.3	20.3/18.3/18.7/26.0/23.5/20.5	31.0/29.5/28.7/26.0/24.2/22.4	37.0/34.0/30.7/28.9/25.6/23.8		
		m ³ /min	15.0/12.8/12.0/10.8/10.0/8.8	17.0/14.0/12.8/11.8/10.8/9.1	19.0/15.0/13.9/12.6/11.4/10.5	19.0/15.0/13.9/12.6/11.8/10.5	26.0/20.0/18.3/17.0/15.1/13.0	27.0/21.1/19.1/18.0/16.1/14.7	25.0/22.3/19.6/17.9/16.9/15.3	20.3/18.3/18.7/26.0/23.5/20.5	31.0/29.5/28.7/26.0/24.2/22.4	37.0/34.0/30.7/28.9/25.6/23.8		
Piping	Connection Type	-	Flare-nut Connection(with Flare Nuts)											
		Liquid	mm	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35	φ9.53	φ9.53	φ9.53	φ9.53	φ9.53	φ9.53
			inch	(1/4)	(1/4)	(1/4)	(1/4)	(1/4)	(3/8)	(3/8)	(3/8)	(3/8)	(3/8)	(3/8)
		Gas	mm	φ12.7	φ12.7	φ12.7	φ12.7	φ12.7	φ15.88	φ15.88	φ15.88	φ15.88	φ15.88	φ15.88
			inch	(1/2)	(1/2)	(1/2)	(1/2)	(1/2)	(5/8)	(5/8)	(5/8)	(5/8)	(5/8)	(5/8)
Condensate Drain	-	O.D. 32												
Weight	Net Weight	kg	20	20	20	20	21	21	23	23	26	26	26	
		kg	24	24	24	24	25	25	27	27	31	31	31	
Dimensions	External	H mm	238	238	238	238	238	238	238	288	288	288		
		W mm	840	840	840	840	840	840	840	840	840	840		
		D mm	840	840	840	840	840	840	840	840	840	840		
	Packaging	H mm	292	292	292	292	292	292	292	292	342	342	342	
		W mm	945	945	945	945	945	945	945	945	945	945	945	
		D mm	945	945	945	945	945	945	945	945	945	945	945	
Decoration Panel	Model	-	HPE-GNK1											
		-	Neutral White											
	Body	H mm	47	47	47	47	47	47	47	47	47	47	47	
		Dimensions	W mm	950	950	950	950	950	950	950	950	950	950	950
			D mm	950	950	950	950	950	950	950	950	950	950	950
	Packaging	H mm	100	100	100	100	100	100	100	100	100	100	100	
		Dimensions	W mm	1022	1022	1022	1022	1022	1022	1022	1022	1022	1022	1022
			D mm	1022	1022	1022	1022	1022	1022	1022	1022	1022	1022	1022
	Net Weight	kg	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	
	Gross Weight	kg	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	

Notes:

- The nominal cooling capacity and heating capacity are based on following conditions:
Cooling Operation Conditions
Indoor Air Inlet Temperature: 27°C DB (80°F DB), 19.0°C WB (66.2°F WB)
Outdoor Air Inlet Temperature: 35°C DB (95°F DB)
Piping Length: 7.5 Meters Piping Lift: 0 Meter
Heating Operation Conditions
Indoor Air Inlet Temperature: 20°C DB (68°F DB)
Outdoor Air Inlet Temperature: 7°C DB (45°F DB), 6°C WB (43°F WB)
- The sound pressure level is based on following conditions: 1.5m beneath the unit.
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

R32 | R410A

Mini 4-Way Cassette Type



Model	AVC-05HJDBA	AVC-07HJDBA	AVC-09HJDBA	AVC-12HJDBA	AVC-15HJDBA	AVC-17HJDBA	AVC-19HJDBA			
Power supply	AC 1 ϕ, 220V~240V/50Hz/60Hz									
Capacity	Cooling	kW	1.5	2.2	2.8	3.6	4.5	5.0	5.6	
		Btu/h	5,100	7,500	9,600	12,300	15,300	17,000	19,100	
Capacity	Heating	kW	2.0	2.5	3.3	4.2	5.0	5.6	6.3	
		Btu/h	6,800	8,500	11,200	14,300	17,000	19,100	21,500	
Power Input	Cooling	W	14	14	14	16	22	30	40	
		W	14	14	14	16	22	30	40	
Sound Pressure	Cooling	dB(A)	30/29/28/26	30/29/28/26	32/30/28/26	34/32/29/26	38/36/31/28	42/39/36/31	45/42/38/34	
		dB(A)	30/29/28/26	30/29/28/26	32/30/28/26	34/32/29/26	38/36/31/28	42/39/36/31	45/42/38/34	
Air Flow Rate	m ³ /min	7.2/6.5/6.2/5.6	7.2/6.5/6.2/5.6	7.8/7.2/6.5/5.8	7.8/7.2/6.5/5.8	9.3/8.7/7.1/6.7	11.0/9.5/8.7/7.1	12.5/10.8/9.3/8.0		
Piping	Connection Type	-	Flare-nut Connection(with Flare Nuts)							
		Liquid	mm	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35
			inch	(1/4)	(1/4)	(1/4)	(1/4)	(1/4)	(1/4)	(1/4)
		Gas	mm	φ12.7	φ12.7	φ12.7	φ12.7	φ12.7	φ12.7	φ12.7
			inch	(1/2)	(1/2)	(1/2)	(1/2)	(1/2)	(1/2)	(1/2)
Condensate Drain	-	O.D. 32								
Weight	Net Weight	kg	14.5	14.5	14.8	14.8	15.8	15.8	15.8	
		kg	17.3	17.3	17.6	17.6	18.6	18.6	18.6	
Dimensions	External	H mm	215	215	215	215	215	215	215	
		W mm	570	570	570	570	570	570	570	
		D mm	570	570	570	570	570	570	570	
	Packaging	H mm	292	292	292	292	292	292	292	
		W mm	730	730	730	730	730	730	730	
		D mm	668	668	668	668	668	668	668	
Decoration Panel	Model	-	HPE-DNK1							
		-	Neutral White							
	Body	H mm	37	37	37	37	37	37	37	
		Dimensions	W mm	620	620	620	620	620	620	620
			D mm	620	620	620	620	620	620	620
	Packaging	H mm	115	115	115	115	115	115	115	
		Dimensions	W mm	690	690	690	690	690	690	690
			D mm	680	680	680	680	680	680	680
	Net Weight	kg	2.7	2.7	2.7	2.7	2.7	2.7	2.7	
	Gross Weight	kg	4.0	4.0	4.0	4.0	4.0	4.0	4.0	

Notes:

- The nominal cooling capacity and heating capacity are based on following conditions:
Cooling Operation Conditions
Indoor Air Inlet Temperature: 27°C DB (80°F DB), 19.0°C WB (66.2°F WB)
Outdoor Air Inlet Temperature: 35°C DB (95°F DB)
Piping Length: 7.5 Meters Piping Lift: 0 Meter
Heating Operation Conditions
Indoor Air Inlet Temperature: 20°C DB (68°F DB)
Outdoor Air Inlet Temperature: 7°C DB (45°F DB), 6°C WB (43°F WB)
- The sound pressure level is based on following conditions: 1.5m beneath the unit.
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

RELIABILITY
EFFICIENCY
COMFORT
FLEXIBILITY
OUTDOOR UNIT
INDOOR UNIT
CONTROL SYSTEM
ACCESSORY

1-Way Cassette Type


Chic Aesthetics

Inspired from ceiling concealed ducted units and integrated with the design of cassette units to present 1 way cassette. High class appearance blends into common white plaster ceilings and practical solution for cornered floor layouts, hotel rooms and residential applications.



Even Air Supply

Louvers are consist of horizontal and vertical flaps to supply air evenly to the edges of any rooms. Wider opening angle from 17° to 65° supplies air further and lower down to floor needed during heating modes.



Space Saving

Slim body height of 192mm fits in limited ceiling spaces commonly seen in budget hotels and residential applications.



Easier Maintain

The electric box of the cassette is designed and placed beneath the panel. When operate on PCB, it just needs to open the panel and the cover of box. It's easy to take the service, maintenance and commissioning.



1-Way Cassette Type



Model		AVY-07UXJSJA	AVY-09UXJSJA	AVY-12UXJSJA	AVY-14UXJSJA	AVY-18UXJSKA	AVY-24UXJSKA	
Power Supply		AC 1Φ, 220~240V/50Hz/60Hz						
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1
		Btu/h	7,500	9,600	12,300	15,400	19,100	24,200
Power Input	Heating	kW	2.5	3.2	4.0	5.0	6.3	8.0
		Btu/h	8,500	10,900	13,600	17,100	21,500	27,300
Sound Pressure	Cooling	W	14	14	24	34	34	74
	Heating	W	14	24	34	44	44	94
Airflow Rate								
Airflow Rate		m ³ /min	6.2/5.9/5.6/	6.6/6.2/5.6/	8.3/7.3/6.8/	8.3/7.3/6.8/	12.1/9.9/8.8/	15.6/12.6/11.2/
			5.1/4.8/4.6	5.1/4.8/4.6	6.2/5.6/5.1	6.2/5.6/5.1	8.2/7.8/6.6	9.9/8.4/7.1
Connection Type		Flare-nut Connection (with Flare Nuts)						
Piping	Liquid	mm	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35	φ9.53
		inch	1/4	1/4	1/4	1/4	1/4	3/8
	Gas	mm	φ12.70	φ12.70	φ12.70	φ12.70	φ12.70	φ15.88
		inch	1/2	1/2	1/2	1/2	1/2	5/8
Condensate Drain	mm	I.D.32						
Weight	Net Weight	kg	19	19	20	20	24	24
	Gross Weight	kg	23	23	24	24	29	29
Dimensions	External	H mm	192	192	192	192	192	192
		W mm	910	910	910	910	1180	1180
		D mm	470	470	470	470	470	470
	Packaging	H mm	268	268	268	268	268	268
		W mm	1136	1136	1136	1136	1406	1406
		D mm	574	574	574	574	574	574
Model		HP-D-NA	HP-D-NA	HP-D-NA	HP-D-NA	HP-E-NA	HP-E-NA	
Panel Colour		Neutral White						
Body	H mm	55	55	55	55	55	55	
	W mm	1100	1100	1100	1100	1370	1370	
	D mm	550	550	550	550	550	550	
Panel	H mm	130	130	130	130	130	130	
	W mm	1160	1160	1160	1160	1430	1430	
	D mm	610	610	610	610	610	610	
Net Weight	kg	5	5	5	5	6	6	
Gross Weight	kg	8	8	8	8	10	10	

Notes:


1. The nominal cooling capacity is based on the following conditions:
 Indoor Air Inlet Temperature: 27°C DB (80°F DB), 19.0°C WB (66.2°F WB)
 Outdoor Air Inlet Temperature: 35°C DB (95°F DB)
 Piping Length: 7.5 Meters Piping Lift: 0 Meter

2. The sound pressure level is based on the following conditions: 1.0m beneath the unit, 1.0m from Discharge Grille. The above data was measured in an anechoic chamber so that the reflected sound should be taken into consideration in the field. When bottom air inlet is adopted, the sound pressure will increase according to factors such as installation mode and the room structure.

2-Way Cassette Type


Compact and Classy Design

The slim structure of the cassette having height as low as 298mm can be installed in ceiling spaces with a minimum of 310mm. Narrow corridors or zoned spaces are best fitted with 2 way cassette due to its compact design.




Independent Louvers Control

Each louver's opening angles are controllable individually with a total of 7 choices, with opening angle from 27° to 84° to cover high ceiling narrow long corridors needs and effective warm air supply during winter seasons.



Branch Discharge Option

In irregular room layouts, branch discharge could come in handy by extending air distribution area to the most awkward corners without additional indoor units.



2-Way Cassette Type



Model		AVL-07 UXJSGA	AVL-09 UXJSGA	AVL-12 UXJSGA	AVL-14 UXJSGA	AVL-18 UXJSGA	AVL-24 UXJSGA	AVL-27 UXJSGA	AVL-30 UXJSGA	AVL-38 UXJSHA	AVL-48 UXJSHA	AVL-54 UXJSHA	
Power Supply		AC 1Φ, 220-240V/50Hz/60Hz											
Capacity	Cooling	kW	2.2	2.8	3.6	4.3	5.6	7.1	8.4	9.0	11.2	14.0	16.0
		Btu/h	7,500	9,600	12,300	14,700	19,100	24,200	28,700	30,700	38,200	47,800	54,600
	Heating	kW	2.8	3.3	4.0	4.9	6.5	8.0	9.0	10.0	13.0	16.0	18.0
		Btu/h	9,600	11,300	13,600	16,700	22,200	27,300	30,700	34,100	44,400	54,600	61,400
Power Input	Cooling	W	14	14	14	24	34	44	64	74	84	104	114
	Heating	W	14	14	14	24	34	44	64	74	84	104	114
Sound Pressure		dB(A)	32/30/ 29/27	33/30/ 29/28	34/31/ 30/28	40/37/ 34/32	42/39/ 36/33	45/42/ 40/36	47/44/ 40/36	49/46/ 42/37	46/44/ 40/38	48/45/ 42/38	49/46/ 43/40
	Airflow Rate	m ³ /min	10.0/8.5/ 7.2/6.0	11.0/9.4/ 8.2/6.6	12.0/10.5/ 8.9/7.5	15.0/13.2/ 11.5/9.9	17.0/14.9/ 13.0/11.2	19.0/16.4/ 14.3/12.3	21.0/18.4/ 15.6/12.6	22.0/19.3/ 16.3/13.1	30.0/26.4/ 23.1/19.8	35.0/30.8/ 26.9/21.1	37.0/32.5/ 28.4/24.1
	Connection Type	-	Flare-nut Connection (with Flare Nuts)										
Piping	Liquid	mm	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35	φ9.53	φ9.53	φ9.53	φ9.53	φ9.53	φ9.53
		inch	1/4	1/4	1/4	1/4	1/4	3/8	3/8	3/8	3/8	3/8	3/8
	Gas	mm	φ12.70	φ12.70	φ12.70	φ12.70	φ12.70	φ15.88	φ15.88	φ15.88	φ15.88	φ15.88	φ15.88
		inch	1/2	1/2	1/2	1/2	1/2	5/8	5/8	5/8	5/8	5/8	5/8
Condensate Drain	mm	I.D.32											
Weight	Net Weight	kg	22	22	22	24	24	24	24	24	39	39	39
	Gross Weight	kg	28	28	28	30	30	30	30	30	47	47	47
Dimensions	External	H mm	298	298	298	298	298	298	298	298	298	298	298
		W mm	860	860	860	860	860	860	860	860	1420	1420	1420
		D mm	630	630	630	630	630	630	630	630	630	630	630
	Packaging	H mm	350	350	350	350	350	350	350	350	350	350	350
		W mm	1070	1070	1070	1070	1070	1070	1070	1070	1630	1630	1630
		D mm	710	710	710	710	710	710	710	710	710	710	710
Model	-	HP-C-NA	HP-C-NA	HP-C-NA	HP-C-NA	HP-C-NA	HP-C-NA	HP-C-NA	HP-C-NA	HP-F-NA	HP-F-NA	HP-F-NA	
Panel Colour	-	Neutral White											
Decoration Panel	Body Dimensions	H mm	30	30	30	30	30	30	30	30	30	30	30
		W mm	1100	1100	1100	1100	1100	1100	1100	1100	1660	1660	1660
		D mm	710	710	710	710	710	710	710	710	710	710	710
	Packaging Dimensions	H mm	160	160	160	160	160	160	160	160	160	160	160
		W mm	1170	1170	1170	1170	1170	1170	1170	1170	1710	1710	1710
		D mm	740	740	740	740	740	740	740	740	740	740	740
Net Weight	kg	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	10.5	10.5	10.5	
Gross Weight	kg	13.3	13.3	13.3	13.3	13.3	13.3	13.3	13.3	17.8	17.8	17.8	

Notes:

1. The nominal cooling capacity is based on the following conditions:
 Indoor Air Inlet Temperature: 27°C DB (80°F DB), 19.0°C WB (66.2°F WB)
 Outdoor Air Inlet Temperature: 35°C DB (95°F DB)
 Piping Length: 7.5 Meters Piping Lift: 0 Meter

2. The sound pressure level is based on the following conditions: 1.5m beneath the unit.
 The above data was measured in an anechoic chamber so that the reflected sound should be taken into consideration in the field.

Console Type

Stylish Design

With smooth white cover, LED shown and temperature display, the console unit is an super stylish air-conditioning, which is suitable for the residential or commercial applications which need an unit installed on or close to the floor.



Multiple Blowing Types

Cooling Mode

The unit adopts the stereo cooling mode that can reach the setting temperature rapidly.



*Note: During cooling mode, the lower air louver will close automatically after the indoor unit operates in low fan speed mode for an hour. Otherwise it will keep open.

Heating Mode

Air supply through the below louver achieves floor heating effect and increases the comfortability.



*Note: In the Eco mode, when the indoor return air temp. is close to the setting temp., the upper air deflector is automatically closed, and the lower air outlet mode is activated.

Flexible Installation Options

The unit can stand directly on the floor, or be hanged on the wall. According to the interior decoration style, the machine can choose surface mounted, embedded mounted, concealed mounted.



Standing on the floor



Hanging on the wall




Surface mounted

Embedded mounted

Concealed mounted

Flexible Piping Connection

Both refrigerant and drainage pipings are freely to connect in any direction including two sides (L or R) and bottom and back. An additional direction to the back of the unit suitable for pipes which passing through walls.



Console Type




Model		AVK-05HJFCAA	AVK-07HJFCAA	AVK-09HJFCAA	AVK-12HJFCAA	AVK-15HJFCAA	AVK-17HJFCAA	
Power Supply		AC 1ϕ, 220V~240V/50Hz/60Hz						
Capacity	Cooling	kW	1.5	2.2	2.8	3.6	4.5	5.0
		Btu/h	5,100	7,500	9,600	12,300	15,300	17,000
Capacity	Heating	kW	2.0	2.5	3.3	4.2	5.0	5.6
		Btu/h	6,800	8,500	11,200	14,300	17,000	19,100
Power Input	Cooling	W	10	11	12	14	18	23
	Heating	W	10	11	12	14	18	23
Sound Pressure	dB(A)	32/30/29/28/26/24	34/32/31/29/27/26	36/35/32/31/29/27	39/36/34/31/29/27	41/39/37/35/33/32	44/43/41/39/37/36	
Airflow Rate		m ³ /min	6.0/5.7/5.3/	7.4/7.0/6.4/	8.0/7.4/7.0/	8.2/7.6/6.8/	9.0/8.5/7.8/	10.1/9.7/9.0/
			5.1/4.7/4.5	6.0/5.6/5.3	6.4/6.0/5.6	6.2/5.7/5.3	7.2/6.6/6.4	8.5/7.9/7.3
Panel Colour	-	Pure White	Pure White	Pure White	Pure White	Pure White	Pure White	
Piping	Connection Type	-	Flare-nut Connection (with Flare Nuts)					
	Liquid	mm	ϕ 6.35	ϕ 6.35	ϕ 6.35	ϕ 6.35	ϕ 6.35	ϕ 6.35
Piping		inch	1/4	1/4	1/4	1/4	1/4	1/4
	Gas	mm	ϕ 12.70	ϕ 12.70	ϕ 12.70	ϕ 12.70	ϕ 12.70	ϕ 12.70
Piping		inch	1/2	1/2	1/2	1/2	1/2	1/2
	Condensate Drain	mm	O.D. 18					
Weight	Net Weight	kg	16.1	16.1	16.1	17.4	17.4	17.4
	Gross Weight	kg	20.6	21.1	21.1	21.5	21.5	21.5
Dimensions	External	H	mm	630	630	630	630	630
		W	mm	700	700	700	700	700
		D	mm	225	225	225	225	225
	Packaging	H	mm	725	725	725	725	725
		W	mm	790	790	790	790	790
		D	mm	315	315	315	315	315

Notes:

- The nominal cooling capacity and heating capacity are based on the following conditions:
 Cooling Operation Conditions
 Indoor Air Inlet Temperature: 27°C DB (80°F DB), 19.0°C WB (66.2°F WB)
 Outdoor Air Inlet Temperature: 35°C DB (95°F DB)
 Piping Length: 7.5 Meters Piping Lift: 0 Meter
 Heating Operation Conditions
 Indoor Air Inlet Temperature: 20°C DB (68°F DB)
 Outdoor Air Inlet Temperature: 7°C DB (45°F DB), 6°C WB (43°F WB)


- The sound pressure level is based on following conditions:
 It is measured in anechoic room. Operation noise differs with operation and ambient conditions.
 Location of Microphone:



Ceiling Ducted Type (AC/DC Low Height)




Space Saving

Concealed AC/DC Low Height Ducted unit is as slim as 192mm, fitting into the narrowest ceiling spaces. Save ceiling spaces for higher room height without compromising user's comfort and satisfaction.



3D Air Flow

Classy air discharge louver panel with LED temperature and humidity display is available as an optional accessory for the low-height ceiling ducted units. The 3D louvers on the panel offer wide air flow coverage to keep every corners of your room cool or warm in any seasons of the year.



Ceiling Ducted Type (AC Low Height)



Model		AVE-05 HCFRL	AVE-07 HCFRL	AVE-09 HCFRL	AVE-12 HCFRL	AVE-15 HCFRL	AVE-17 HCFRL	AVE-19 HCFRL	AVE-22 HCFRL	AVE-24 HCFRL	
Power Supply		AC 1 φ, 220V~240V/50Hz									
Capacity	Cooling	kW	1.7	2.2	2.8	3.6	4.5	5.0	5.6	6.3	7.1
		Btu/h	5,800	7,500	9,600	12,300	15,300	17,100	19,100	21,500	24,200
	Heating	kW	1.9	2.5	3.2	4.0	5.0	5.6	6.3	7.1	8.0
		Btu/h	6,500	8,500	11,300	13,600	17,100	19,100	21,500	24,200	27,300
Power Input	Cooling	W	50	50	70	70	80	80	100	120	120
	Heating	W	50	50	70	70	80	80	100	120	120
Sound Pressure	dB(A)	29/24/22	29/24/22	35/25/23	35/25/23	36/25/23	36/25/23	35/25/23	39/26/25	39/26/25	
Airflow Rate	m ³ /min	7/5.5/4.7	7/5.5/4.7	9/5.7/4.8	9/5.7/4.8	12/6.3/5.5	12/6.3/5.5	13.5/8/7.7	18/9.3/8.7	18/9.3/8.7	
External Static Pressure	Pa	10(30)	10(30)	10(30)	10(30)	10(30)	10(30)	10(30)	10(30)	10(30)	
Piping	Connection Type	-	Flare-nut Connection (with Flare Nuts)								
	Liquid	mm	φ 6.35	φ 6.35	φ 6.35	φ 6.35	φ 6.35	φ 6.35	φ 6.35	φ 9.53	φ 9.53
		inch	1/4	1/4	1/4	1/4	1/4	1/4	1/4	3/8	3/8
	Gas	mm	φ 12.70	φ 12.70	φ 12.70	φ 12.70	φ 12.70	φ 12.70	φ 15.88	φ 15.88	φ 15.88
		inch	1/2	1/2	1/2	1/2	1/2	1/2	5/8	5/8	5/8
	Condensate Drain	mm	I.D.32								
Weight	Net Weight	kg	16	16	17	17	21	21	25	26	26
	Gross Weight	kg	19	19	20	20	24	24	29	29	29
Dimensions	External	H mm	192	192	192	192	192	192	192	192	192
		W mm	700	700	700	700	910	910	1180	1180	1180
		D mm	447	447	447	447	447	447	447	447	447
	Packaging	H mm	270	270	270	270	270	270	270	270	270
		W mm	925	925	925	925	1136	1136	1406	1406	1406
		D mm	574	574	574	574	574	574	574	574	574

Notes:

1. The nominal cooling capacity and heating capacity are based on the following conditions:
 Cooling Operation Conditions
 Indoor Air Inlet Temperature: 27°C DB (80°F DB), 19.0°C WB (66.2°F WB)
 Outdoor Air Inlet Temperature: 35°C DB (95°F DB)
 Piping Length: 7.5 Meters Piping Lift: 0 Meter
 Heating Operation Conditions
 Indoor Air Inlet Temperature: 20°C DB (68°F DB)
 Outdoor Air Inlet Temperature: 7°C DB (45°F DB), 6°C WB (43°F WB)

2. The sound pressure level is based on the following conditions: 1.5m beneath the unit.
 The above data was measured in an anechoic chamber so that the reflected sound should be taken into consideration in the field.

R32 | R410A

Ceiling Ducted Type (DC Low Height)



Model		AVE-05HJDDH	AVE-07HJDDH	AVE-09HJDDH	AVE-12HJDDH	AVE-15HJDDH	AVE-19HJDDH	AVE-24HJDDH	
Power supply		AC 1 φ, 220V~240V/50Hz/60Hz							
Capacity	Cooling	kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1
		Btu/h	5,800	7,500	9,600	12,300	15,300	19,100	24,200
	Heating	kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0
		Btu/h	6,500	8,500	11,300	13,600	17,100	21,500	27,300
Power Input	Cooling	W	30	30	50	50	60	60	90
	Heating	W	30	30	50	50	60	60	90
Sound Pressure	dB(A)	28/27/26/24/23/21	28/27/26/24/23/21	35/32/32/30/26/23	35/32/32/30/26/23	35/32/32/30/26/23	35/32/30/28/25/23	38/36/35/33/31/24	
Air Flow Rate	m ³ /min	7.0/6.5/6.1/	7.0/6.5/6.1/	9.0/8.1/7.3/	9.0/8.1/7.3/6.7/	12.0/10.8/9.4/	13.5/12.5/11.2/	18.0/16.1/14.3/	
External Static Pressure	Pa	5.7/5/3/4.8	5.7/5/3/4.8	6.7/5.9/5.2	5.9/5.2	8.1/6.8/5.5	10.0/8.8/7.7	12.3/10.5/8.7	
External Static Pressure	Pa	10(10-30-50)							
Piping	Connection Type	-	Flare-nut Connection(with Flare Nuts)						
	Liquid	mm	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35	φ9.53
		inch	1/4	1/4	1/4	1/4	1/4	1/4	3/8
	Gas	mm	φ12.7	φ12.7	φ12.7	φ12.7	φ12.7	φ15.88	φ15.88
		inch	1/2	1/2	1/2	1/2	1/2	5/8	5/8
	Condensate Drain	mm	I.D.32						
Weight	Net Weight	kg	16	16	17	17	20	24	24
	Gross Weight	kg	19	19	20	20	24	29	29
Dimensions	External	H mm	192	192	192	192	192	192	192
		W mm	700	700	700	700	910	1180	1180
		D mm	447	447	447	447	447	447	447
	Packaging	H mm	270	270	270	270	270	270	270
		W mm	925	925	925	925	1136	1406	1406
		D mm	574	574	574	574	574	574	574

Notes:



1. The nominal cooling capacity and heating capacity are based on the following conditions:
 Cooling Operation Conditions
 Indoor Air Inlet Temperature: 27°C DB (80°F DB), 19.0°C WB (66.2°F WB)
 Outdoor Air Inlet Temperature: 35°C DB (95°F DB)
 Piping Length: 7.5 Meters Piping Lift: 0 Meter
 Heating Operation Conditions
 Indoor Air Inlet Temperature: 20°C DB (68°F DB)
 Outdoor Air Inlet Temperature: 7°C DB (45°F DB), 6°C WB (43°F WB)

2. The sound pressure level is based on the following conditions: 1.5m beneath the unit.
 The above data was measured in an anechoic chamber so that the reflected sound should be taken into consideration in the field.

Ceiling Ducted Type(DC High Static Pressure)


Auto-adjust External Static Pressure

After installation, the actual duct resistance frequently differ from the initially calculated, causing the actual air flow too low or too high. The auto-adjust ESP function can effectively solve this problem. At the initial commission, the system can automatically select the most appropriate ESP value according to the actual duct resistance.



Cold Wind Limit Setting

Thanks to the Cold Wind Limit Setting function, the lowest limit of the outlet air temperature can be set in the range of 10~16°C, which can ensure that the actual outlet temperature will never be lower than the set value, and avoid uncomfortable feeling caused by the direct blowing of cold wind.




New Improved Bendable Filters

Filters that comes with the units are now optimized to be bendable by improving the material's malleability to improve installation flexibility in narrow ceiling height and restricted spaces.




Self-cleaning Function

Featured with self-cleaning technology, the evaporator can be self-cleaned automatically just with the tap of a button in the controller, which is very convenient and saves the cost of manual cleaning, while ensuring a clean environment.



4 processes for deep cleaning

Ceiling Ducted Type (DC High Static Pressure)



Model		AVD-07	AVD-09	AVD-12	AVD-15	AVD-19	AVD-24	AVD-24	AVD-30	AVD-38	AVD-48	AVD-54	AVD-76	AVD-96		
		HJFH	HJFH	HJFH	HJFH	HJFH	HJFH	HJFH1	HJFH	HJFH	HJFH	HJFH	HJFH	HJFH		
Power Supply		AC 1Φ, 220V-240V/50Hz/60Hz														
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1	7.1	9.0	11.2	14.0	16.0	22.4	28.0	
		Btu/h	7,500	9,600	12,300	15,400	19,100	24,200	24,200	30,800	38,000	48,000	54,500	76,500	95,600	
Capacity	Heating	kW	2.5	3.2	4.0	4.6	6.3	8.0	8.0	10.0	12.5	16.0	18.0	25.0	31.5	
		Btu/h	8,500	10,900	13,700	17,100	21,600	27,400	27,400	34,200	42,500	54,500	61,500	85,300	107,500	
Power Input	Cooling	W	40	40	55	55	55	82	74	100	132	180	223	610	830	
	Heating	W	40	40	55	55	55	82	74	100	132	180	223	610	830	
Sound Pressure Level	dB(A)	30/27/23/ 21/20/19	30/27/23/ 21/20/19	35/33/32/ 28/26/24	35/33/32/ 28/26/24	33/30/27/ 25/23/22	36/34/31/ 28/24/22	33/31/28/ 25/23/21	34/32/30/ 28/25/22	37/35/31/ 29/26/23	38/36/34/ 31/29/26	41/38/35/ 33/30/27	49/48/47/ 46/45/44	53/52/50/ 49/47/45		
Airflow Rate	m ³ /min	9/8/6.8/ 6.3/5.8/5.3	9/8/6.8/ 6.3/5.8/5.3	12/11/10/ 9/8/7.2	12/11/10/ 9/8/7.2	14.5/13/11.5/ 10.5/9.5/8.7	19/17/15/ 13/11/9.5	20.6/19/17/ 15/13.8/12.5	25/23/21/ 19/17/15	28/25/23/ 21/19/17	35/32.5/29.5/ 26.5/23.5/21.8	39/35.5/31/ 26.5/23.5/21.8	57/54/52/ 51/49/48	72/68/65/ 61/58/50		
External Static Pressure	Pa	30 (30/40/50/60/70/80/90/100/110/120/130/140/150)						50 (50/60/70/80/90/100/110/120/130/140/150/160/170/180/190/200)						150(50-250)	150(50-250)	
Piping	Connection Type	-	Flare-Nut Connection(With Flare Nut)									Brazing				
	Liquid	mm	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35	φ9.53	φ9.53	φ9.53	φ9.53	φ9.53	φ9.53	φ9.53	φ9.53	
		inch	1/4	1/4	1/4	1/4	1/4	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	
	Gas	mm	φ12.7	φ12.7	φ12.7	φ12.7	φ15.88	φ15.88	φ15.88	φ15.88	φ15.88	φ15.88	φ15.88	φ22.2 (φ19.05 ^{*1})	φ22.2	
inch		1/2	1/2	1/2	1/2	5/8	5/8	5/8	5/8	5/8	5/8	5/8	7/8 (3/4 ^{*1})	7/8		
Condensate Drain	-	I.D. 32														
Weight	Net Weight	kg	23	23	24	24	30	30	40	40	40	49	49	104	104	
	Gross Weight	kg	29	29	29	29	37	37	48	48	48	57	57	125	125	
Dimensions	External	H mm	270	270	270	270	270	270	300	300	300	300	300	470	470	
		W mm	650+75	650+75	650+75	650+75	900+75	900+75	1100+75	1100+75	1100+75	1100+75	1400+75	1400+75	1250	1250
		D mm	720	720	720	720	720	720	800	800	800	800	800	800	1120	1120
	Packing	H mm	385	385	385	385	385	385	415	415	415	415	415	415	546	546
		W mm	895	895	895	895	1140	1140	1345	1345	1345	1345	1640	1640	1466	1466
		D mm	870	870	870	870	870	870	950	950	950	950	950	950	1345	1345

Notes:

1. The nominal cooling capacity and heating capacity are based on the following conditions:
 Cooling Operation Conditions
 Indoor Air Inlet Temperature: 27° C DB(80° F DB), 19.0° C WB(66.2° F WB)
 Outdoor Air Inlet Temperature: 35° C DB(95° F DB)
 Heating Operation Conditions
 Indoor Air Inlet Temperature: 20° C DB(68° F DB),
 Outdoor Air Inlet Temperature: 7° C DB(45° F DB), 6° C WB(43° F WB)
 Piping Length: 7.5 Meters Piping Lift: 0 Meter

2. The sound pressure level is based on following conditions.
 1.5m below the unit; With 2.0m discharge duct and 1.0m return duct
 The above data were measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
 3. *1: The size of AVD-76° series gas pipe is φ22.2mm when leaving the factory, and the diameter can be changed to 19.05mm after welding the adapter pipe.

RELIABILITY
EFFICIENCY
COMFORT
FLEXIBILITY
OUTDOOR UNIT
INDOOR UNIT
CONTROL SYSTEM
ACCESSORY

Ceiling Ducted Type (High/Low Static Pressure)

Flexible Air Duct Layout

High static pressure facilitates extensive ducts and air outlets network, effectively sends air-conditioned air to every corner of the room.




New Improved Bendable Filters

Standard filters that comes with high/low static pressure ceiling ducted type are now optimized to be bendable by improving the material's malleability to improve installation flexibility in narrow ceiling height and restricted spaces.




Fresh Air Introducing

There is a fresh air duct opening reserved in the unit for 10% free fresh air introductory directly from outdoor, providing fresh air to the indoor continuously.



Various Device Connection Options

Third party devices to control the on-off air conditioners is possible with dry contact connections to the Indoor unit. Devices like room key card, window contact and fire alarms can be connected simultaneously.




Smart & Precise Temperature Control

To prevent the human height area of the room cools or warms to user's ideal temperature setting. Two Temperature Sensor Control Technology is integrated into the unit whereby the controller, and return section consist of built in temperature sensors to send real-time signals to the unit for a more precise supplying temperature.



Hisense VRF




Conventional

Wall Mounted Type


High-efficiency DC Fan Motor

Equipped with a DC fan motor, the unit significantly reduces the power consumption by 60% compared to conventional AC products, ensuring low-cost operation.



6 Fan Speed

6 indoor fan speeds are available to meet the needs of different indoor conditions.



R32 | R410A

Wall Mounted Type



Model		AVS-05 HJDTD	AVS-07 HJDTD	AVS-09 HJDTD	AVS-12 HJDTD	AVS-15 HJDTD	AVS-19 HJDTD	AVS-24 HJDTD	AVS-28 HJDTD		
Power Supply		AC 1 ϕ , 220V-240V/50Hz/60Hz									
Capacity	Cooling	kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1	8.4	
		Btu/h	5,800	7,500	9,600	12,300	15,400	19,100	24,200	28,700	
Power Input	Heating	kW	2.0	2.5	3.3	4.0	5.0	6.3	8.0	8.4	
		Btu/h	6,500	8,500	11,300	13,700	17,100	21,500	27,300	28,700	
Sound Pressure	Cooling	W	20	20	20	30	20	30	50	80	
	Heating	W	20	20	20	30	30	30	70	80	
Airflow Rate		dB(A)	33/32/32/ 30/30/28	36/35/33/ 32/30/28	36/35/33/ 32/30/28	38/35/33/ 32/30/28	38/37/36/ 32/31/29	40/38/36/ 35/33/31	45/42/41/ 38/35/31	50/48/45/ 41/36/33	
		m ³ /min	8.7/8.3/8.2/ 7.5/7.2/7.0	9.8/9.2/8.7/ 8.2/7.5/7.0	9.8/9.2/8.7/ 8.2/7.5/7.0	10.3/9.2/8.7/ 8.2/7.5/7.0	11.5/11.0/10.3/ 9.0/8.7/8.0	16.2/15.0/14.2/ 13.3/12.2/11.5	20.0/18.0/17.0/ 15.0/13.3/11.7	23.3/22.0/20.0/ 17.0/14.2/12.2	
Panel Colour		White									
Piping	Connection Type		Flare-nut Connection(with Flare Nuts)								
	Liquid	mm	ϕ 6.35	ϕ 6.35	ϕ 6.35	ϕ 6.35	ϕ 6.35	ϕ 9.53	ϕ 9.53	ϕ 9.53	
		inch	1/4	1/4	1/4	1/4	1/4	3/8	3/8	3/8	
	Gas	mm	ϕ 9.53	ϕ 9.53	ϕ 9.53	ϕ 9.53	ϕ 12.7	ϕ 15.88	ϕ 15.88	ϕ 15.88	
inch		3/8	3/8	3/8	3/8	1/2	5/8	5/8	5/8		
Condensate Drain		O.D. 22									
Weight	Net Weight	kg	9.5	9.5	9.5	9.5	13.0	14.4	14.4	14.4	
	Gross Weight	kg	13.4	13.4	13.4	13.4	17.8	19.4	19.4	19.4	
Dimensions	External Dimension	H	mm	270	270	270	270	315	315	315	
		W	mm	845	845	845	845	960	1120	1120	
		D	mm	203	203	203	203	230	230	230	
	Packaging Dimension	H	mm	375	375	375	375	430	430	430	
		W	mm	943	943	943	943	1058	1223	1223	
		D	mm	310	310	310	310	328	328	328	

Dual Purification to Enhance the Health of Indoor Air

Self-cleaning of Indoor Units

The indoor units feature an intelligent self-cleaning function that efficiently clears the heat exchangers without manual intervention, saving your valuable time and cost.



56°C High-temperature Sterilization

With an advanced 56°C high-temperature sterilization function, our indoor units swiftly eliminate viruses within the indoor unit. This ensures the released air is pure, providing users a healthy and comfortable indoor environment.



Notes:

1. The rated capacity is based on the following conditions:
Cooling conditions: indoor air inlet temperature: 27°C DB, 19°C WB, outdoor air inlet temperature: 35°C DB, pipe length: 7.5m, pipe height difference: 0m.
Heating conditions: indoor air inlet temperature: 20°C DB, outdoor air inlet temperature: 7°C DB, 6°C WB, pipe length: 7.5m, pipe height difference: 0m.

2. The above noise values are measured in an anechoic chamber so that reflected sound should be taken into consideration during actual operation.
The above noise values are measured under the fan mode operation, and measured at a point 1m in front of the unit and 0.8m below the unit.

Ceiling & Floor Type

Sleek Smooth Design

Shiny white cover panel of the unit has a streamlined elegant aesthetic. The bolts and nuts used to secure the unit onto wall or ceiling are designed to be concealed in the unit for a sleek room interior look.



Flexible Installation


The unit can be installed to be standing on floors or hanging on ceilings. Whereby interior walls maximized to display items, can hang the unit on the ceiling.



Hanging on the wall Standing on the floor


Wide Air Supply

Louvers consist of horizontal and vertical flaps to cover larger coverage area to the edges of any rooms. Wider opening angle from up to 120° for vertical louvers and up to 71° for horizontal louvers supplies air further and lower down to floor.



Convenient Installation and Maintenance

Adjust the ceiling or wall mounting height by just opening the side panels without the need to access the internal parts. Service manholes are unnecessary due to the strategic repositioning of piping connections and electrical box behind the air return panel.



Ceiling & Floor Type



Model			AVV-17URSCA	AVV-18URSCA	AVV-22URSCA	AVV-24URSCA	AVV-27URSCB	AVV-30URSCB	AVV-38URSCB	AVV-48URSCC
Power Supply			AC 1 Φ, 220V-240V/50Hz/60Hz							
Capacity	Cooling	kW	5.0	5.6	6.3	7.1	8.4	9.0	11.2	14.2
		Btu/h	17,100	19,100	21,500	24,200	28,700	30,700	38,200	48,500
	Heating	kW	5.6	6.5	7.5	8.5	9.6	10.0	13.0	16.3
		Btu/h	19,100	22,200	25,600	29,000	32,800	34,100	44,400	55,600
Power Input	Cooling	W	40	40	70	70	70	80	130	160
	Heating	W	40	40	70	70	70	80	130	160
Sound Pressure	Ceiling	dB(A)	39/35/30	39/35/30	45/41/37	45/41/37	43/39/34	45/40/36	51/46/40	50/46/42
	Floor	dB(A)	43/38/35	43/38/35	48/44/40	48/44/40	46/41/37	48/43/39	54/49/43	55/50/46
Airflow Rate	m ³ /min		13.0/11.0/9.0	13.0/11.0/9.0	16.1/14.0/11.3	16.1/14.0/11.3	18.2/15.2/12.2	19.4/16.3/13.3	24.8/20.5/16.3	33.0/28.0/23.0
Speed-up Setting HH1	m ³ /min		14.2	14.2	17.8	17.8	19.8	21.2	27.0	36.0
Speed-up Setting HH2	m ³ /min		16.0	16.0	20.0	20.0	22.3	23.5	29.2	37.4
Panel Colour			Neture White							
Piping	Connection Type		Flare-nut Connection (with Flare Nuts)							
	Liquid	mm	φ 6.35	φ 6.35	φ 9.53	φ 9.53	φ 9.53	φ 9.53	φ 9.53	φ 9.53
		inch	1/4	1/4	3/8	3/8	3/8	3/8	3/8	3/8
	Gas	mm	φ 15.88	φ 15.88	φ 15.88	φ 15.88	φ 15.88	φ 15.88	φ 15.88	φ 15.88
		inch	5/8	5/8	5/8	5/8	5/8	5/8	5/8	5/8
	Condensate Drain	mm	I.D.32							
Weight	Net Weight	kg	31	31	32	32	39	40	41	47
	Gross Weight	kg	38	38	39	39	46	47	48	56
Dimensions	External	H mm	230	230	230	230	230	230	230	230
		W mm	990	990	990	990	1285	1285	1285	1580
	Packaging	D mm	680	680	680	680	680	680	680	680
		H mm	340	340	340	340	340	340	340	340
		W mm	1110	1110	1110	1110	1400	1400	1400	1690
		D mm	830	830	830	830	830	830	830	830

Notes:

- The nominal cooling capacity and heating capacity are based on the following conditions:
 Cooling Operation Conditions
 Indoor Air Inlet Temperature: 27°C DB (80°F DB), 19.0°C WB (66.2°F WB)
 Outdoor Air Inlet Temperature: 35°C DB (95°F DB)
 Piping Length: 7.5 Meters Piping Lift: 0 Meter
 Heating Operation Conditions
 Indoor Air Inlet Temperature: 20°C DB (68°F DB)
 Outdoor Air Inlet Temperature: 7°C DB (45°F DB), 6°C WB (43°F WB)

- The sound pressure level is based on the following conditions:
 1.0m beneath the unit, 1.0m from Discharge Grille.
 The above data was measured in an anechoic chamber so that the reflected sound should be taken into consideration in the field. When bottom air inlet is adopted, sound pressure will increase according to factors such as installation mode and the room structure.

Floor Concealed Type



Space Saving

Floor concealed units are designed to be installed on floors completely concealed into the walls which designed to be slim and compact with only height of 620mm to be hidden under half-heighted windows.



Adjustable Static Pressure and Flexible Installation

With 2-level external static pressure adjustable, project design and installation are more flexible. Users can choose the air duct to increase the air supply distance in order to achieve the completely concealed installation.



Model		AVH-09UXCSAA	AVH-14UXCSAA	AVH-18UXCSBA	AVH-24UXCSBA	
Power Supply		AC 1Φ, 220V-240V/50Hz				
Model		AVH-09UX2SAA	AVH-14UX2SAA	AVH-18UX2SBA	AVH-24UX2SBA	
Power Supply		AC 1Φ, 220V/60Hz				
Capacity	Cooling	kW	2.8	4.3	5.6	7.1
		Btu/h	9,600	14,700	19,100	24,200
	Heating	kW	3.3	4.9	6.5	8.5
		Btu/h	11,300	16,700	22,200	29,000
Power Input	Cooling	W	50	80	90	120
	Heating	W	50	80	90	120
Sound Pressure	dB(A)	34/31/27	40/36/34	41/36/32	44/40/36	
Airflow Rate	m ³ /min	8.5/7.5/6.3	10.3/9.0/8.0	14.8/12.3/10.5	16.3/13.8/11.8	
Piping	Connection Type	-	Flare-nut Connection (with Flare Nuts)			
	Liquid	mm	φ 6.35	φ 6.35	φ 6.35	φ 9.53
		inch	1/4	1/4	1/4	3/8
	Gas	mm	φ 12.70	φ 12.70	φ 15.88	φ 15.88
		inch	1/2	1/2	5/8	5/8
	Condensate Drain	mm	I.D.32			
Weight	Net Weight	kg	18	22	26	27
	Gross Weight	kg	30	31	37	37
Dimensions	External	H mm	620	620	620	620
		W mm	948+139	948+139	1218+139	1218+139
		D mm	202	202	202	202
	Packaging	H mm	675	675	675	675
		W mm	1160	1160	1430	1430
		D mm	240	240	240	240

Notes:


1. The nominal cooling capacity and heating capacity are based on the following conditions:
 Cooling Operation Conditions
 Indoor Air Inlet Temperature: 27°C DB (80°F DB), 19.0°C WB (66.2°F WB)
 Outdoor Air Inlet Temperature: 35°C DB (95°F DB)
 Piping Length: 7.5 Meters Piping Lift: 0 Meter
 Heating Operation Conditions
 Indoor Air Inlet Temperature: 20°C DB (68°F DB)
 Outdoor Air Inlet Temperature: 7°C DB (45°F DB), 6°C WB (43°F WB)

2. The sound pressure level is based on the following conditions:
 1.5m meters from the unit and 1.5m meters from floor level.
 The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

All Fresh Air Indoor Unit


Space Saving

Fresh air unit consisting of height of 370mm only requires small amount of ceiling space and fits into complicated kitchen ceilings with various exhaust duct connections.



Larger Airflow Rate & Static Pressure Options

The total amount of fresh air units could be reduced with larger capacity, large airflow rate per unit. With the reduced amount of units, fresh air ducts often need to be supply to the furthest room. Hence achievable with high static pressures offered.



*Note: only specific model can reach this figure.

Simple & Flexible Piping System

Fresh air from the units could be pre-cooled connecting to the same refrigerant systems with other indoor units, introducing cooled or warm fresh air directly without overburdening other fan coil units.



All Fresh Air Indoor Unit



Model	AVA-30UX CSCH-70	AVA-48UX CSQH-108	AVA-76UX CSRH-168	AVA-96UX CSRH-210	AVA-114UX 6SRH-300	AVA-154UX 6SSH-400	AVA-190UX 6STH-500	AVA-190UX 6STH-600		
Power Supply	AC 1 φ, 220V-240V/50Hz				AC 3 φ, 380V-415V/50Hz					
Model	AVA-30UX 2SCH-70	AVA-48UX 2SQH-108	AVA-76UX 2SRH-168	AVA-96UX 2SRH-210						
Power Supply	AC 1 φ, 220V/60Hz				-					
Capacity	Cooling	kW	9.0	14.0	22.4	28.0	33.5	45.0	56.0	56.0
	Btu/h	30,700	47,800	76,500	95,600	114,300	153,600	191,100	191,100	
Heating	kW	8.6	13.7	21.9	24.5	26.8	36.0	44.8	44.8	
	Btu/h	29,400	46,800	74,700	83,600	91,500	122,900	152,900	152,900	
Power Input	Cooling	W	150	330	490	510	740	1120	1330	1620
	Heating	W	150	330	490	510	740	1120	1330	1620
Sound Pressure	dB(A)	32	43	45	46	56	61	64	66	
Airflow Rate	m ³ /min	11.0	18.0	28.0	35.0	50.0	66.7	83.3	100.0	
External Static Pressure	Pa	60(120)	200	220	220	220	300	320	300	
Piping	Liquid	mm	φ 9.53	φ 9.53	φ 9.53	φ 9.53	φ 12.70	φ 12.70	φ 15.88	φ 15.88
		inch	3/8	3/8	3/8	3/8	1/2	1/2	5/8	5/8
Gas	mm	φ 15.88	φ 15.88	φ 19.05	φ 22.20	φ 25.40	φ 25.40	φ 28.60	φ 28.60	
	inch	5/8	5/8	3/4	7/8	1	1	1-1/8	1-1/8	
Condensate Drain	mm	I.D.32				RC1 (Internal Screw)				
Weight	Net Weight	kg	46	60	97	97	97	196	222	222
	Gross Weight	kg	51	64	117	117	117	240	267	267
Dimensions	External	H mm	370	370	486	486	486	635	735	735
		W mm	920	1320	1270	1270	1270	1950	1950	1950
		D mm	800	800	1069	1069	1069	805	805	805
	Packaging	H mm	390	390	540	540	540	816	916	916
		W mm	1112	1512	1466	1466	1466	2213	2213	2213
		D mm	922	922	1290	1290	1290	1006	1006	1006
Temperature Range of Fresh Air	-	Cooling: 20°C-43°C, Heating: -5°C-15°C								


Notes:

- The nominal cooling capacity and heating capacity are based on following conditions:
Cooling operation conditions: 33°C DB, 28°C WB, piping length: 7.5m, piping lift: 0m.
Heating operation conditions: 0°C DB, -2.9°C WB, piping length: 7.5m, piping lift: 0m.
(Heating capacity is tested when defrosting is not available)
- The sound pressure level is based on following conditions: 1.5m beneath the unit.
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
- The unit shall be connected to the outdoor unit. In case of connecting the fresh air indoor unit with other types of indoor units in the same refrigerant system, please calculate the capacity of the unit as 46.1KBtu/h (30.7KBtu/h), 71.7KBtu/h (47.8KBtu/h), 143.3KBtu/h (95.6KBtu/h).
- When the outdoor unit is connected only with all fresh air indoor unit, the configuration rate is 100%.
- Under cooling mode, when outdoor temperature is lower than 20°C, the system will automatically shift to ventilation operation;
Under heating mode, when outdoor temperature is higher than 15°C the system will automatically shift to ventilation operation;
In case inlet temperature is below -5°C, all fresh air unit will stop.


Heat Recovery Ventilator

Compact Body, Convenient Installation

Its compact design facilitates easy installation in narrow ceilings. With a width of only 735mm, the unit (HKF/50C1EC) is perfect for the tight ceiling spaces.




Airflow System



3-level Fan Speed for Your Choice

The three-level fan speed adjustment, offering high, medium, and low options, provides flexibility to cater to individual preferences in various environments.



*This feature is available for the unit HKF/50C1EC, HKF/80C1EC, HKF/100C1EC.

Low Noise

The unit features a low-noise fan, optimal internal silencer, and air channels, significantly reducing operation noise to 26.5dB(A)*. Additionally, a static pressure adjustment plate on the exhaust side optimizes outdoor static pressure, further minimizing the noise.

* The noise level under the low airflow speed for the unit HKF/50C1EC can achieve 26.5dB(A).

Heat Recovery Ventilator


Intelligent Control

The unit can be easily connected to the central control system through the dedicated converter* , enabling centralized control alongside the air-conditioning system.


* For central control requirements, please contact our technical engineers regarding the converter.

Features

- Large LED screen display
- Temp. and fan speed display
- Fan speed setting
- Timer



Wired Controller HYXE-KC01



High-efficiency Heat-exchange Core

The hexagonal high-efficiency counterflow heat exchanger core adopts ultra-thin high-performance heat transfer membrane and an integrated optimized flow channel, which extends the time of the heat exchange, thereby improving the heat exchange efficiency. It effectively processes the temperature and humidity of the outdoor fresh air to a level close to the indoor air condition, thereby reducing air conditioning energy consumption.




Note: The unit HKF/50C1EC is equipped with a hexagonal heat exchanger.

RELIABILITY
EFFICIENCY
COMFORT
FLEXIBILITY
OUTDOOR UNIT
INDOOR UNIT
CONTROL SYSTEM
ACCESSORY

Energy Saving Analysis

During the summer, the indoor air at 27°C is exhausted and passes through the heat exchanger core. This process pre-cools the outdoor air from 35°C to 30.2°C, which is then introduced into the indoor space as fresh air, as shown in the diagram. The air conditioning system only needs to further cool this air by 3.2°C to maintain a comfortable indoor temperature. Taking the HKF-50C1EC as an example, the air flow is 500m³/h, heat recovery efficiency is 60%, and enthalpy exchange efficiency is 63%.



Inlet fresh air		HRV	Fan
Dry bulb temp.	30.2	35	
Wet bulb temp.	22.9	28	
Moisture content	14.7	21.1	
Relative humidity	54.5	59.1	
Enthalpy	68	89.4	
Cooling recovery	1.76	0	
Heat load	2.8	2.8	


Air conditioning		Indoor air	
Dry bulb temp.		27	
Moisture content		19.5	
Relative humidity		49.8	
Enthalpy		55.5	

Outdoor Air	
Dry bulb temp.	35
Wet bulb temp.	28
Relative humidity	59.1
Enthalpy	89.4

Exhaust air	
Dry bulb temp.	27
Moisture content	19.5
Relative humidity	49.8
Enthalpy	55.5

HRV VS Traditional Fan

During the winter, the indoor air at 21°C is exhausted and passes through the heat exchanger core. This process preheats the outdoor air from 5°C to 17°C, which is then introduced into the indoor space as fresh air, as shown in the diagram. The air conditioning system only needs to further heat this air by 4°C to maintain a comfortable indoor temperature. Taking the HKF-50C1EC as an example, the air flow is 500m³/h, heat recovery efficiency is 80%, and enthalpy exchange efficiency is 70%.



Inlet		HRV	Fan
Dry bulb temp.	17.8	5	
Wet bulb temp.	10.16	2	
Moisture content	4.5	6	
Relative humidity	36	58.5	
Enthalpy	29.4	12.9	
Heating recovery	1.4	0	
Heat load	2	2	

Air conditioning		Indoor air	
Dry bulb temp.		21	
Moisture content		13	
Relative humidity		39.2	
Enthalpy		36.5	

Outdoor Air	
Dry bulb temp.	5
Wet bulb temp.	2
Relative humidity	58.5
Enthalpy	12.9

Exhaust air	
Dry bulb temp.	21
Moisture content	13
Relative humidity	39.2
Enthalpy	36.5

HRV VS Traditional Fan



Model (HKF/*)		50C1EC	80C1EC	100C1EC	150C1EE	200C1EE	250C1EE	300C1EE		
Power Supply		AC 1Φ, 220V/50Hz			AC 3Φ, 380V/50Hz					
Air Flow	High	m³/h	500	800	1000	1500	2000	2500	3000	
	Medium	m³/h	300	600	750	—	—	—	—	
	Low	m³/h	180	400	500	—	—	—	—	
Fresh Air Static Pressure	High	Pa	80	130	165	180	160	180	200	
	Medium	Pa	70	100	120	—	—	—	—	
	Low	Pa	40	80	60	—	—	—	—	
Exhaust Air Static Pressure	High	Pa	80	130	165	180	160	180	200	
	Medium	Pa	70	100	120	—	—	—	—	
	Low	Pa	40	80	60	—	—	—	—	
ESP	Fresh Air Available	High	Pa	80	130	165	180	160	200	
	Medium	Pa	70	100	120	—	—	—	—	
	Low	Pa	40	80	60	—	—	—	—	
Exhaust Air Available	High	Pa	80	130	165	180	160	200	228	
	Medium	Pa	70	100	120	—	—	—	—	
	Low	Pa	40	80	60	—	—	—	—	
Sound Pressure Level	High	dB(A)	38.5	40	43	46	47	51	52	
	Medium	dB(A)	33.5	38	41	—	—	—	—	
	Low	dB(A)	26.5	34	38	—	—	—	—	
Enthalpy Exchange Efficiency	Cooling	High	%	63	57	57	56	56	57	
		Medium	%	63	57	57	—	—	—	—
		Low	%	65	59	58	—	—	—	—
Heating	High	%	69	66	66	65	65	64	63	
	Medium	%	69	66	66	—	—	—	—	
	Low	%	71	68	68	—	—	—	—	
Heat Exchange System		Air-to-air cross flow heat recovery (sensible heat + potential heat)								
Heat Exchange Part		Ventilation high efficiency all-in-one heat exchange core								
Operation Current	High	A	1.42	2.02	4.88	2.13	2.59	2.92	4.7	
	Medium	A	0.95	1.88	4.3	—	—	—	—	
	Low	A	0.67	1.72	3.47	—	—	—	—	
Input Power	High	W	313	422	1020	1050	1550	1440	2320	
	Medium	W	204	392	900	—	—	—	—	
	Low	W	140	360	726	—	—	—	—	
Net Size (L × H × W)	mm	1112 × 270 × 735	1115 × 390 × 1135	1115 × 390 × 1135	1500 × 540 × 1200	1550 × 540 × 1400	1610 × 600 × 1330	1700 × 640 × 1500		
Package Size (L × H × W)	mm	1220 × 380 × 1060	1330 × 545 × 1210	1330 × 545 × 1210	1660 × 690 × 1345	1710 × 710 × 1545	1770 × 765 × 1470	1790 × 818 × 1590		
Flange Dimensions	Air Inlet	mm				320 × 300	320 × 300	365 × 275	365 × 275	
	Air Outlet	mm	Φ 194	Φ 242	Φ 242	320 × 300	320 × 300	500 × 350	500 × 350	
Net Weight	kg	52	72	79	126	172	185	222		
Gross Weight	kg	61	93	92	149	177	189	240		
Operation Range		-10 ~ 52°C(DB), 85%RH or lower								

AHU Connection KIT

The Hisense AHU-kit integrates external heat exchangers of Air-handling units (AHU) into a Hisense VRF system to provide more flexible air conditioning solutions.

Main Function

- ON/OFF Control
- Temperature Setting
- Capacity Demand
- Operation Mode

— Communication wire — Sensor signal — Refrigerant pipe



*The wired controller HYXE-VA01A is standard.

AHU Connection KIT

AHU kit can provide 3 kinds of control type for AHU application: Inlet air temperature control, outlet air temperature control and duty signal control.

Capacity Control Mode	Set Temperature by Remote Controller	Set ODU Capacity Range
Inlet Air (room air) Temperature Control	Cooling: 16~32 °C Heating: 16~32 °C	—
Outlet Air Temperature Control		
Duty Signal Control (0~10V or 0~5V or 4~20mA)	—	15%~100%

AHU Connection KIT		HZX-2 BEJ	HZX-4 BEJ	HZX-6 BEJ	HZX-10 BEJ	HZX-20 BEJ					HZX-30 BEJ						
Power Supply		AC 1Φ, 220V~240V/50Hz/60Hz															
Nominal Capacity of AHU	kBtu/h	19	36	54	76	96	114	132	154	170	190	212	232	250	272	287	
Allowed Heat Exchanger Capacity (H/M/L)	Cooling	kW	5.6	11.2	16.0	22.4	28.0	33.5	40.0	45.0	50.0	56.0	61.5	69.0	73.0	80.0	85.0
		kW	5.0	9.0	14.0	20.0	25.0	30.0	35.0	43.0	48.0	52.0	58.0	65.0	71.0	76.0	82.0
	Heating	kW	4.0	7.1	11.2	16.0	20.0	28.0	33.5	40.0	45.0	50.0	56.0	61.5	69.0	73.0	80.0
		kW	7.1	12.5	18.0	25.0	31.5	37.5	45.0	50.0	56.0	63.0	69.0	77.5	82.5	90.0	95.0
		kW	5.6	10.0	16.0	22.4	28.0	33.5	40.0	47.5	53.0	60.0	66.0	75.0	79.0	86.0	92.0
Heat Exchanger Volume	Min	dm ³	0.57	1.03	1.92	2.92	3.89	4.76	5.85	6.79	7.57	8.47	9.04	9.50	10.39	11.39	12.36
	Max	dm ³	1.16	2.37	2.92	3.89	4.76	5.91	6.89	8.00	8.92	9.97	11.13	12.34	12.89	13.86	14.73
Equivalent Indoor Unit Capacity	kBtu/h	19	36	54	76	96	114	132	154	170	190	212	232	250	272	287	
Net Weight	kg	7.1	7.1			7.2					9.2						
Gross Weight	kg	11.7	11.8			11.9					15.4						
Package Dimension (H×W×D)	mm	350×510×450										460×510×450					
Control Box	Model	HZX-BEJ/1															
	Outer Dimension(H×W×D)	112×419×349															
Expansion Valve Box	Model	HZX-2 BEJ/2	HZX-4 BEJ/2	HZX-6 BEJ/2	HZX-10 BEJ/2	HZX-20 BEJ/2					HZX-30 BEJ/2 (2 sets)						
	Outer Dimension(H×W×D)	61×437×166										61×437×166(2 sets)					

Operation conditions		Cooling	Heating
Indoor air inlet temperature	DB	27.0°C	20.0°C
	WB	19.0°C	—
Outdoor air inlet temperature	DB	35.0°C	7.0°C
	WB	—	6.0°C

DB: dry bulb; WB: wet bulb
Pipe Length: 7.5m; pipe height: 0m

RELIABILITY
EFFICIENCY
COMFORT
FLEXIBILITY
OUTDOOR UNIT
INDOOR UNIT
CONTROL SYSTEM
ACCESSORY

CONTROL SYSTEM



Individual Control

Centralized Control

Intelligent Control

AIR
CONDITIONING
SOLUTION

Overview

Model	Wired Controller HYXM-VB01A	Wired Controller HYXE-VC01	Wired Controller HYXE-VA01A	Wired Controller HYXM-VG01	Wired Controller HYXE-S01H	Wireless Controller HYE-VD01
Picture						
Max. connectable indoor units	6	6	16	16	16	—
Power supply	15V	15V	15V	15V	15V	3V
Dimension(mm)	86*90	86*86	120*120	120*120	120*70	178.6*47.8
Cool/Heat/Fan/Auto/Dry	●	●	●	●	●	●
Auto dehumidification(humidity sensor)	●	●	●	●	●	×
Fan speed	●	●	●	●	●	●
Louver setting	●	●	●	●	●	●
Temperature setting	●	●	●	●	●	●
Operation monitoring	●	●	●	●	●	×
Timer	●	●	●	●	●	●
7-day timer	●	×	×	●	×	×
Holiday setting	●	×	×	●	×	×
Main-sub connection	●	●	●	×	×	×
Main-sub control	×	×	×	●	×	×
Change indoor address	●	●	●	●	×	×
Check function	●	●	●	●	●	×
Option setting	●	●	●	●	●	×
Air filter cleaning reminding	●	●	●	●	●	×
Error code display	●	●	●	●	●	×
Auto test run	●	●	●	●	●	●
Indoor/outdoor PCB checking	●	●	●	●	●	×
Self diagnostic function	●	●	●	●	●	●
Back light	●	●	●	●	●	●
Built-in temperature sensor	×	●	●	●	×	●
Wireless control available	●	●	×	●	×	—
Individual louver control	●	●	●	●	×	●
Breeze mode	●	●	●	●	×	×
Motion sensor	●	×	●	●	×	×
Health(Airpure)	●	●	●	●	×	●
High-temp sterilization	×	×	×	●	×	×
Hi-Motion	●	×	×	●	×	×
ECO (energy saving)	●	●	●	●	×	●
Quiet (Indoor unit)	●	●	●	●	●	●
Sleep(Indoor unit)	●	●	●	●	×	●
Window interlock	●	●	●	●	×	×
Key card	●	●	●	●	×	×
3D-air flow	●	●	●	●	×	●
Child lock	●	●	×	●	×	×
Self cleaning	●	●	●	●	×	●
Auto changeover	×	×	×	●	×	×
Dynamic ESP	×	●	×	●	×	×
Outlet air temp limit	×	●	×	●	×	×

Remarks: Available: ● Unavailable: ×

RELIABILITY

EFFICIENCY

COMFORT







FLEXIBILITY






OUTDOOR UNIT

INDOOR UNIT

CONTROL SYSTEM

ACCESSORY

Type	Wired Controller					Wireless Controller
Model	HYXM-VB01A	HYXE-VC01	HYXM-VG01	HYXE-VA01A	HYXE-S01H	HYE-VD01
Picture						
4-Way Cassette	○	○	○	○	○	○
Mini 4-Way Cassette	○	○	○	○	○	○
1-Way Cassette	○	○	○	○	×	○
2-Way Cassette	○	○	○	○	×	○
Ceiling Ducted Type (AC/DC)	○	○	○	○	○	○
Ceiling Ducted Type (High/Low)	○	○	○	○	○	○
Console	○	○	○	○	○	●
Wall Mounted Type	○	○	○	○	○	●
Ceiling & Floor Type	○	○	○	○	○	●
Floor Concealed Type	○	○	○	○	×	○
All Fresh Air	○	○	○	○	○	○
Heat Recovery Ventilator	○	●	○	○	○	×
AHU Kit	○	○	○	●	×	×

Type	Receiver Kit				Centralized Controller	ON/OFF
Model	HYRE-V02H	HYRE-Z01H	HYRE-T03H	HYRE-X01H	HYJM-RA10D	HYJ-J01H
Picture						
4-Way Cassette	×	×	○	×	○	○
Mini 4-Way Cassette	×	○	×	×	○	○
1-Way Cassette	×	×	×	○	○	○
2-Way Cassette	○	×	×	×	○	○
Ceiling Ducted Type (AC/DC)	○	×	×	×	○	○
Ceiling Ducted Type (High/Low)	○	×	×	×	○	○
Console	○	×	×	×	○	○
Wall Mounted Type	○	×	×	×	○	○
Ceiling & Floor Type	○	×	×	×	○	○
Floor Concealed Type	○	×	×	×	○	○
All Fresh Air	○	×	×	×	○	○
Heat Recovery Ventilator	×	×	×	×	○	○

Remarks: Standard: ● Optional: ○ Incompatible: ×

Individual Control

Wired Controller

HYXM-VB01A




Mode	Cool/Heat/Auto/Fan/Dry
Timer	24-hour/Weekly schedule/Holiday setting
Maintenance	Error code/Parameter check/Auto test run/ Indoor&Outdoor PCB checking/Self diagnostic function
Louver	Louver setting/Individual louver control/ 3D-air flow
Special function	Breeze mode/Motion sensor/Health/ Hi-Motion/ECO/Quiet/Sleep/Self-cleaning
Fan speed	6
Temperature setting	0.5°C
Main-sub control	•
Air filter cleaning reminding	•
Back light	•
Wireless control available	•

Features

- Size: 86mm × 90mm
- Max. connectable indoor units: 6
- LCD display
- Touch screen
- Language:
VB01A: English, Turkish, Russian,
German, Arabic, spanish
VB01A#01: English, French, Italian,
Dutch, Polish, Thai

Colorful Screen



HYXE-VC01



Features

- Size: 86mm × 86mm
- Max. connectable indoor units: 6
- LCD display with back light
- Touch button
- Flat back-cover for easy mounting

Mode	Cool/Heat/Auto/Fan/Dry
Timer	24-hour timer
Maintenance	Error code/Parameter check/Auto test run/ Self diagnostic function/Indoor & Outdoor PCB checking/ Air filter cleaning reminding/IDU address setting
Louver	7 Louver setting/3D-air flow/ Individual louver control
Special function	Health/ECO/Quiet/Sleep/Self-cleaning
Fan speed	6
Temperature setting	0.5°C accuracy/Display the setting temp. or room temp.
Main-sub control	•
Wireless control available	•
Built-in temperature sensor	•

HYXM-VG01



Features

- Size: 120mm × 120mm
- Max. connectable indoor units: 16
- Touch button
- Language:
Support 11 languages: English, French, German, Italian, Spanish, Dutch, Portuguese, Polish, Turkish, Russian, Arabic


Mode	Cool/Heat/Auto/Fan/Dry
Timer	24-hour/Weekly schedule/Holiday setting
Maintenance	Error code/Parameter check/Auto test run/ Indoor&Outdoor PCB checking/Self diagnostic function
Louver	Louver setting/Individual louver control/ 3D-air flow
Special function	Breeze mode/Motion sensor/Health/ Hi-Motion/ECO/Quiet/Sleep
Fan speed	6
Temperature setting	0.5°C
Main-sub control	•
Air filter cleaning reminding	•
Back light	•
Built-in temperature sensor	•
Built-in receiver kit	•

Two color options are available for you to choose from, catering to different indoor decorations.



Diverse Display Colors

The colors displayed on the controller are based on the operation mode of indoor units, making it easier for users to get the current information of indoor units at a quick glance.




Brand-new Auto Changeover

Auto changeover allows the indoor unit to keep indoor temperature within a certain range by automatically switching the unit operation mode. No need for manual adjustments, our units does it all for you to ensure optimal indoor comfort at all times.



Refrigerant Leakage Alarm

When the refrigerant leaks, an alarm will pop up and the buzzer will sound to make the operation safe and reliable.



HYXE-VA01A



Features

Mode	Cool/Heat/Auto/Fan/Dry
Timer	72-hour
Maintenance	Error code/Parameter check/Auto test run/ Indoor&Outdoor PCB checking/Self diagnostic function
Louver	Louver setting/Individual louver control/3D-air flow
Special function	Breeze mode/Motion sensor/Health/ECO/Quiet/ Sleep/Self-cleaning
Fan speed	6
Temperature setting	0.5°C
Main-sub control	•
Air filter cleaning reminding	•
Back light	•
Built-in temperature sensor	•

- Size: 120mm × 120mm
- Max. connectable indoor units: 16
- LCD display
- Touch button

Wireless Controller

HYE-VD01



Features

Mode	Cool/Heat/Auto/Fan/Dry
Timer	24-hour timer
Maintenance	Auto test run/Self diagnostic function/ Identification of adjacent receiver
Louver	Louver setting/3D-air flow*/Individual louver control
Special function	Health/ECO/Quiet/Sleep/Self-cleaning
Fan speed	6
Temperature setting	1°C accuracy/Display the setting temp. or room temp.
Built-in temperature sensor	•

- Size: 178.6mm × 47.8mm
- LCD display with back light

*When used to control 3D air-flow Panels, an additional receiver kit of wireless control will be necessary.

HYXE-S01H




Features

Mode	Cool/Heat/Auto/Fan/Dry/Quiet
Timer	24-hour
Maintenance	Error code/Parameter check/Auto test run/ Indoor&Outdoor PCB checking/Self diagnostic function
Louver	Louver setting
Fan speed	6
Temperature control	•
Air filter cleaning reminding	•


- Size: 120mm × 70mm
- Max. connectable indoor units: 16
- LCD display
- Touch button

Receiver Kit for Wireless Control-Optional


HYRE-X01H



HYRE-V02H



HYRE-Z01H



HYRE-T03H



Centralized Control

Smart Touch II
HYJM-RA10D



- Cool/Heat/Auto/Fan/Dry
- Remote control with web access
- Support rotation operation setting
- Weekly/Holiday timer
- Error reminder email
- External input/Output function
- ECO/Health/Self-cleaning/Quiet mode setting of the outdoor unit
- Support OTA update (remotely) and USB update (locally)

Features

- 10 inch colorful touch screen
- 1280 × 800 High Resolution
- Size: 170mm × 252mm × 37mm
- Connected quantity:
160 indoor units, 64 outdoor units
- 14 different languages:
English, French, Spanish, German, Italian, Dutch, Polish, Turkish, Russian, Arabic, Portuguese, Vietnamese, Thai, Chinese


Energy Management

Visualized energy management is available through the Smart Touch II, enabling quick access to electricity consumption data and analysis. Utilizing big data analytics, it also provides energy-saving solutions to help you optimize energy usage efficiently.




Access Remotely with Ease

Users have the flexibility to control the air-conditioning system using either the local Smart Touch II or remote web access.




Free Connection

- Max. 4 Smart Touch controllers can be used in one system
- One controller can be connected to max. 160 IDUs, 64 ODU



Future-proof

Ensure you stay up to date with both remote OTA updates and local USB updates.



Ideal for:

Offices, Schools, Factories, Hospitals, Hotels, Restaurants



ON/OFF Controller
HYJ-J01H



- Group control (ON/OFF)
- Indoor unit power OFF reminder
- Indoor units Auto log in
- Error reminder

Features

- Size: 120mm × 120mm
- Max. connectable indoor units: 128
- Max. connectable indoor unit groups: 16
- Touch button

Hi-Cloud Manager

Hisense Intelligent Control Solution



Intelligent Control

What is Hi-Cloud Manager?

Hi-Cloud Manager is the unified access management of Hisense HVAC intelligent control. Users can log in the control web at anytime and anywhere.

Five "Clouds" are embed in the web interface including Hi-Mit Cloud, Smart Touch Cloud, Hi-Dom Cloud, Hi-Checker Cloud, and Distributor Cloud (specially for distributors).

Features:


- Centralized remote control
- Global project map
- Schedule management
- Overview of key data
- Project management
- Energy conservation management
- Operation statistics
- Regional plane navigation
- Alarm and message management

URL <https://hicloudmanager.hijuconn.com>

It's recommended to use the Chrome browser.

Users-friendly

- End user**
Create a customized and smart experience.
- Distributor**
Upgrade service capabilities for the projects under control.
- Service engineer**
Ensure efficient service to improve customers' satisfaction.




Hi-Mit II



Convenient Control

- 12 languages available
- Energy management
- 2-level permission
- Online repair
- 7x24 schedule setting
- Customized scenes setting




Energy management interface

Customized mode interface


Anytime and anywhere, control is in your hands

Brand-new Adapter and App

- Stylish appearance and compact body
- Compatible with VRF, hydro box and heat recovery ventilator
- Supporting OTA update
- Simple and intuitive interfaces




— Commu. Cable
— Electric Cable



Strong Capability

- Up to 64 IDUs and 64 ODUs can be connected to one Hi-Mit II adapter.
- One user account of APP can control 8 adapters, up to 512 IDUs.



Specifications

Model	Power Supply	Max. Current	Power Input	Dimension	Net Weight
HCCS-H64H2C1M	DC 12V	1A	2.4W	91x117x31mm	0.14kg





Hi-Dom III

Features


- Remote control available
- Multilevel user management
- AC control (on-off, mode, temp, air flow)
- AC locked control (running forbidden control, the max. and min. temp and cooling/heating locked)
- Running according to timer
- Malfunction history check
- Running record display
- Data synchronize
- Supporting for external I/O
- 2D navigation
- Electricity consumption allocation
- Multiple languages available
- Standard with Modbus RTU port

● Humanized interaction interface and comfortable user experience.



● The electricity consumption allocation makes it easy for users to allocate total electricity consumption among building occupants. Both segmented tariff and single tariff are available.



● Thanks to the 2D navigation, users can import floor plans and place indoor units in the corresponding rooms, creating a tailored system schematic. Thus all the indoor units can be monitored and controlled intuitively.



● Support operation history data record like the below picture. Also the operation data can be exported to excel format, convenient for customers to read.



- Max. connectable IDUs of one adapter: 160
- Max. connectable of adapters under one computer control: 32
- Max. connectable IDUs under one computer control: 5120

Specifications

	Model	Power Supply	Dimension (LxWxD)	Note
Adapter	HCCS-H160H2C2YM	12V	180x115.4x64.5mm	With electric charging function
	HCCS-H160H2C2NM	12V	180x115.4x64.5mm	Without electric charging function



Intelligent service tool, improves your service

Hi-Checker is a plug and play service tool, with which service engineers can access the system and monitor operation status or data, very convenient for system communication and maintenance. Besides, it features cloud-based management, easy to access operation status remotely.



Small and Portable Body



Remote Access



Black Box Function



Powerful Charts



OTA Update

Easy to Use


- Compact size which allows high portability and space saving.
- Capable to slot in a 32G memory card for data collection and storage. Also the memory card and card reader are standard with Hi-Checker.
- Multiple choices of power supply types. It can be powered by the standard adapter (DC 5V), computer or power bank.
- Support OTA update, ensuring the software is always up to date.



Easy to Access

4 Ways to Access the Operation Data

- Conventional connection type. The simplest and reliable way by just connecting the Hi-Checker to your computer directly through USB.
- Internet connection type. Be connected to a stable Wi-Fi signal to achieve operation data and status monitoring anytime and anywhere.
- Hotspot connection type. Be connected to a temporary hotspot signal from the smartphone, allowing the Hi-Checker to remotely monitor the operation data when there is no stable Wi-Fi signal on site.
- SD card storage type. Hi-Checker equipped with SD card can be connected to the air conditioning system all the time, so that all the operation data can be stored in the card for later analysis.



Easy to Understand


- Powerful and detailed chart analysis on the operation data, allowing users to determine the system condition easily. Together with the smart system diagram, it is interesting and easier for maintenance.
- Users can export the professional report either in .csv or .pdf format, very user-friendly.



Specifications

Mode	Size (LxWxH)mm	Net Weight (g)	Power Supply	Connectable IDUs
HCCS-H64H2C2M	138x68x28	130	5V=500mA	160

Building Management System



KNX®



KNX gateway	HS-RC-KNX-1i
Power Supply	DC, 29V
Max. Number of Connectable Indoor Units	1
Dimension (H x W x D)	70 x 70 x 28mm
Features	<ul style="list-style-type: none"> ○ Standard data point types ○ Error code ○ Directly control of all indoor units ○ Air filter reminder ○ Running hours counter

Modbus®



Modbus gateway	HCPC-H2M4C
Power Supply	DC, 12V
Max. Number of Connectable Indoor Units	160
Dimension (H x W x D)	50 x 170 x 220mm
Features	<ul style="list-style-type: none"> ○ On-Off setting ○ Temperature setting ○ Operating mode setting ○ Inlet air temperature monitoring ○ Airflow setting and monitoring ○ All units On-Off control ○ Alarm monitoring and code display ○ Humidity control

Mini Modbus®



MiniModbus gateway	HCPC-H2M5C
Power Supply	DC, 12V
Max. Number of Connectable Indoor Units	32
Dimension (H x W x D)	27 x 75 x 100mm
Features	<ul style="list-style-type: none"> ○ On-Off Setting ○ Temperature Setting (0.5°C adjustment) ○ Airflow Setting (Auto/3 or 6 fan speed) ○ Humidification control ○ Operating Mode Setting ○ Inlet Air Temp. Monitoring ○ All Units On/Off Control ○ Alarm Monitoring and Code Display

BACnet® & KNX®




BACnet & KNX gateway	HCPC-H1KB16	HCPC-H1KB64
Power Supply	DC, 12~36V / 3W or AC, 24V/0.2A/50~60Hz or DC, 24V(Recommended)	
Max. Number of Connectable Indoor Units	16	64
Dimension (H x W x D)	100x115x100mm	100x115x100mm
Features	<ul style="list-style-type: none"> ○ Central control of all indoor units ○ Indoor unit data monitoring ○ Heat/Dry/Fan/Cool/Auto mode 	<ul style="list-style-type: none"> ○ Control-vane position swing control ○ Function prohibition of wired controller

Note: Bacnet® is a registered trademark of American Society of Heating, Refrigerating and Air-conditioning Engineers (ASHRAE).
 Modbus® is a registered trademark of Schneider Electric.
 KNX® is a registered trademark of Konnex.




Accessories


Hi-Motion

Model	Applicable Models	Picture
HCM-S01E	All types of indoor units	


Motion Sensor

Model	Applicable Models	Picture
HPS-MACN	Mini 4-Way Cassette Type	
HCM-01E	4-Way Cassette Type	

Fresh Air Duct Adapter


Model	Applicable Models	Picture
HFL-56CSA	4-Way Cassette Type and Mini 4-Way Cassette Type	

Humidity Sensor

Model	Applicable Models	Picture
HCHR-S01E	4-Way Cassette Type, Console, Ceiling Ducted Type	

Filter

Filter model	Filter Dimension	Frame Dimension	Application Models	Picture
HF-224L-FE	910 × 432.5mm	1055 × 463mm	AVD-76UX6SEHL	
HF-280L-FE	1100 × 432.5mm	1245 × 463mm	AVD-76/96HJFH AVD-96UX6SFHL	

Filter box model	Dimension (L × W × H) mm	Applicable Models	Applicable Filter	Picture
HFB-96LFGDE	1339 × 384 × 462	AVD-76/96HJFH	High-efficiency filter:HF-96HFGDE Coarse filter:HF-96LFGDE	



Drain Pump

Model	Applicable Models	Power Supply	Picture
HPS-F133E	AVD-07-24HJFH / AVD-07-24HCFCF / AVD-07-24HCFL	220-240V/50Hz	
HPS-F363E	AVD-24HJFH1 / AVD-30-54HJFH / AVD-27-54HCFCF / AVD-27-54HCFL		
HPS-F134E	AVD-07-24H3FCH	208-230V/60Hz	
HPS-F364E	AVD-27-54H3FCH		
HPS-151	All the High/Low Static Pressure Ceiling Ducted Units and All Fresh Air IDU 3-10HP	220-240V/50/60Hz	
HPS-F8103E	AVD-76/96HJFH	220-240V/50/60Hz	


3D Air-flow Panel

Panel Model	Applicable Models	Outer Dimensions (H × W × D)	Picture
HP-CB-NA	Ceiling ducted type (AC low-height) AVE-05/07/09/12*	180 × 740 × 70mm	
HP-DB-NA	Ceiling ducted type (AC low-height) AVE-15/17*	180 × 950 × 70mm	
HP-EB-NA	Ceiling ducted type (AC low-height) AVE-19/22/24*	180 × 1220 × 70mm	

AirPure Kit

Model	Power Supply	Applicable Indoor Units	Picture
HJK-ELZA	AC 1Φ, 220V~240V 50/60Hz	4-Way Cassette Type, Mini 4-Way Cassette Type	
HJK-ELZB	AC 1Φ, 220V~240V 50/60Hz	Ceiling Ducted, Console	

Voltage Protector

Model	Power Supply	Dimension (H × W × D)	Picture
HOPT-EOUPA01	AC 3Φ, 380V~415V/50Hz	295 × 222 × 103mm	


Note: Suitable for Hi-FLEXi S series, S series heat recovery unit and S mavo+ unit.

Piping Connection Kit

There are two types of piping connection kit, non-insulation type and insulation type. The models below are the referenced models without suffix. Please contact with our engineer for detailed model information when ordering.

Manifold Pipe (For outdoor unit)

(Indoor Unit on Left Side)



For S Series Heat Recovery 2 Pipes System

Outdoor Unit	AVWT-290-522FKFSA	AVWT-544FKFSA	AVWT-552-634FKFSA	AVWT-654-794FKFSA	AVWT-816FKFSA	AVWT-824-968FKFSA	AVWT-988-1068FKFSA	AVWT-1088FKFSA
Manifold Pipe1	HFQ-M32F	HFQ-M462F	HFQ-M462F	HFQ-M682F	HFQ-M682F	HFQ-M682F	HFQ-M682F	HFQ-M682F
Manifold Pipe2	-	-	HFQ-M32F	HFQ-M32F	HFQ-M462F	HFQ-M32F	HFQ-M462F	HFQ-M462F
Manifold Pipe3	-	-	-	-	-	HFQ-M32F	HFQ-M32F	HFQ-M462F

For S Series Heat Recovery 3 Pipes System

Outdoor Unit	AVWT-290-344FKFSA	AVWT-360-522FKFSA	AVWT-544FKFSA	AVWT-552FKFSA	AVWT-570-634FKFSA	AVWT-654-794FKFSA	AVWT-816FKFSA	AVWT-824-968FKFSA	AVWT-988-1068FKFSA	AVWT-1088FKFSA
Manifold Pipe1	HFQ-M212F	HFQ-M302F	HFQ-M462XF	HFQ-M462XF	HFQ-M462XF	HFQ-M682XF	HFQ-M682XF	HFQ-M682XF	HFQ-M682XF	HFQ-M682XF
Manifold Pipe2	-	-	-	HFQ-M212F	HFQ-M302F	HFQ-M302F	HFQ-M462XF	HFQ-M302F	HFQ-M462XF	HFQ-M462XF
Manifold Pipe3	-	-	-	-	-	-	-	HFQ-M302F	HFQ-M302F	HFQ-M462XF

For S Series System

Outdoor Unit	AVWT-290-422HKSS	AVWT-444-544HKSS	AVWT-552-634HKSS	AVWT-654HKSS	AVWT-676-816HKSS	AVWT-824-886HKSS	AVWT-908-1088HKSS
Manifold Pipe1	HFQ-M32F	HFQ-M462F	HFQ-M462F	HFQ-M682F	HFQ-M682F	HFQ-M682F	HFQ-M682F
Manifold Pipe2	-	-	HFQ-M32F	HFQ-M32F	HFQ-M462F	HFQ-M462F	HFQ-M462F
Manifold Pipe3	-	-	-	-	-	HFQ-M32F	HFQ-M462F

For S mavo+ Series System

Outdoor Unit	AVWT-290-422HKFSEA	AVWT-444-544HKFSEA	AVWT-552-634HKFSEA	AVWT-654-696HKFSEA	AVWT-714-816HKFSEA	AVWT-824-886HKFSEA	AVWT-908-1088HKFSEA
Manifold Pipe1	HFQ-M32F	HFQ-M462F	HFQ-M462F	HFQ-M682F	HFQ-M682F	HFQ-M682F	HFQ-M682F
Manifold Pipe2	-	-	HFQ-M32F	HFQ-M32F	HFQ-M462F	HFQ-M462F	HFQ-M462F
Manifold Pipe3	-	-	-	-	-	HFQ-M32F	HFQ-M462F

For X3 Series System

Outdoor Unit	AVWT-172-229UESZX	AVWT-250-307UESZX	AVWT-324-386UESZX	AVWT-404-460UESZX	AVWT-480-620UESZX
Manifold Pipe1	HFQ-M22F	HFQ-M32F	HFQ-M32F	HFQ-M32F	HFQ-M462F
Manifold Pipe2	-	-	HFQ-M22F	HFQ-M32F	HFQ-M32F
Manifold Pipe3	-	-	-	-	HFQ-M32F

For W Series 2 Pipes System

Outdoor Unit	AVWT-210-AVWT-280(22HP-24HP)	AVWT-250-AVWT-380(26HP-40HP)	AVWT-400-AVWT-570(42HP-60HP)
Manifold Pipe1	HFQ-M22F	HFQ-M32F	HFQ-M32F
Manifold Pipe2	-	-	HFQ-M32F

For W Series 3 Pipes Heat Recovery System

Outdoor Unit	AVWT-202-AVWT-212(22HP-24HP)	AVWT-250-AVWT-344(26HP-36HP)	AVWT-360-AVWT-380(38HP-40HP)	AVWT-400-AVWT-570(42HP-60HP)
Manifold Pipe1	HFQ-M202F	HFQ-M212F	HFQ-M302F	HFQ-M302F
Manifold Pipe2	-	-	-	HFQ-M302F

Branch Pipe (For indoor unit)

First Branch Pipe

For S Series Heat Recovery 2 Pipes System

Outdoor Unit HP	8 to 10	12 to 16	18 to 24	26 to 54	56 to 66	68 to 112
Branch Pipe	HFQ-102F	HFQ-162F	HFQ-242F	HFQ-302F	HFQ-462F	HFQ-682F

For S Series Heat Recovery 3 Pipes System

Outdoor Unit HP	8 to 10	12 to 16	18 to 24	26 to 36	38 to 54	56 to 66	68 to 112
Branch Pipe	HFQ-M282F	HFQ-M452F	HFQ-M562F	HFQ-M692F	HFQ-M902F	HFQ-462XF	HFQ-682XF

For S/S mavo+ Series System

Outdoor Unit HP	8 to 10	12 to 16	18 to 24	26 to 44	46 to 66	68 to 112
Branch Pipe	HFQ-102F	HFQ-162F	HFQ-242F	HFQ-302F	HFQ-462F	HFQ-682F

For X3 Series System

Outdoor Unit HP	8 to 10	12 to 16	18 to 24	26 to 44	46 to 66	68 to 112
Branch Pipe	HFQ-102F	HFQ-162F	HFQ-242F	HFQ-302F	HFQ-462F	HFQ-682F

First Branch Pipe~Last Branch Pipe

For S Series Heat Recovery 2 Pipes System

Total Indoor Unit Hp	Lower than 6	6 to 8.99	9 to 11.99	12 to 15.99	16 to 17.99	18 to 25.99	26 to 35.99	36 to 55.99	56 to 57.99	58 to 67.99	Over 68
Gas (mm)	15.88	19.05	22.2	25.4	28.6	28.6	31.75	38.1	41.3	44.5	50.8
Liquid (mm)	9.53	9.53	9.53	12.7	12.7	15.88	19.05	19.05	22.2	22.2	25.4
Branch Pipe	HFQ-102F	HFQ-102F	HFQ-102F	HFQ-162F	HFQ-162F	HFQ-242F	HFQ-302F	HFQ-302F	HFQ-462F	HFQ-462F	HFQ-682F

For S Series Heat Recovery System

Total Indoor Unit Hp	Lower than 6	6 to 8.99	9 to 11.99	12 to 15.99	16 to 17.99	18 to 21.99	22 to 25.99	26 to 35.99	36 to 55.99	56 to 57.99	58 to 67.99	Over 68
Low Pressure Gas (mm)	15.88	19.05	22.2	25.4	28.6	28.6	28.6	31.75	38.1	41.3	44.5	50.8
High/Low Pressure Gas (mm)	12.7	15.88	19.05	22.2	22.2	22.2	25.4	28.6	31.75	38.1	41.3	44.5
Liquid(mm)	9.53	9.53	9.53	12.7	12.7	15.88	15.88	19.05	19.05	22.2	22.2	25.4
Branch Pipe	HFQ-M142F	HFQ-M282F	HFQ-M282F	HFQ-M452F	HFQ-M562F	HFQ-M562F	HFQ-M692F	HFQ-M692F	HFQ-M902F	HFQ-462XF	HFQ-462XF	HFQ-462XF

For S/S mavo+ Series System

Total Indoor Unit Hp	Lower than 6	6 to 8.99	9 to 11.99	12 to 15.99	16 to 17.99	18 to 25.99	26 to 33.99	34 to 45.99	46 to 58.99	59 to 68.99	Over 69
Gas (mm)	15.88	19.05	22.2	25.4	28.6	28.6	31.75	38.1	41.3	44.5	50.8
Liquid (mm)	9.53	9.53	9.53	12.7	12.7	15.88	19.05	19.05	22.2	22.2	25.4
Branch Pipe	HFQ-102F	HFQ-102F	HFQ-102F	HFQ-162F	HFQ-162F	HFQ-242F	HFQ-302F	HFQ-302F	HFQ-462F	HFQ-462F	HFQ-682F

For X3 Series System

Total Indoor Unit Hp	Lower than 6	6 to 8.99	9 to 11.99	12 to 15.99	16 to 17.99	18 to 25.99	26 to 33.99	34 to 45.99	46 to 58.99	59 to 68.99	Over 69
Gas (mm)	15.88	19.05	22.2	25.4	28.6	28.6	31.75	38.1	41.3	44.5	50.8
Liquid (mm)	9.53	9.53	9.53	12.7	12.7	15.88	19.05	19.05	22.2	22.2	25.4
Branch Pipe	HFQ-102F	HFQ-102F	HFQ-102F	HFQ-162F	HFQ-162F	HFQ-242F	HFQ-302F	HFQ-302F	HFQ-462F	HFQ-462F	HFQ-682F

Last Branch Pipe~Indoor Unit

Indoor Unit	Pipe Size (φmm)		Max. Liquid Pipe Length
	Gas Pipe	Liquid Pipe	
7kBtu/h~14kBtu/h	12.70	6.35 ^{**}	40
17kBtu/h~18kBtu/h	15.88	6.35 ^{**}	40
22kBtu/h~54kBtu/h	15.88	9.53	40
76kBtu/h	19.05	9.53	40
96kBtu/h	22.20	9.53	40

Note: 1. When liquid pipe length of indoor unit (07-18kBtu/h) is more than 15m, please change the liquid pipe dimension from φ6.35 into φ9.53.

Manifold Pipe Parameter

Unit: mm, ID: Inner Diameter, OD: Outer Diameter.

Model	Gas Line	Liquid Line	Reducer for Gas Line	Reducer for Liquid Line
HFQ-M22F#E HFQ-M22F#ES				—
HFQ-M32F#E HFQ-M32F#ES				—

Manifold Pipe Parameter

Model	Gas Line	Liquid Line	Reducer for Gas Line	Reducer for Liquid Line
HFQ-M462F#E HFQ-M462F#ES				
HFQ-M682F#E HFQ-M682F#ES				—

Model	Low Pressure Gas Line	High Pressure Gas Line	Liquid Line	Reducer for Low Pressure Gas Line	Reducer for High Pressure Gas Line	Reducer for Liquid Line
HFQ-M202F#E						—
HFQ-M212F#E						—
HFQ-M302F#E						—
HFQ-M462XF#ES						
HFQ-M682XF#ES						

Note: The model with #E stands for non-insulation type, while with #ES represents insulation type.

Branch Pipe Parameter

Model	Low Pressure Gas Line	High Pressure Gas Line	Liquid Line	Reducer for Low Pressure Gas Line	Reducer for High Pressure Gas Line	Reducer for Liquid Line
HFQ-M142F#E				—	—	
HFQ-M282F#E				—	—	
HFQ-M452F#E						
HFQ-M562F#E						
HFQ-M692F#E						
HFQ-M902F#E						
HFQ-462XF#ES						
HFQ-682XF#ES						

Note: The model with #E stands for non-insulation type, while with #ES represents insulation type.

Branch Pipe Parameter

Model	Gas Line	Liquid Line	Reducer for Gas Line	Reducer for Liquid Line
HFQ-052F#E			—	—
HFQ-102F#E HFQ-102F#ES			—	
HFQ-162F#E HFQ-162F#ES				
HFQ-242F#E HFQ-242F#ES				
HFQ-302F#E HFQ-302F#ES				
HFQ-462F#E HFQ-462F#ES				
HFQ-682F#E HFQ-682F#ES				

Note: The model with #E stands for non-insulation type, while with #ES represents insulation type.

RELIABILITY
EFFICIENCY
COMFORT
FLEXIBILITY
OUTDOOR UNIT
INDOOR UNIT
CONTROL SYSTEM
ACCESSORY